

CHICKEN

A practical and portable Scheme system
User's Manual
Version 1 Build 43

Felix L. Winkelmann

Copyright © 2000-2004, Felix L. Winkelmann All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of the author nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS “AS IS” AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES LOSS OF USE, DATA, OR PROFITS OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Table of Contents

1	Introduction	2
2	Basic mode of operation	3
3	Using the compiler	4
3.1	Command line format	4
3.2	Runtime options	10
3.3	An example	11
3.4	Extending the compiler	13
3.5	Distributing compiled C files	14
4	Using the interpreter	15
4.1	Command line format	15
4.2	Writing Scheme scripts	16
4.3	Toplevel commands	18
4.4	Macros and procedures implemented in the interpreter	18
5	Supported language	21
5.1	Deviations from the standard	21
5.2	Extensions to the standard	22
5.3	Non standard read syntax	23
5.4	Non-standard macros and special forms	25
5.4.1	Making extra libraries and extensionsd available..	25
5.4.2	Binding forms for optional arguments	26
5.4.3	Other binding forms	27
5.4.4	Substitution forms and macros	28
5.4.5	Conditional forms	29
5.4.6	Record structures	30
5.4.7	Other forms	30
5.5	Declarations	32
5.6	Parameters	35
5.7	Unit library	36
5.7.1	Arithmetic	36
5.7.2	File Input/Output	38
5.7.3	Files	38
5.7.4	String ports	39
5.7.5	Feature identifiers	39
5.7.6	Keywords	39
5.7.7	Exceptions	40
5.7.8	Environment information and system interface ...	42
5.7.9	Execution time	43
5.7.10	Interrupts and error-handling	44

5.7.11	Garbage collection	45
5.7.12	Other control structures	45
5.7.13	String utilities	46
5.7.14	Generating uninterned symbols	46
5.7.15	Standard Input/Output	46
5.7.16	User-defined named characters	46
5.7.17	Vectors	47
5.7.18	The <i>unspecified</i> value	47
5.7.19	call/cc	47
5.8	Unit eval	47
5.8.1	Loading code	47
5.8.2	Read-eval-print loop	48
5.8.3	Macros	49
5.8.4	Loading extension libraries	49
5.8.5	Reader extensions	50
5.8.6	Eval	51
5.9	Unit extras	51
5.9.1	Lists	51
5.9.2	String-port extensions	52
5.9.3	Formatted output	53
5.9.4	Hash tables	53
5.9.5	Queues	54
5.9.6	Sorting	55
5.9.7	Random numbers	56
5.9.8	Input/Output extensions	56
5.9.9	Strings	58
5.9.10	Combinators	59
5.9.11	Binary searching	61
5.10	Unit srfi-1	61
5.11	Unit srfi-4	61
5.12	Unit srfi-13	62
5.13	Unit srfi-14	62
5.14	Unit srfi-25	63
5.15	Unit match	63
5.16	Unit regex	64
5.17	Unit syntax-case	66
5.18	Unit srfi-18	67
5.19	Unit format	68
5.20	Unit posix	68
5.20.1	Directories	69
5.20.2	Pipes	69
5.20.3	Fifos	71
5.20.4	File descriptors and low-level I/O	71
5.20.5	Retrieving file attributes	73
5.20.6	Changing file attributes	73
5.20.7	Processes	74
5.20.8	Symbolic links	75
5.20.9	Permissions, owners, users and groups	75

5.20.10	Record locking	77
5.20.11	Signal handling	78
5.20.12	Environment access	79
5.20.13	Memory mapped I/O	79
5.20.14	Time routines	80
5.20.15	<i>Raw</i> exit	81
5.20.16	ERRNO values	81
5.20.17	Finding files	81
5.20.18	Getting the hostname and system information ..	82
5.20.19	Setting a files buffering mode	82
5.20.20	Terminal ports	82
5.20.21	How Scheme procedures relate to UNIX C functions	82
5.21	Unit <i>utils</i>	86
5.21.1	Pathname operations	86
5.21.2	Temporary files	87
5.21.3	Deleting a file without signalling an error	87
5.21.4	Iterating over input lines and files	87
5.21.5	Executing shell commands with <i>formatstring</i> and error checking	87
5.21.6	Reading a file's contents	88
5.22	Unit <i>tcp</i>	88
5.23	Unit <i>srfi-37</i>	89
5.24	Unit <i>lolevel</i>	90
5.24.1	Foreign pointers	91
5.24.2	Tagged pointers	93
5.24.3	Extending procedures with data	93
5.24.4	Bytevectors	94
5.24.5	Data in unmanaged memory	96
5.24.6	Locatives	97
5.24.7	Accessing toplevel variables	98
5.24.8	Low-level data access	99
5.24.9	Procedure-call- and variable reference hooks ...	100
5.24.10	Magic	100
5.25	Unit <i>tinyclos</i>	101
5.25.1	Defining forms	101
5.25.2	Base language	102
5.25.3	Introspection	103
5.25.4	Intercessory protocol	104
5.25.5	Additional protocol	105
5.25.6	Utility procedures	105
5.25.7	Builtin classes	105

6	Interface to external functions and variables	109
6.1	Accessing external objects	109
6.2	Foreign type specifiers	111
6.3	Entry points	115
6.4	Callbacks	121
6.5	Locations	122
6.6	Other support procedures	123
6.7	The <i>Easy</i> Foreign Function Interface	124
6.7.1	#> ... <# Syntax	126
6.7.2	General operation	127
6.7.3	Pseudo declarations	127
6.7.4	Grammar	131
6.7.5	C notes	135
6.7.6	C++ notes	135
6.8	C interface	136
7	chicken-setup	141
7.1	Extension libraries	141
7.2	Installing extensions	141
7.3	Creating extensions	141
7.4	Procedures and macros available in setup scripts	141
7.5	Examples for extensions	142
7.6	chicken-setup reference	145
8	Additional files	147
8.1	srfi-13-syntax.scm	147
8.2	chicken-highlevel-macros.scm	147
8.3	chicken-more-macros.scm	147
8.4	chicken-ffi-macros.scm	147
8.5	chicken-entry-points.scm	148
8.6	chicken-default-entry-points.scm	148
8.7	test-infrastructure.scm	148
8.7.1	The Test Package Macro API	148
8.7.2	The Test Case Macro API	149
8.7.3	The Expectation Macro API	150
8.7.4	Result Object API	153
8.7.5	Test Package Result Object API	153
8.7.6	Test Case Result Object API	154
8.7.7	Expect Result Object API: Single Clause Style Expectation	154
8.7.8	Expect Result Object API: Equivalence Style Expectation	155
8.7.9	Expect Result Object API: Tolerance Style Expectation	157
8.7.10	Various Helper API	158
8.7.11	Termination API	158

8.7.12	Destructor Object API.....	159
8.7.13	Todo API.....	160
8.7.14	Gloss API	161
8.7.15	Skip API	161
8.7.16	Side Effect API.....	162
8.7.17	Miscellaneous API.....	163
8.7.18	Analysis of the Result Tree.....	163
8.7.19	Output Generation API.....	163
8.7.20	Example Usages of the Test Suite Infrastructure	164
9	Data Representation	167
10	Bugs and limitations	169
11	Acknowledgements	170
	Bibliography	172
	Index	173

1 Introduction

CHICKEN is a compiler that translates Scheme source files into C, which in turn can be fed to a C-compiler to generate a standalone executable. This principle, which is used by several existing compilers, achieves high portability because C is implemented on nearly all available platforms.

This package is distributed under the BSD license and as such is free to use and modify. An interpreter is also available and can be used as a scripting environment or for testing programs before compilation.

The method of compilation and the design of the runtime-system follow closely Henry Baker's *CONS Should Not CONS Its Arguments, Part II: Cheney on the M.T.A.* paper and expose a number of interesting properties: consing (creation of data on the heap) is relatively inexpensive, because a generational garbage collection scheme is used, in which short-lived data structures are reclaimed extremely quickly. Moreover, **call-with-current-continuation** is practically for free and CHICKEN does not suffer under any performance penalties if first-class continuations are used in complex ways. The generated C code is fully tail-recursive.

Some of the features supported by CHICKEN:

- SRFIs 0, 1, 2, 4, 6, 7, 8, 9, 10, 13, 14, 16, 18, 22, 23, 25, 28, 30, 37 and 39.
- **syntax-case** highlevel macros
- Lightweight threads based on first-class continuations
- Pattern matching with Andrew Wright's **match** package
- Record structures
- An object system with multiple inheritance, multimethods and a meta-object protocol
- Extended comment- and string-literal syntaxes
- Libraries for regular expressions, string handling, Common LISP style **format**, UNIX system calls and extended data structures
- Create interpreted or compiled shell scripts written in Scheme for UNIX or Windows
- Compiled C files can be easily distributed
- Allows the creation of fully self-contained statically linked executables
- On systems that support it, compiled code can be loaded dynamically

2 Basic mode of operation

The compiler translates Scheme source code into fairly portable C that can be compiled and linked with most available C compilers. CHICKEN supports the generation of executables and libraries, linked either statically or dynamically. Compiled Scheme code can be loaded dynamically, or can be embedded in applications written in other languages. Separate compilation of modules is fully supported.

The most portable way of creating separately linkable entities is supported by so-called *units*. A unit is a single compiled object module that contains a number of toplevel expressions that are executed either when the unit is the *main* unit or if the unit is *used*. To use a unit, the unit has to be *declareed* as used, like this:

```
(declare (uses UNITNAME))
```

The toplevel expressions of used units are executed in the order in which the units appear in the **uses** declaration. Units may be used multiple times and **uses** declarations may be circular (the unit is initialized at most once). To compile a file as a unit, add a **unit** declaration:

```
(declare (unit UNITNAME))
```

When compiling different object modules, make sure to have one main unit. This unit is called initially and initializes all used units before executing its toplevel expressions. The main-unit has no **unit** declaration.

Another method of using definitions in separate source files is to *include* them. This simply inserts the code in a given file into the current file:

```
(include "FILENAME")
```

One important thing: macro definitions are only available when processed by **include** or **visit**. Macro definitions in separate units are not available, since they are defined at compile time, i.e the time when that other unit was compiled (macros defined using the low-level macro system can optionally be available at runtime, see **define-macro** in [Section 5.4.4 \[Substitution forms and macros\]](#), page 28).

On platforms that support dynamic loading of compiled code (like Windows and most ELF based systems like Linux or BSD), it is not necessary to use unit declarations. Here code can be compiled into a shared object (**.so**) and loaded dynamically into a running application.

3 Using the compiler

The interface to `chicken` is intentionally simple. System dependent makefiles, shell-scripts or batch-files should perform any necessary steps before and after invocation of `chicken`. On UNIX-compatible systems, a shell script named `chicken-config` is supplied that emits the correct options for the host system's C compiler. Enter

```
chicken-config -help
```

on the command line for a list of available options. On most UNIX systems, a Scheme script named `csc` provides a much simpler interface to the Scheme- and C-compilers and linker. Enter

```
csc -help
```

on the command line for more information. A batch-file (`csc.bat`) with the same functionality is also available for Windows platforms. The Windows version of `csc` (`csc.bat`) does not accept more than 8 arguments.

3.1 Command line format

```
chicken FILENAME {OPTION}
```

`FILENAME` is the complete pathname of the source file that is to be translated into C. A filename argument of “-” specifies that the source text should be read from standard input. Note that the filename has to be the first argument to `chicken`. Possible options are:

```
-analyze-only
```

Stop compilation after first analysis pass.

```
-benchmark-mode
```

Equivalent to `-debug-level 0 -optimize-level 3 -fixnum-arithmetic -disable-interrupts -block -lambda-lift`.

```
-block
```

Enable block-compilation. When this option is specified, the compiler assumes that global variables are not modified outside this compilation-unit. Specifically, toplevel bindings are not seen by `eval` and unused toplevel bindings are removed.

```
-case-insensitive
```

Enables the reader to read symbols case insensitive. The default is to read case sensitive (in violation of R5RS). This option registers the `case-insensitive` feature identifier.

```
-check-syntax
```

Aborts compilation process after macro-expansion and syntax checks.

```
-compress-literals THRESHOLD
```

Compiles quoted literals that exceed the size `THRESHOLD` as strings and parse the strings at run-time. This reduces the size of the code and speeds up compile-times of the host C compiler, but has a small run-time performance penalty. The size of a literal is computed by counting recursively the objects in the

literal, so a vector counts as 1 plus the count of the elements, a pair counts as the counts of the car and the cdr, respectively. All other objects count 1.

`-debug MODES`

Enables one or more compiler debugging modes. `MODES` is a string of characters that select debugging information about the compiler that will be printed to standard output.

<i>t</i>	show time needed for compilation
<i>b</i>	show breakdown of time needed for each compiler pass
<i>o</i>	show performed optimizations
<i>r</i>	show invocation parameters
<i>s</i>	show program-size information and other statistics
<i>a</i>	show node-matching during simplification
<i>p</i>	show execution of compiler sub-passes
<i>l</i>	show lambda-lifting information
<i>m</i>	show GC statistics during compilation
<i>n</i>	print the line-number database
<i>c</i>	print every expression before macro-expansion
<i>e</i>	lists all exported toplevel bindings
<i>x</i>	display information about experimental features
<i>D</i>	when printing nodes, use node-tree output
<i>N</i>	show the real-name mapping table
<i>U</i>	show expressions after the secondary user pass
<i>O</i>	show database before lambda-lifting pass
<i>L</i>	show expressions after lambda-lifting
<i>F</i>	show output of “easy” FFI parser
<i>P</i>	show execution of outer partitioning
<i>Q</i>	show execution of middle partitioning
<i>R</i>	show execution of inner partitioning
<i>1</i>	show source expressions
<i>2</i>	show canonicalized expressions
<i>3</i>	show expressions converted into CPS
<i>4</i>	show database after each analysis pass
<i>5</i>	show expressions after each optimization pass
<i>6</i>	show expressions after each inlining pass

- 7 show expressions after complete optimization
- 8 show database after final analysis
- 9 show expressions after closure conversion
- debug-level LEVEL**
Selects amount of debug-information. **LEVEL** should be an integer.
 - **-debug-level 0** is equivalent to **-no-trace**.
 - **-debug-level 1** does nothing.
- disable-c-syntax-checks**
Disable basic syntax checking of embedded C code fragments.
- disable-interrupts**
Equivalent to the **(disable-interrupts)** declaration. No interrupt-checks are generated for compiled programs.
- disable-stack-overflow-checks**
Disables detection of stack overflows. This is equivalent to running the compiled executable with the **-:o** runtime option.
- dynamic**
This option should be used when compiling files intended to be loaded dynamically into a running Scheme program.
- epilogue FILENAME**
Includes the file named **FILENAME** at the end of the compiled source file. The include-path is not searched. This option may be given multiple times.
- explicit-use**
Disables automatic use of the units **library**, **eval** and **extras**. Use this option if compiling a library unit instead of an application unit.
- extend FILENAME**
Loads a Scheme source file or compiled Scheme program (on systems that support it) before compilation commences. This feature can be used to extend the compiler. This option may be given multiple times. The file is also searched in the current include path and in the extension-repository.
- feature SYMBOL**
Registers **SYMBOL** to be a valid feature identifier for **cond-expand**.
- ffi**
Compile C/C++ code and generate Scheme bindings. This is effectively equivalent to wrapping the code in **#>! ... <#**.
- ffi-define SYMBOL**
Defines a macro that will be accessible in **foreign-parse** declarations.
- ffi-include-path PATH**
Set include path for “easy” FFI parser.
- fixnum-arithmetic**
Equivalent to **(fixnum-arithmetic)** declaration. Assume all mathematical operations use small integer arguments.

-heap-size NUMBER

Sets a fixed heap size of the generated executable to **NUMBER** bytes. The parameter may be followed by a **M** (**m**) or **K** (**k**) suffix which stand for mega- and kilobytes, respectively. The default heap size is 5 kilobytes. Note that only half of it is in use at every given time.

-heap-initial-size NUMBER

Sets the size that the heap of the compiled application should have at startup time.

-heap-growth PERCENTAGE

Sets the heap-growth rate for the compiled program at compile time (see: **-:hg**).

-heap-shrinkage PERCENTAGE

Sets the heap-shrinkage rate for the compiled program at compile time (see: **-:hs**).

-help

Print a summary of available options and the format of the command line parameters and exit the compiler.

-syntax**-hygienic**

Load “syntax-case” macro package and enable high-level macros in compiled code. This option registers the **hygienic-macros** feature identifier.

-hygienic-at-run-time

Makes hygienic (“syntax-case”) macro system available at run-time. Note that this has a slight overhead, because the hygienic macro definitions have to be loaded. This will only install the standard R5RS macros, plus SRFI-0 (**cond-expand**). To load all further macros, execute:

```
(require-extension chicken-more-macros)
```

-include-path PATHNAME

Specifies an additional search path for files included via the **include** special form. This option may be given multiple times. If the environment variable **CHICKEN_INCLUDE_PATH** is set, it should contain a list of alternative include pathnames separated by “;”. The environment variable **CHICKEN_HOME** is also considered as a search path.

-keyword-style STYLE

Enables alternative keyword syntax, where **STYLE** may be either **prefix** (as in Common Lisp), **suffix** (as in DSSSL) or **none**. Any other value is ignored. The default is **suffix**. If **-strict** or **-strict-reader** is specified, then the keyword style is set to **none**.

-lambda-lift

Enable the optimization known as lambda-lifting.

-no-trace

Disable generation of tracing information. If a compiled executable should halt due to a runtime error, then a list of the name and the line-number (if available)

of the last procedure calls is printed, unless `-no-trace` is specified. With this option the generated code is slightly faster.

`-no-feature SYMBOL`

Unregisters feature identifier `SYMBOL`.

`-no-warnings`

Disable generation of compiler warnings.

`-nursery NUMBER -stack-size NUMBER`

Sets the size of the first heap-generation of the generated executable to `NUMBER` bytes. The parameter may be followed by a M (m) or K (k) suffix. The default stack-size depends on the target platform.

`-optimize-leaf-routines`

Enable leaf routine optimization.

`-optimize-level LEVEL`

Enables certain sets of optimization options. `LEVEL` should be an integer.

- `-optimize-level 0` does nothing.
- `-optimize-level 1` is equivalent to `-optimize-leaf-routines`
- `-optimize-level 2` is equivalent to `-optimize-leaf-routines -usual-integrations`
- `-optimize-level 3` is equivalent to `-optimize-leaf-routines -usual-integrations -unsafe`

`-output-file FILENAME`

Specifies the pathname of the generated C file. Default is `FILENAME.c`.

`-postlude EXPRESSIONS`

Add `EXPRESSIONS` after all other toplevel expressions in the compiled file. This option may be given multiple times. Processing of this option takes place after processing of `-epilogue`.

`-prelude EXPRESSIONS`

Add `EXPRESSIONS` before all other toplevel expressions in the compiled file. This option may be given multiple times. Processing of this option takes place before processing of `-prologue`.

`-profile`

Instruments the source code to count procedure calls and execution times. After the program terminates (either via an explicit `exit` or implicitly), profiling statistics are written to a file named `PROFILE`. Each line of the generated file contains a list with the procedure name, the number of calls and the time spent executing it. Use the `chicken-format-profile` program to display the profiling information in a more user-friendly form. Enter `chicken-format-profile` with no arguments at the command line to get a list of available options.

`-prologue FILENAME`

Includes the file named `FILENAME` at the start of the compiled source file. The include-path is not searched. This option may be given multiple times.

- quiet**
Disables output of compile information.
- require-for-syntax NAME**
Loads the extension `NAME` before the compilation process commences.
- r5rs**
Equivalent to `-hygienic -strict`.
- run-time-macros**
Makes low-level macros (compiled without the `-hygienic` option) also available at run-time. By default low-level macros are not available at run-time. Note that highlevel-macros (`syntax-case`) defined in compiled code are never available at run-time.
- split NUMBER**
Splits output into multiple C files that can be compiled separately. The generated C files will be named `filename0`, ..., `filename<NUMBER-1>` with as many files as given in `NUMBER`.
- split-level NUMBER**
Specifies how hard the partitioning algorithm should work:
- 0 Exit after first iteration (quickest)
 - 1 Exit when cost does not decrease by at least one-half (the default)
 - 2 Exit when cost does not change
- strict**
Disable non-standard macros. This option registers the `strict` feature identifier. Implies `-strict-letrec` and `-strict-reader`.
- strict-srfi-0**
Disable non-standard macros except `cond-expand`. This option registers the `strict` feature identifier. Implies `-strict-letrec` and `-strict-reader`.
- strict-reader**
Disables non-standard read syntax. Implies `-case-insensitive`.
- strict-letrec**
Enable fully R5RS compliant `letrec`. This generates slightly less efficient code but preserves standard semantics.
- to-stdout**
Write compiled code to standard output instead of creating a `.c` file.
- unit NAME**
Compile this file as a library unit. Equivalent to
`-prelude "(declare (unit NAME))"`
- unsafe**
Disable runtime safety checks.

-unsafe-libraries

Marks the generated file for being linked with the unsafe runtime system. This should be used when generating shared object files that are to be loaded dynamically. If the marker is present, any attempt to load code compiled with this option will signal an error.

-uses NAME

Use definitions from the library unit **NAME**. This is equivalent to

```
-prelude "(declare (uses NAME))"
```

-usual-integrations

Specifies that standard procedures and certain internal procedures are never redefined, and can be inlined. This is equivalent to declaring `(usual-integrations)`.

-version

Prints the version and some copyright information and exit the compiler.

-verbose

Prints progress information to standard output during compilation.

The environment variable `CHICKEN_OPTIONS` can be set to a string with default command-line options for the compiler.

3.2 Runtime options

After successful compilation a C source file is generated and can be compiled with a C compiler. Executables generated with `CHICKEN` (and the compiler itself) accept a small set of runtime options:

-:?

Shows a list of the available runtime options and exits the program.

-:c

Forces console mode. Currently this is only used in the interpreter (`csi`) to force output of the `#;>` prompt even if `stdin` is not a terminal (for example if running in an `emacs` buffer under Windows).

-:d

Prints some debug-information during startup.

-:hNUMBER

Specifies fixed heap size

-:hiNUMBER

Specifies the initial heap size

-:hgPERCENTAGE

Sets the growth rate of the heap in percent. If the heap is exhausted, then it will grow by `PERCENTAGE`. The default is 200.

- `-:hmNUMBER`
Specifies a maximal heap size. The default is (2GB - 15).
- `-:hsPERCENTAGE`
Sets the shrink rate of the heap in percent. If no more than a quarter of PERCENTAGE of the heap is used, then it will shrink to PERCENTAGE. The default is 50. Note: If you want to make sure that the heap never shrinks, specify a value of 0. (this can be useful in situations where an optimal heap-size is known in advance).
- `-:o`
Disables detection of stack overflows at run-time
- `-:sNUMBER`
Specifies stack size
- `-:tNUMBER`
Specifies symbol table size
- `-:w`
Enables garbage collection of unused symbols. By default unused and unbound symbols are not garbage collected.
- `-:r`
Writes trace output to stdout. This option has no effect with in files compiled with the `-no-trace` or `-debug-level 0` options.

The argument values may be given in bytes, in kilobytes (suffixed with `K` or `k`), in megabytes (suffixed with `M` or `m`), or in gigabytes (suffixed with `G` or `g`). Runtime options may be combined, like `-:dc`, but everything following a `NUMBER` argument is ignored. So `-:wh64m` is OK, but `-:h64mw` will not enable GC of unused symbols.

3.3 An example

To compile a Scheme program (assuming a UNIX-like environment) we perform the following steps:

- Consider this Scheme source file, named `foo.scm`

```
;;; foo.scm

(define (fac n)
  (if (zero? n)
      1
      (* n (fac (- n 1))) ) )

(write (fac 10))
(newline)
```

- Compile the file `foo.scm`
`% chicken foo.scm`
- Compile the generated C file `foo.c`

```
% gcc foo.c -o foo 'chicken-config -cflags -libs'
• Start the compiled program
% foo
3628800
```

If multiple bodies of Scheme code are to be combined into a single executable, then we have to compile each file and link the resulting object files together with the runtime system:

- Consider these two Scheme source files, named `foo.scm` and `bar.scm`

```
;;; foo.scm

(declare (uses bar))

(write (fac 10)) (newline)

;;; bar.scm

(declare (unit bar))

(define (fac n)
  (if (zero? n)
      1
      (* n (fac (- n 1))) ) )
```

- Compile the files `foo.scm` and `bar.scm`

```
% chicken foo.scm
% chicken bar.scm
```
- Compile the generated C files `foo.c` and `bar.c`

```
% gcc -c foo.c 'chicken-config -cflags'
% gcc -c bar.c 'chicken-config -cflags'
```
- Link the object files `foo.o` and `bar.o`

```
% gcc foo.o bar.o -o foo 'chicken-config -libs'
```
- Start the compiled program

```
% foo
3628800
```

The declarations specify which of the compiled files is the main module, and which is the library module. An executable can only have one main module, since a program has only a single entry-point. In this case `foo.scm` is the main module, because it doesn't have a `unit` declaration.

Extensions to the basic CHICKEN runtime libraries are available in a separate utility library (`libsrfi-chicken.[a|so]` and `libstuffed-chicken.[a|so]` on UNIX-like platforms, `libsrfi-chicken.lib` and `libstuffed-chicken.lib` on Windows systems). Whenever you use one or more of the units `format`, `srfi-1`, `srfi-4`, `srfi-13`, `srfi-14`,

`srfi-18`, `srfi-25`, `srfi-37`, `posix`, `utils`, `lolevel`, `tinyclos` or `regex`, then you should add these library to the command line of the C compiler or linker. The compiler driver `csc` and the helper script `chicken-config` will do this automatically.

3.4 Extending the compiler

The compiler supplies a couple of hooks to add user-level passes to the compilation process. Before compilation commences any Scheme source files or compiled code specified using the `-extend` option are loaded and evaluated. The parameters `user-options-pass`, `user-read-pass`, `user-preprocessor-pass`, `user-pass`, `user-pass-2` and `user-post-analysis-pass` can be set to procedures that are called to perform certain compilation passes instead of the usual processing (for more information about parameters see: [Section 5.6 \[Parameters\]](#), page 35).

user-options-pass [parameter]

Holds a procedure that will be called with a list of command-line arguments and should return two values: the source filename and the actual list of options, where compiler switches have their leading `-` (hyphen) removed and are converted to symbols. Note that this parameter is invoked **before** processing of the `-extend` option, and so can only be changed in compiled user passes.

user-read-pass [parameter]

Holds a procedure of three arguments. The first argument is a list of strings with the code passed to the compiler via `-prelude` options. The second argument is a list of source files including any files specified by `-prologue` and `-epilogue`. The third argument is a list of strings specified using `-postlude` options. The procedure should return a list of toplevel Scheme expressions.

user-preprocessor-pass [parameter]

Holds a procedure of one argument. This procedure is applied to each toplevel expression in the source file **before** macro-expansion. The result is macro-expanded and compiled in place of the original expression.

user-pass [parameter]

Holds a procedure of one argument. This procedure is applied to each toplevel expression **after** macro-expansion. The result of the procedure is then compiled in place of the original expression.

user-pass-2 [parameter]

Holds a procedure of three arguments, which is called with the canonicalized node-graph and the analysis database accessors as arguments (see below for an explanation of the accessor arguments). The result is ignored, so this pass has to mutate the node-structure to cause any effect.

user-post-analysis-pass [parameter]

Holds a procedure that will be called after the last performed program analysis. The procedure (when defined) will be called with three arguments: the program database, a getter and a setter-procedure which can be used to access and manipulate the

program database, which holds various information about the compiled program. The getter procedure should be called with two arguments: a symbol representing the binding for which information should be retrieved, and a symbol that specifies the database-entry. The current value of the database entry will be returned or `#f`, if no such entry is available. The setter procedure is called with three arguments: the symbol and key and the new value.

For information about the contents of the program database contact the author.

Loaded code (via the `-extend` option) has access to the library units `extras`, `srfi-1`, `srfi-4`, `utils`, `regex` and the pattern matching macros. The highlevel macro-system and multithreading is not available.

Note that the macroexpansion/canonicalization phase of the compiler adds certain forms to the source program. These extra expressions are not seen by `user-preprocessor-pass` but by `user-pass`.

3.5 Distributing compiled C files

It is relatively easy to create distributions of Scheme projects that have been compiled to C. The runtime system of CHICKEN consists of only two handcoded C files (`runtime.c` and `chicken.h`), plus the file `chicken-config.h`, which is generated by the build process. All other modules of the runtime system and the extension libraries are just compiled Scheme code. For more information, study the CHICKEN source code and/or get in contact with the author.

4 Using the interpreter

CHICKEN provides an interpreter named `csi` for evaluating Scheme programs and expressions.

4.1 Command line format

`csi {FILENAME|OPTION}`

where `FILENAME` specifies a file with Scheme source-code. If the extension of the source file is `.scm`, it may be omitted. The runtime options described in [Section 3.1 \[Compiler command line format\]](#), [page 4](#) are also available for the interpreter. If the environment variable `CSI_OPTIONS` is set to a list of options, then these options are additionally passed to every direct or indirect invocation of `csi`. Please note that runtime options (like `-:...`) can not be passed using this method. The options recognized by the interpreter are:

--

Ignore everything on the command-line following this marker. Runtime options (`-:...`) are still recognized.

-case-insensitive

Enables the reader to read symbols case insensitive. The default is to read case sensitive (in violation of R5RS). This option registers the `case-insensitive` feature identifier.

-batch

Quit the interpreter after processing all command line options.

-eval EXPRESSIONS

Evaluate `EXPRESSIONS`.

-feature SYMBOL

Registers `SYMBOL` to be a valid feature identifier for `cond-expand`.

-help

Write a summary of the available command line options to standard output and exit.

-syntax

-hygienic

Load `syntax-case` macro package and enable high-level macros in interpreted code. This option registers the `hygienic-macros` feature identifier.

-include-path PATHNAME

Specifies an alternative search-path for files included via the `include` special form. This option may be given multiple times. If the environment variable `CHICKEN_INCLUDE_PATH` is set, it should contain a list of alternative include pathnames separated by `“;”`. The environment variable `CHICKEN_HOME` is also considered as a search path.

- keyword-style STYLE**
Enables alternative keyword syntax, where **STYLE** may be either **prefix** (as in Common Lisp) or **suffix** (as in DSSSL). Any other value is ignored.
- no-feature SYMBOL**
Unregisters feature identifier **SYMBOL**.
- no-init**
Do not load initialization-file. If this option is not given and the file ‘`~/csirc`’ exists, then it is loaded before the read-eval-print loop commences.
- no-warnings**
Disables any warnings that might be issued by the reader or evaluated code.
- quiet**
Do not print a startup message.
- r5rs**
Equivalent to **-hygienic -strict**.
- script PATHNAME**
This is equivalent to **-batch -quiet -no-init PATHNAME**. Arguments following **PATHNAME** are available by using **command-line-arguments** and are not processed as interpreter options.
- script-meta PATHNAME**
This is similar to the **-script** option, but the file specified by **PATHNAME** is opened, the first line is treated as containing additional command line options and (after processing all the options) the code from the given file is loaded.
- strict**
Disable non-standard macros. Implies **-strict-letrec** and **-strict-reader**.
- strict-srfi-0**
Disable non-standard macros except **cond-expand**. Implies **-strict-letrec** and **-strict-reader**.
- strict-reader**
Disables non-standard read syntax. Implies **-case-insensitive**.
- strict-letrec**
Enable fully R5RS compliant **letrec**. This generates slightly less efficient code but preserves standard semantics.
- version**
Write the banner with version information to standard output and exit.

4.2 Writing Scheme scripts

- Since UNIX shells use the **#!** notation for starting scripts, the interpreter ignores the first line of a source file, if prefixed by **#!**.

The easiest way is to use the **-script** option like this:

```
% cat foo
#! /usr/local/bin/csi -script
(print (eval (with-input-from-string
              (car (command-line-arguments))
              read)))
```

```
% chmod +x foo
% foo "(+ 3 4)"
7
```

The parameter `command-line-arguments` is set to a list of the parameters that were passed to the Scheme script. Scripts can be compiled to standalone executables (don't forget to declare used library units). Note that the compiler does **not** parse the extra arguments passed to a script via the `-script-meta` option!

To overcome a limitation of UNIX that allows only a single argument to scripts, the `-script-meta` options is provided:

```
% cat foo
#! /usr/local/bin/csi -script-meta
-case-insensitive
(print (with-input-from-string (car (command-line-arguments)) read))
```

```
% chmod +x foo
% foo "FooBar"
"foobar"
```

- CHICKEN implements SRFI-22 but provides no driver programs (`scheme-r4rs`, `scheme-ieee-1178-1990`, `scheme-r5rs` and `scheme-srfi-0`). Scheme scripts can be compiled, the compiler determines language dialect from the invocation line:

```
% cat bar
#! /usr/bin/env scheme-r5rs
(define (main args)
  (write (list->string (reverse (string->list (cadr args)))))
  (newline)
  0)
```

```
% csi -script bar "one two three"
"eerht owt eno"
% chicken bar -quiet
% gcc bar.c 'chicken-config -cflags -libs' -o cbar
% cbar "one two three"
"eerht owt eno"
```

For more information, see the [SRFI-22 document](#)

- Windows and DOS:

CHICKEN supports writing shell scripts in Scheme for these platforms as well, using a slightly different approach. The first example would look like this on Windows:

```
C:>type foo.bat
@;csibatch %0 %1 %2 %3 %4 %5 %6 %7 %8 %9
```

```
(print (eval (with-input-from-string
              (car (command-line-arguments))
              read)))
```

```
C:>foo "(+ 3 4)"
7
```

Like UNIX scripts, batch files can be compiled. Windows batch scripts do not accept more than 8 arguments.

4.3 Toplevel commands

The toplevel loop understands a number of special commands:

<code>,?</code>	Show summary of available toplevel commands.
<code>,NUM</code>	Evaluate NUMth command in history-list
<code>,h</code>	List history of last commands
<code>,l FILENAME</code>	Load file with given FILENAME (may be a symbol or string).
<code>,ln FILENAME</code>	Load file and print result(s) of each top-level expression.
<code>,p EXP</code>	Pretty-print evaluated expression EXP.
<code>,d EXP</code>	Describe result of evaluated expression EXP.
<code>,du EXP</code>	Dump contents of the result of evaluated expression EXP.
<code>,dur EXP N</code>	Dump N bytes of the result of evaluated expression EXP.
<code>,q</code>	Quit the interpreter.
<code>,r</code>	Show system information.
<code>,s STRING-OR-SYMBOL</code>	Execute shell-command.
<code>,t EXP</code>	Evaluate form and print elapsed time.
<code>,x EXP</code>	Pretty-print macroexpanded expression EXP (the expression is not evaluated).

4.4 Macros and procedures implemented in the interpreter

Additional macros and procedures available in the interpreter are:

advise [syntax]

(advise NAME MODE PROC)

Modifies the behavior of the procedures named NAME, according to MODE:

before

Call the procedure PROC before every invocation of NAME, with the same arguments.

after

Call the procedure PROC with the result value(s) of NAME.

around

Call the procedure PROC with the arguments passed to NAME. Additionally the (original) value of NAME is passed as the first argument to PROC.

Only the PROC argument is evaluated. Note that multiple pieces of advice on the same procedure are allowed.

```
#;> (define (fac n)
      (if (zero? n) 1 (* n (fac (sub1 n)))))
#;> (define count 0)
#;> (advise fac before (lambda _ (set! count (add1 count))))
#;> (fac 10)                      ==> 3628800
#;> count                        ==> 11
#;> (advise fac around
      (let ((i 0))
        (define (indent)
          (do ((i i (sub1 i)))
              ((zero? i))
            (write-char #\space)))
        (lambda (f n)
          (indent)
          (print "fac: " n)
          (set! i (add1 i))
          (let ((x (f n)))
            (set! i (sub1 i))
            (indent)
            (print "-> " x)
            x))))
#;> (fac 3)
fac: 3
fac: 2
fac: 1
fac: 0
-> 1
```

```

-> 1
-> 2
-> 6                      ==> 6
#;> count                 ==> 15
#;> (set! count 0)
#;> (unadvise fac)
#;> (fac 10)               ==> 3628800
#;> count                 ==> 0

```

unadvise [syntax]

(unadvise NAME ...)

Removes all pieces of advice from the procedures **NAME** ... and restores their original behavior.

trace [syntax]

(trace NAME ...)

Switches tracing on for the procedures with the given names.

```

#;> (fac 10)               ==> 3628800
#;> (trace fac)
#;> (fac 3)
|(fac 3)
| (fac 2)
|  (fac 1)
|   (fac 0)
|   fac -> 1
|   fac -> 1
| fac -> 2
|fac -> 6                  ==> 6
#;> (untrace fac)
#;> (fac 3)                ==> 6

```

untrace [syntax]

(untrace NAME ...)

Switches tracing of the given procedures off.

\$ [procedure]

(\$ [INDEX])

Returns entry number **INDEX** in the history list.

& [procedure]

(& [INDEX])

Returns result(s) of entry number **INDEX** in the history list.

5 Supported language

5.1 Deviations from the standard

[2] Identifiers are by default case-sensitive.

[4.1.4] Extended DSSSL style lambda lists are supported. DSSSL formal argument lists are defined by the following grammar:

```

<formal-argument-list> ==> <required-formal-argument>*
                           [(#!optional <optional-formal-argument>*)]
                           [(#!rest <rest-formal-argument>)]
                           [(#!key <key-formal-argument>*)]
<required-formal-argument> ==> <ident>
<optional-formal-argument> ==> <ident>
                           | (<ident> <initializer>)
<rest-formal-argument> ==> <ident>
<key-formal-argument> ==> <ident>
                           | (<ident> <initializer>)
<initializer> ==> <expr>

```

When a procedure is applied to a list of actual arguments, the formal and actual arguments are processed from left to right as follows:

1. Variables in required-formal-arguments are bound to successive actual arguments starting with the first actual argument. It shall be an error if there are fewer actual arguments than required-formal-arguments.
2. Next, variables in optional-formal-arguments are bound to any remaining actual arguments. If there are fewer remaining actual arguments than optional-formal-arguments, then variables are bound to the result of the evaluation of initializer, if one was specified, and otherwise to **#f**. The initializer is evaluated in an environment in which all previous formal arguments have been bound.
3. If there is a rest-formal-argument, then it is bound to a list of all remaining actual arguments. The remaining actual arguments are also eligible to be bound to keyword-formal-arguments. If there is no rest-formal-argument and there are no keyword-formal-arguments, then it shall be an error if there are any remaining actual arguments.
4. If **#!key** was specified in the formal-argument-list, there shall be an even number of remaining actual arguments. These are interpreted as a series of pairs, where the first member of each pair is a keyword specifying the argument name, and the second is the corresponding value. It shall be an error if the first member of a pair is not a keyword. It shall be an error if the argument name is not the same as a variable in a keyword-formal-argument, unless there is a rest-formal-argument. If the same argument name occurs more than once in the list of actual arguments, then the first value is used. If there is no actual argument for a particular keyword-formal-argument, then the variable is bound to the result of evaluating initializer if one was specified, and otherwise **#f**. The initializer is evaluated in an environment in which all previous formal arguments have been bound.

It shall be an error for an `<ident>` to appear more than once in a formal-argument-list.

Example:

```
((lambda (x y) x) 3 4 5 6)    =>(3 4 5 6)
((lambda (x y #!rest z) z)
 3 4 5 6)                    => (5 6)
((lambda (x y #!optional z #!rest r #!key i (j 1))
  (list x y z i: i j: j))
 3 4 5 i: 6 i: 7)            => (3 4 5 i: 6 j: 1)
```

[4.1.6] `set!` for unbound toplevel variables is allowed.

[5.2] `define` with a single argument is allowed and initializes the toplevel or local binding to an unspecified value.

[6.2.4] The runtime system uses the numerical string-conversion routines of the underlying C library and so does only understand standard (C-library) syntax for floating-point constants.

[6.2.5] The routines `complex?`, `real?` and `rational?` are identical to the standard procedure `number?`. The procedures `numerator`, `denominator` and `rationalize` are not implemented. Also not implemented are all procedures related to complex numbers.

[6.2.6] The procedure `string->number` does not obey read/write invariance on inexact numbers.

[6.5] Code evaluated in `scheme-report-environment` or `null-environment` still sees non-standard syntax unless running under the interpreter (`csi`) invoked with the `-strict` option.

[6.6.2] The procedure `char-ready?` is handling terminal input ports only under DJGPP correctly. On other platforms it returns always `#t`. The procedure `read` does not obey read/write invariance on inexact numbers.

[6.6.3] The procedures `write` and `display` do not obey read/write invariance to inexact numbers.

5.2 Extensions to the standard

[2.1] Identifiers may contain special characters if delimited with `| ... |`.

[2.3] The brackets `[...]` are provided as an alternative syntax for `(...)`. A number of reader extensions is provided. See [Section 5.3 \[Non standard read syntax\]](#), page 24.

[4] Numerous non-standard macros are provided. See [Section 5.4 \[Non-standard macros and special forms\]](#), page 25 for more information.

[4.2.2] It is allowed for initialization values of bindings in a `letrec` construct to refer to previous variables in the same set of bindings, so

```
(letrec ([foo 123]
  [bar foo] )
  bar)
```

is allowed and returns 123. This extension is not available when strict R5RS `letrec` semantics have been selected (by using the `-strict`, `-strict-srfi-0` or `-strict-letrec` option).

[4.2.3] `(begin)` is allowed in non-toplevel contexts and evaluates to an unspecified value.

[4.2.5] Delayed expressions may return multiple values.

[5.2.2] CHICKEN extends standard semantics by allowing internal definitions everywhere, and not only at the beginning of a body. A set of internal definitions is equivalent to a `letrec` form enclosing all following expressions in the body:

```
(let ([foo 123])
  (bar)
  (define foo 456)
  (baz foo) )

expands into

(let ([foo 123])
  (bar)
  (letrec ([foo 456])
    (baz foo) ) )
```

This extension to the standard semantics is not available in combination with the hygienic (`syntax-case`) macro system. Under the hygienic macro system an error will be signalled when internal definitions occur at a position that is not at the beginning of a body.

[6] CHICKEN provides numerous non-standard procedures. See the manual sections on library units for more information.

[6.3.4] User defined character names are supported. See `char-name` in [Section 5.7.16 \[User-defined named characters\]](#), page 46.

[6.3.5] CHICKEN supports special characters preceded with a backslash “\” in quoted string constants. “\n” denotes the newline-character, “\r” carriage return, “\b” backspace, “\t” TAB and “\xXX” a character with the code XX in hex.

The third argument to `substring` is optional and defaults to the length of the string.

[6.4] `force` called with an argument that is not a promise returns that object unchanged. Captured continuations can be safely invoked inside before- and after-thunks of a `dynamic-wind` form and execute in the outer dynamic context of the `dynamic-wind` form.

[6.5] The second argument to `eval` is optional and defaults to the value of (`interaction-environment`). `scheme-report-environment` and `null-environment` accept an optional 2nd parameter: if not `#f` (which is the default), toplevel bindings to standard procedures are mutable and new toplevel bindings may be introduced.

[6.6.1] if the procedures `current-input-port` and `current-output-port` are called with an argument (which should be a port), then that argument is selected as the new current input- and output-port, respectively. The procedures `open-input-file`, `open-output-file`, `with-input-from-file`, `with-output-to-file`, `call-with-input-file` and `call-with-output-file` accept an optional second (or third) argument which should be one or more keywords, if supplied. These arguments specify the mode in which the file is opened. Possible values are the keywords `#:text`, `#:binary` or `#:append`.

5.3 Non standard read syntax

#| ... |# [read syntax]
A multiline “block” comment. May be nested. Implements [SRFI-30](#))

#,EXPRESSION [read syntax]
Treats EXPRESSION as a comment.

#, (CONSTRUCTORNAME DATUM ...) [read syntax]
Allows user-defined extension of external representations. (For more information see the documentation for [SRFI-10](#))

#'EXPRESSION [read syntax]
An abbreviation for (syntax EXPRESSION).

#\$EXPRESSION [read syntax]
An abbreviation for (location EXPRESSION).

#:SYMBOL [read syntax]
Syntax for keywords. Keywords are symbols that evaluate to themselves, and as such don't have to be quoted.

#<<TAG [read syntax]
Specifies a multiline string constant. Anything up to a line equal to TAG will be returned as a single string:

```
(define msg #<<END
"Hello, world!", she said.
END
)
```

is equivalent to

```
(define msg "\"Hello, world!\", she said.")
```

#<#TAG [read syntax]
Similar to #<<, but allows substitution of embedded Scheme expressions prefixed with # and optionally enclosed in { ... }. Two consecutive #s are translated to a single #:

```
(define three 3)
(display #<#EOF
This is a simple string with an embedded ‘##’ character
and substituted expressions: (+ three 99) ==> #(+ three 99)
(three is "#{three}")
EOF
)
```

prints
This is a simple string with an embedded ‘#’ character
and substituted expressions: (+ three 99) ==> 102
(three is "3")

#> ... <# [read syntax]
Abbreviation for (declare (foreign-declare " ... ")).

`#>? ... <#` [read syntax]
 Abbreviation for `(declare (foreign-parse " ... "))`.

`#>! ... <#` [read syntax]
 Abbreviation for
`(declare`
`(foreign-declare " ... ")`
`(foreign-parse " ... "))`

`#%...` [read syntax]
 Reads like a normal symbol.

`#!...` [read syntax]
 If occurring in the first line of an interpreted or compiled source file, then the `#!` and everything following it are ignored. If occurring anywhere else, reads as a normal symbol. The special (self-evaluating) symbol `#!eof` is read as the end-of-file object.

5.4 Non-standard macros and special forms

5.4.1 Making extra libraries and extensionsd available

require-extension [syntax]
use [syntax]
`(require-extension ID ...)`
`(use ID ...)`

This form does all necessary steps to make the libraries or extensions given in `ID ...` available. It loads syntactic extension, if needed and generates code for loading/linking with core library modules or separately installed extensions. `use` is just a shorter alias for `require-extension`.

During interpretation/evaluation `require-extension` performs one of the following:

- If `ID` names a built in features `chicken srfi-22 srfi-23 srfi-30 srfi-39 srfi-8 srfi-6 srfi-2 srfi-0 srfi-10 srfi-9`, then nothing is done.
- If `ID` names one of syntactic extensions `chicken-match-macros chicken-more-macros chicken-default-entry-points chicken-highlevel-macros test-infrastructure chicken-entry-points chicken-ffi-macros`, then this extension will be loaded.
- If `ID` names one of the core library units shipped with CHICKEN, then a `(load-library 'ID)` will be performed. If one of those libraries define specific syntax (`match srfi-13`), then the required source file defining the syntax will be loaded.
- If `ID` names an installed extension with the `syntax` or `require-at-runtime` attribute, then the equivalent of `(require-for-syntax 'ID)` is performed.
- Otherwise `(require-extension ID)` is equivalent to `(require 'ID)`.

During compilation one of the following happens instead:

- If ID names a built in features `chicken srfi-22 srfi-23 srfi-30 srfi-39 srfi-8 srfi-6 srfi-2 srfi-0 srfi-10 srfi-9`, then nothing is done.
- If ID names one of syntactic extensions `chicken-match-macros chicken-more-macros chicken-default-entry-points chicken-highlevel-macros test-infrastructure chicken-entry-points chicken-ffi-macros`, then this extension will be loaded at compile-time, making the syntactic extensions available in compiled code.
- If ID names one of the core library units shipped with CHICKEN, then a `(declare (uses ID))` is generated. If one of those libraries define specific syntax (`match srfi-13`), then the required source file defining the syntax will be loaded at compile-time, making the syntactic extension available in compiled code.
- If ID names an installed extension with the `syntax` or `require-at-runtime` attribute, then the equivalent of `(require-for-syntax 'ID)` is performed.
- Otherwise `(require-extension ID)` is equivalent to `(require 'ID)`.

To make long matters short - just use `require-extension` and it will normally figure everything out for dynamically loadable extensions and core library units.

5.4.2 Binding forms for optional arguments

:optional [syntax]

`(:optional ARGS DEFAULT)`

Use this form for procedures that take a single optional argument. If `ARGS` is the empty list `DEFAULT` is evaluated and returned, otherwise the first element of the list `ARGS`. It is an error if `ARGS` contains more than one value.

```
(define (incr x . i) (+ x (:optional i 1)))
(incr 10)                ==> 11
(incr 12 5)              ==> 17
```

case-lambda [syntax]

`(case-lambda (LAMBDA-LIST1 EXP1 ...) ...)`

SRFI-16. Expands into a lambda that invokes the body following the first matching lambda-list.

```
(define plus
  (case-lambda
    ((()) 0)
    ((x) x)
    ((x y) (+ x y))
    ((x y z) (+ (+ x y) z))
    (args (apply + args))))

(plus)                ==> 9
(plus 1)              ==> 1
(plus 1 2 3)          ==> 6
```

For more information see the documentation for [SRFI-16](#)

let-optionals [syntax]
let-optionals* [syntax]

```
(let-optionals ARGS ((VAR1 DEFAULT1) ...) BODY ...)
(let-optionals* ARGS ((VAR1 DEFAULT1) ... [RESTVAR]) BODY ...)
```

Binding constructs for optional procedure arguments. **ARGS** should be a rest-parameter taken from a lambda-list. **let-optionals** binds **VAR1 ...** to available arguments in parallel, or to **DEFAULT1 ...** if not enough arguments were provided. **let-optionals*** binds **VAR1 ...** sequentially, so every variable sees the previous ones. If a single variable **RESTVAR** is given, then it is bound to any remaining arguments, otherwise it is an error if any excess arguments are provided.

```
(let-optionals '(one two) ((a 1) (b 2) (c 3))
(list a b c) )                ==> (one two 3)
(let-optionals* '(one two) ((a 1) (b 2) (c a))
(list a b c) )                ==> (one two one)
```

5.4.3 Other binding forms

and-let* [syntax]

```
(and-let* (BINDING ...) EXP1 EXP2 ...)
```

SRFI-2. Bind sequentially and execute body. **BINDING** can be a list of a variable and an expression, a list with a single expression, or a single variable. If the value of an expression bound to a variable is **#f**, the **and-let*** form evaluates to **#f** (and the subsequent bindings and the body are not executed). Otherwise the next binding is performed. If all bindings/expressions evaluate to a true result, the body is executed normally and the result of the last expression is the result of the **and-let*** form. See also the documentation for [SRFI-2](#).

cut [syntax]
cute [syntax]

```
(cut SLOT ...)
(cute SLOT ...)
```

Syntactic sugar for specializing parameters.

define-values [syntax]

```
(define-values (NAME ...) EXP)
```

Defines several variables at once, with the result values of expression **EXP**.

fluid-let [syntax]

```
(fluid-let ((VAR1 X1) ...) BODY ...)
```

Binds the variables **VAR1 ...** dynamically to the values **X1 ...** during execution of **BODY ...**.

let-values [syntax]

```
(let-values (((NAME ...) EXP) ...) BODY ...)
```

Binds multiple variables to the result values of **EXP ...**. All variables are bound simultaneously.

let*-values [syntax]

```
(let*-values (((NAME ...) EXP) ...) BODY ...)
```

Binds multiple variables to the result values of EXP The variables are bound sequentially.

```
(let*-values (((a b) (values 2 3))
              ((p) (+ a b)) )
  p)                               ==> 5
```

letrec-values [syntax]

```
(letrec-values (((NAME ...) EXP) ...) BODY ...)
```

Binds the result values of EXP ... to multiple variables at once. All variables are mutually recursive.

```
(letrec-values (((odd even)
                 (values
                  (lambda (n) (if (zero? n) #f (even (sub1 n))))
                  (lambda (n) (if (zero? n) #t (odd (sub1 n)))) ) ) )
  (odd 17) )                       ==> #t
```

parameterize [syntax]

```
(parameterize ((PARAMETER1 X1) ...) BODY ...)
```

Binds the parameters PARAMETER1 ... dynamically to the values X1 ... during execution of BODY (see also: `make-parameter` in [Section 5.6 \[Parameters\]](#), page 35). Note that PARAMETER may be any expression that evaluates to a parameter procedure.

receive [syntax]

```
(receive (NAME1 ... [. NAMEn]) VALUEEXP BODY ...)
(receive VALUEEXP)
```

SRFI-8. Syntactic sugar for `call-with-values`. Binds variables to the result values of VALUEEXP and evaluates BODY

The syntax

```
(receive VALUEEXP)
```

is equivalent to

```
(receive _ VALUEEXP _)
```

set!-values [syntax]

```
(set!-values (NAME ...) EXP)
```

Assigns the result values of expression EXP to multiple variables.

5.4.4 Substitution forms and macros**define-constant** [syntax]

```
(define-constant NAME CONST)
```

Define a variable with a constant value, evaluated at compile-time. Any reference to such a constant should appear textually **after** its definition. This construct is equivalent to `define` when evaluated or interpreted. Constant definitions should

only appear at toplevel. Note that constants are local to the current compilation unit and are not available outside of the source file in which they are defined. Names of constants still exist in the Scheme namespace and can be lexically shadowed. If the value is mutable, then the compiler is careful to preserve its identity. `CONST` may be any constant expression, and may also refer to constants defined via `define-constant` previously. This form should only be used at top-level.

define-inline

[syntax]

```
(define-inline (NAME VAR ... [. VAR]) BODY ...)
(define-inline NAME EXP)
```

Defines an inline procedure. Any occurrence of `NAME` will be replaced by `EXP` or `(lambda (VAR ... [. VAR]) BODY ...)`. This is similar to a macro, but variable-names and -scope will be correctly handled. Inline substitutions take place **after** macro-expansion. `EXP` should be a lambda-expression. Any reference to `NAME` should appear textually **after** its definition. Note that inline procedures are local to the current compilation unit and are not available outside of the source file in which they are defined. Names of inline procedures still exist in the Scheme namespace and can be lexically shadowed. This construct is equivalent to `define` when evaluated or interpreted. Inline definitions should only appear at toplevel.

define-macro

[syntax]

```
(define-macro (NAME VAR ... [. VAR]) EXP1 ...)
(define-macro NAME (lambda (VAR ... [. VAR]) EXP1 ...))
(define-macro NAME1 NAME2)
```

Define a globally visible macro special form. The macro is available as soon as it is defined, i.e. it is registered at compile-time. If the file containing this definition invokes `eval` and the declaration `run-time-macros` (or the command line option `-run-time-macros`) has been used, then the macro is visible in evaluated expressions during runtime. The second possible syntax for `define-macro` is allowed for portability purposes only. In this case the second argument **must** be a lambda-expression or a macro name. Only global macros can be defined using this form. `(define-macro NAME1 NAME2)` simply copies the macro definition from `NAME2` to `NAME1`, creating an alias.

This form is also available with the `syntax-case` macro system.

5.4.5 Conditional forms**switch**

[syntax]

```
(switch EXP (KEY EXP1 ...) ... [(else EXPn ...)])
```

This is similar to `case`, but a) only a single key is allowed, and b) the key is evaluated.

unless

[syntax]

```
(unless TEST EXP1 EXP2 ...)
```

Equivalent to:

```
(if (not TEST) (begin EXP1 EXP2 ...))
```

when [syntax]

```
(when TEST EXP1 EXP2 ...)
```

Equivalent to:

```
(if TEST (begin EXP1 EXP2 ...))
```

5.4.6 Record structures

define-record [syntax]

```
(define-record NAME SLOTNAME ...)
```

Defines a record type. Call `make-NAME` to create an instance of the structure (with one initialization-argument for each slot). `(NAME? STRUCT)` tests any object for being an instance of this structure. Slots are accessed via `(NAME-SLOTNAME STRUCT)` and updated using `(NAME-SLOTNAME-set! STRUCT VALUE)`.

```
(define-record point x y)
(define p1 (make-point 123 456))
(point? p1)                ==> #t
(point-x p1)                ==> 123
(point-y-set! p1 99)
(point-y p1)                ==> 99
```

define-record-printer [syntax]

```
(define-record-printer (NAME RECORDVAR PORTVAR) BODY ...)
(define-record-printer NAME PROCEDURE)
```

Defines a printing method for record of the type `NAME` by associating a procedure with the record type. When a record of this type is written using `display`, `write` or `print`, then the procedure is called with two arguments: the record to be printed and an output-port.

```
(define-record foo x y z)
(define f (make-foo 1 2 3))
(define-record-printer (foo x out)
  (fprintf out "#,(foo ~S ~S ~S)"
            (foo-x x) (foo-y x) (foo-z x)) )
(define-reader-ctor 'foo make-foo)
(define s (with-output-to-string
  (lambda () (write f))))
s ==> "#,(foo 1 2 3)"
(equal? f (with-input-from-string
  s read))) ==> #t
```

`define-record-printer` works also with [SRFI-9](#) record types.

define-record-type [syntax]

```
(define-record-type NAME (CONSTRUCTOR TAG ...) PREDICATE
  (FIELD ACCESSOR [MODIFIER]) ...)
```

[SRFI-9](#) record types. For more information see the documentation for [SRFI-9](#)

5.4.7 Other forms

assert [syntax]

(assert EXP [STRING ARG ...])

Signal error if EXP evaluates to false. An optional message STRING and arguments ARG ... may be supplied to give a more informative error-message. If compiled in *unsafe* mode (either by specifying the `-unsafe` compiler option or by declaring (`unsafe`)), then this expression expands to an unspecified value.

cond-expand [syntax]

(cond-expand FEATURE-CLAUSE ...)

SRFI-0. Expands by selecting feature clauses. Predefined feature-identifiers are `srfi-0`, `srfi-2`, `srfi-6`, `srfi-8`, `srfi-9`, `srfi-10`, and `chicken`. In `strict-srfi-0` mode only `srfi-0` and `chicken` are defined. If the source file containing this form is currently compiled, the feature `compiling` is defined. For further information, see the documentation for [SRFI-0](#). This form is allowed to appear in non-toplevel expressions.

critical-section [syntax]

(critical-section BODY ...)

Evaluate BODY ... with timer-interrupts temporarily disabled.

ensure [syntax]

(ensure PREDICATE EXP [ARGUMENTS ...])

Evaluates the expression EXP and applies the one-argument procedure PREDICATE to the result. If the predicate returns `#f` an error is signaled, otherwise the result of EXP is returned. If compiled in *unsafe* mode (either by specifying the `-unsafe` compiler option or by declaring (`unsafe`)), then this expression expands to an unspecified value. If specified, the optional ARGUMENTS are used as arguments to the invocation of the error-signalling code, as in (`error ARGUMENTS ...`). If no ARGUMENTS are given, a generic error message is displayed with the offending value and PREDICATE expression.

eval-when [syntax]

(eval-when (SITUATION ...) EXP ...)

Controls evaluation/compilation of subforms. SITUATION should be one of the symbols `eval`, `compile` or `load`. When encountered in the evaluator, and the situation specifier `eval` is not given, then this form is not evaluated and an unspecified value is returned. When encountered while compiling code, and the situation specifier `compile` is given, then this form is evaluated at compile-time. When encountered while compiling code, and the situation specifier `load` is not given, then this form is ignored and an expression resulting into an unspecified value is compiled instead.

The following table should make this clearer:

	in compiled code	In interpreted code
<code>eval</code>	ignore	evaluate
<code>compile</code>	evaluate at compile time	ignore
<code>load</code>	compile as normal	ignore

Note: It is currently not possible to use `define-syntax` or `define` inside `eval-when` forms when hygienic macros are enabled.

include [syntax]

(include STRING)

Include toplevel-expressions from the given source file in the currently compiled/interpreted program. If the included file has the extension `.scm`, then it may be omitted. The file is searched in the current directory and, if not found, in all directories specified in the `-include-path` option.

nth-value [syntax]

(nth-value N EXP)

Returns the Nth value (counting from zero) of the values returned by expression `EXP`.

time [syntax]

(time EXP1 ...)

Evaluates `EXP1 ...` and print elapsed time and memory information. The result of the last expression is returned.

5.5 Declarations

declare [syntax]

(declare DECLSPEC ...)

Process declaration specifiers. Declarations always override any command-line settings. Declarations are valid for the whole compilation-unit (source file), the position of the declaration in the source file can be arbitrary. `DECLSPEC` may be any of the following:

always-bound [declaration specifier]

(always-bound SYMBOL ...)

Declares that the given variables are always bound and accesses to those have not to be checked.

block [declaration specifier]

(block)

Assume global variables are never redefined. This is the same as specifying the `-block` option.

block-global [declaration specifier]

hide [declaration specifier]

(block-global SYMBOL ...)

(hide SYMBOL ...)

Declares that the toplevel bindings for `SYMBOL ...` should not be accessible from code in other compilation units or by `eval`. Access to toplevel bindings declared as block global is also more efficient.

bound-to-procedure [declaration specifier]

(bound-to-procedure SYMBOL ...)

Declares that the given identifiers are always bound to procedure values.

compress-literals [declaration specifier]
 (compress-literals [THRESHOLD [INITIALIZER]])

The same as the `-compress-literals` compiler option. The threshold argument defaults to 50. If the optional argument `INITIALIZER` is given, then the literals will not be created at module startup, but when the procedure with this name will be called.

export [declaration specifier]
 (export SYMBOL ...)

The opposite of `hide`. All given identifiers will be exported and all toplevel variables not listed will be hidden and not be accessible outside of this compilation unit. When the hygienic (`syntax-case`) macro system is used, the exported identifier may also have the form `(MODULE-NAME SYMBOL ...)`, which specifies identifiers to be exported from a module as (undecorated) toplevel variables.

foreign-declare [declaration specifier]
 (foreign-declare STRING ...)

Include given strings verbatim into header of generated file.

foreign-parse [declaration specifier]
 (foreign-parse STRING ...)

Parse given strings and generate foreign-interface bindings. See [Section 6.7 \[The Easy Foreign Function Interface\]](#), page 124 for more information.

interrupts-enabled [declaration specifier]
 (interrupts-enabled)

Enable timer-interrupts checks in the compiled program (the default).

disable-interrupts [declaration specifier]
not [declaration specifier]
 (disable-interrupts)
 (not interrupts-enabled)

Disable timer-interrupts checks in the compiled program. Threads can not be preempted in main- or library-units that contain this declaration.

no-argc-checks [declaration specifier]
 (no-argc-checks)

Disables argument count checking.

no-bound-checks [declaration specifier]
 (no-bound-checks)

Disables the bound-checking of toplevel bindings.

no-procedure-checks [declaration specifier]
 (no-procedure-checks)

Disables checking of values in operator position for being of procedure type.

TYPE	[declaration specifier]
fixnum-arithmetic	[declaration specifier]
([number-type] TYPE)	
(fixnum-arithmetic)	
Declares that only numbers of the given type are used. TYPE may be fixnum or generic (which is the default).	
run-time-macros	[declaration specifier]
(run-time-macros)	
Equivalent to the compiler option of the same name - low-level macros defined in the compiled code are also made available at runtime.	
standard-bindings	[declaration specifier]
([not] standard-bindings SYMBOL ...)	
Declares that all given standard procedures (or all if no symbols are specified) are never globally redefined. If not is specified, then all but the given standard bindings are assumed to be never redefined.	
extended-bindings	[declaration specifier]
([not] extended-bindings SYMBOL ...)	
Declares that all given non-standard and CHICKEN-specific procedures (or all if no symbols are specified) are never globally redefined. If not is specified, then all but the given extended bindings are assumed to be never redefined.	
usual-integrations	[declaration specifier]
([not] usual-integrations SYMBOL ...)	
Declares that all given standard and extended bindings (or all if no symbols are specified) are never globally redefined. If not is specified, then all but the given standard and extended bindings are assumed to be never redefined.	
unit	[declaration specifier]
(unit SYMBOL)	
Specify compilation unit-name (if this is a library)	
unsafe	[declaration specifier]
not	[declaration specifier]
(unsafe)	
(not safe)	
Do not generate safety-checks. This is the same as specifying the -unsafe option. Also implies	
(declare (no-bound-checks) (no-procedure-checks) (no-argc-checks))	
uses	[declaration specifier]
(uses SYMBOL ...)	
Gives a list of used library-units. Before the toplevel-expressions of the main-module are executed, all used units evaluate their toplevel-expressions in the order in which they appear in this declaration. If a library unit A uses another	

unit B, then B's toplevel expressions are evaluated before A's. Furthermore, the used symbols are registered as features during compile-time, so `cond-expand` knows about them.

5.6 Parameters

Certain behavior of the interpreter and compiled programs can be customized via 'parameters', where a parameter is a procedure of zero or one arguments. To retrieve the value of a parameter call the parameter-procedure with zero arguments. To change the setting of the parameter, call the parameter-procedure with the new value as argument:

```
(define foo (make-parameter 123))
(foo)                ==> 123
(foo 99)
(foo)                ==> 99
```

Parameters are fully thread-local, each thread of execution owns a local copy of a parameters' value.

CHICKEN implements [SRFI-39](#)

make-parameter [procedure]
 (make-parameter VALUE [GUARD])

Returns a procedure that accepts zero or one argument. Invoking the procedure with zero arguments returns **VALUE**. Invoking the procedure with one argument changes its value to the value of that argument (subsequent invocations with zero parameters return the new value). **GUARD** should be a procedure of a single argument. Any new values of the parameter (even the initial value) are passed to this procedure. The guard procedure should check the value and/or convert it to an appropriate form.

case-sensitive [parameter]
 If true, then **read** reads symbols and identifiers in case-sensitive mode and uppercase characters in symbols are printed escaped. Defaults to **#t**.

dynamic-load-libraries [parameter]
 A list of strings containing shared libraries that should be checked for explicitly loaded library units (this facility is not available on all platforms). See **load-library**.

command-line-arguments [parameter]
 Contains the list of arguments passed to this program, with the name of the program and any runtime options (all options starting with **-:**) removed.

exit-handler [parameter]
 A procedure of a single optional argument. When **exit** is called, then this procedure will be invoked with the exit-code as argument. The default behavior is to terminate the program.

eval-handler [parameter]
 A procedure of one or two arguments. When **eval** is invoked, it calls the value of this parameter with the same arguments. The default behavior is to evaluate the argument expression and to ignore the second parameter.

force-finalizers [parameter]

If true, force and execute all pending finalizers before exiting the program (either explicitly by `exit` or implicitly when the last toplevel expression has been executed). Default is `#t`.

implicit-exit-handler [parameter]

A procedure of no arguments. When the last toplevel expression of the program has executed, then the value of this parameter is called. The default behaviour is to do nothing, or, if one or more entry-points were defined (see: [Section 6.3 \[Entry points\]](#), [page 115](#)) to enter a loop that waits for callbacks from the host program.

keyword-style [parameter]

Enables alternative keyword syntax, where `STYLE` may be either `#:prefix` (as in Common Lisp) or `#:suffix` (as in DSSSL). Any other value disables the alternative syntaxes.

load-verbose [parameter]

A boolean indicating whether loading of source files, compiled code (if available) and compiled libraries should display a message.

repl-prompt [parameter]

A string that will be printed before reading interactive input from the user in a read-eval-print loop. Defaults to `"#;> "`.

reset-handler [parameter]

A procedure of zero arguments that is called via `reset`. The default behavior in compiled code is to invoke the value of `(exit-handler)`. The default behavior in the interpreter is to abort the current computation and to restart the read-eval-print loop.

strict-reader [parameter]

If true, then most non-standard read syntax is disabled. Defaults to `#f`.

5.7 Unit library

This unit contains basic Scheme definitions. This unit is used by default, unless the program is compiled with the `-explicit-use` option.

5.7.1 Arithmetic

add1 [procedure]

sub1 [procedure]

(add1 N)

(sub1 N)

Adds/subtracts 1 from N.

bitwise-and	[procedure]
bitwise-ior	[procedure]
bitwise-xor	[procedure]
bitwise-not	[procedure]
arithmetic-shift	[procedure]

```

(bitwise-and N1 ...)
(bitwise-ior N1 ...)
(bitwise-xor N1 ...)
(bitwise-not N)
(arithmetic-shift N1 N2)

```

Binary fixnum operations. **arithmetic-shift** shifts the argument **N1** by **N2** bits to the left. If **N2** is negative, than **N1** is shifted to the right.

fixnum?	[procedure]
(fixnum? X)	

Returns **#t** if **X** is a fixnum, or **#f** otherwise.

fx+	[procedure]
fx-	[procedure]
fx*	[procedure]
fx/	[procedure]
fxmod	[procedure]
fxneg	[procedure]
fxmin	[procedure]
fxmax	[procedure]
fx=	[procedure]
fx>	[procedure]
fx<	[procedure]
fx>=	[procedure]
fx<=	[procedure]

```

(fx+ N1 N2)
(fx- N1 N2)
(fx* N1 N2)
(fx/ N1 N2)
(fxmod N1 N2)
(fxneg N)
(fxmin N1 N2)
(fxmax N1 N2)
(fx= N1 N2)
(fx> N1 N2)
(fx< N1 N2)
(fx>= N1 N2)
(fx<= N1 N2)

```

Arithmetic fixnum operations. These procedures do not check their arguments, so non-fixnum parameters will result in incorrect results. **fxneg** negates its argument.

On division by zero, **fx/** and **fxmod** signal a condition of kind (**exn arithmetic**).

signum [procedure]

(signum N)

Returns 1 if N is positive, -1 if N is negative or 0 if N is zero.

5.7.2 File Input/Output

current-error-port [procedure]

(current-error-port [PORT])

Returns default error output port. If PORT is given, then that port is selected as the new current error output port.

end-of-file [procedure]

(end-of-file)

Returns the end-of-file object.

flush-output [procedure]

(flush-output [PORT])

Write buffered output to the given output-port. PORT defaults to the value of (current-output-port).

port-name [procedure]

(port-name PORT)

Fetch filename from PORT. This returns the filename that was used to open this file. Returns a special tag string, enclosed into parentheses for non-file ports.

port-position [procedure]

(port-position PORT)

Returns the current position of PORT as two values: row and column number. If the port does not support such an operation an error is signaled. This procedure is currently only available for input ports.

set-port-name! [procedure]

(set-port-name! PORT STRING)

Sets the name of PORT to STRING.

5.7.3 Files

delete-file [procedure]

(delete-file STRING)

Deletes the file with the pathname STRING. If the file does not exist, an error is signaled.

file-exists? [procedure]

(file-exists? STRING)

Returns **#t** if a file with the given pathname exists, or **#f** otherwise.

pathname-directory-separator [variable]

Contains the directory-separator character for pathnames on this platform.

pathname-extension-separator [variable]

Contains the extension-separator character for pathnames on this platform.

rename-file [procedure]

(rename-file OLD NEW)

Renames the file or directory with the pathname OLD to NEW. If the operation does not succeed, an error is signaled.

5.7.4 String ports

get-output-string [procedure]

(get-output-string PORT)

Returns accumulated output of a port created with (open-output-string).

open-input-string [procedure]

(open-input-string STRING)

Returns a port for reading from STRING.

open-output-string [procedure]

(open-output-string)

Returns a port for accumulating output in a string.

5.7.5 Feature identifiers

features [procedure]

(features)

Returns a list of all registered features that will be accepted as valid feature-identifiers by cond-expand.

register-feature! [procedure]

(register-feature! FEATURE ...)

Register one or more features that will be accepted as valid feature-identifiers by cond-expand. FEATURE ... may be a keyword, string or symbol.

unregister-feature! [procedure]

(unregister-feature! FEATURE ...)

Unregisters the specified feature-identifiers. FEATURE ... may be a keyword, string or symbol.

5.7.6 Keywords

Keywords are special symbols prefixed with `#:` that evaluate to themselves. Procedures can use keywords to accept optional named parameters in addition to normal required parameters. Assignment to and bindings of keyword symbols is not allowed. The parameter `keyword-style` and the compiler/interpreter option `-keyword-style` can be used to allow an additional keyword syntax, either compatible to Common LISP, or to DSSSL.

get-keyword [procedure]

```
(get-keyword KEYWORD ARGLIST [THUNK])
```

Returns the argument from `ARGLIST` specified under the keyword `KEYWORD`. If the keyword is not found, then the zero-argument procedure `THUNK` is invoked and the result value is returned. If `THUNK` is not given, `#f` is returned.

```
(define (increase x . args)
  (+ x (get-keyword #:amount args (lambda () 1))) )
(increase 123)                               ==> 124
(increase 123 #:amount 10)                  ==> 133
```

Note: the `KEYWORD` may actually be any kind of object.

keyword? [procedure]

```
(keyword? X)
```

Returns `#t` if `X` is a keyword symbol, or `#f` otherwise.

keyword->string [procedure]

```
(keyword->string KEYWORD)
```

Transforms `KEYWORD` into a string.

string->keyword [procedure]

```
(string->keyword STRING)
```

Returns a keyword with the name `STRING`.

5.7.7 Exceptions

CHICKEN implements the (currently withdrawn) SRFI-12 exception system. For more information, see the [SRFI-12 document](#)

condition-case [syntax]

```
(condition-case EXPRESSION CLAUSE ...)
```

Evaluates `EXPRESSION` and handles any exceptions that are covered by `CLAUSE ...`, where `CLAUSE` should be of the following form:

```
CLAUSE = ([VARIABLE] (KIND ...) BODY ...)
```

If provided, `VARIABLE` will be bound to the signalled exception object. `BODY ...` is executed when the exception is a property- or composite condition with the kinds given `KIND ...` (unevaluated). If no clause applies, the exception is re-signalled in the same dynamic context as the `condition-case` form.

```

(define (check thunk)
  (condition-case (thunk)
    [(exn file) (print "file error")]
    [(exn) (print "other error")]
    [var () (print "something else")] ) )

(check (lambda () (open-input-file ""))) ; -> "file error"
(check (lambda () some-unbound-variable)) ; -> "othererror"
(check (lambda () (signal 99)))           ; -> "something else"

(condition-case some-unbound-variable
  [(exn file) (print "ignored")] ) ; -> signals error

```

All error-conditions signalled by the system are of kind `exn`. The following composite conditions are additionally defined:

- (`exn arity`)
Signalled when a procedure is called with the wrong number of arguments.
- (`exn type`)
Signalled on type-mismatch errors, for example when an argument of the wrong type is passed to a builtin procedure.
- (`exn arithmetic`)
Signalled on arithmetic errors, like division by zero.
- (`exn i/o`)
Signalled on input/output errors.
- (`exn i/o file`)
Signalled on file-related errors.
- (`exn i/o net`)
Signalled on network errors.
- (`exn bounds`)
Signalled on errors caused by accessing non-existent elements of a collection.
- (`exn runtime`)
Signalled on low-level runtime-system error-situations.
- (`exn runtime limit`)
Signalled when an internal limit is exceeded (like running out of memory).
- (`exn match`)
Signalled on errors raised by failed matches (see the section on `match`).
- (`exn syntax`)
Signalled on syntax errors.

Notes:

- All error-exceptions (of the kind `exn`) are non-continuable.

- Error-exceptions of the **exn** kind have additional **arguments** and **location** properties that contain the arguments passed to the error-handler and the name of the procedure where the error occurred (if available).
- When the **posix** unit is available and used, then a user-interrupt (**signal/int**) signals an exception of the kind **user-interrupt**.
- the procedure **condition-property-accessor** accepts an optional third argument. If the condition does not have a value for the desired property and if the optional argument is given and false, no error is signalled and the accessor returns **#g**.

5.7.8 Environment information and system interface

argv [procedure]

(argv)

Return a list of all supplied command-line arguments. The first item in the list is a string containing the name of the executing program. The other items are the arguments passed to the application. This list is freshly created on every invocation of (argv). It depends on the host-shell whether arguments are expanded ('globbed') or not.

exit [procedure]

(exit [CODE])

Exit the running process and return exit-code, which defaults to 0 (Invokes **exit-handler**).

build-platform [procedure]

(build-platform)

Returns a symbol specifying the toolset which has been used for building the executing system, which is one of the following:

djgpp
cygwin
msvc
mingw32
gnu
metrowerks
unknown

chicken-version [procedure]

(chicken-version)

Returns a string containing the version number of the CHICKEN runtime system.

errno [procedure]

(errno)

Returns the error code of the last system call.

getenv [procedure]

(getenv STRING)

Returns the value of the environment variable **STRING** or **#f** if that variable is not defined.

machine-type [procedure]
(machine-type)

Returns a symbol specifying the processor on which this process is currently running, which is one of the following:

alpha
mips
hppa
ultrasparc
sparc
ppc
ia64
x86
x86-64
unknown

software-type [procedure]
(software-type)

Returns a symbol specifying the operating system on which this process is currently running, which is one of the following:

msdos
windows
unix
macos
unknown

software-version [procedure]
(software-version)

Returns a symbol specifying the operating system version on which this process is currently running, which is one of the following:

linux
freebsd
netbsd
openbsd
macosx
hpux
solaris
sunos
unknown

system [procedure]
(system STRING)

Execute shell command. The functionality offered by this procedure depends on the capabilities of the host shell.

5.7.9 Execution time

cpu-time [procedure]

(cpu-time)

Returns the used CPU time of the current process in milliseconds as two values: the time spent in user code, and the time spent in system code. On platforms where user and system time can not be differentiated, system time will be always be 0.

current-milliseconds [procedure]

(current-milliseconds)

Returns the number of milliseconds since process- or machine startup.

current-seconds [procedure]

(current-seconds)

Returns the number of seconds since midnight, Jan. 1, 1970.

5.7.10 Interrupts and error-handling

enable-interrupts [procedure]

disable-interrupts [procedure]

(enable-interrupts)

(disable-interrupts)

Enables/disables processing of timer-interrupts and interrupts caused by signals.

(disable-interrupts)

(disable-interrupts)

(enable-interrupts)

; <interrupts still disabled - call enable-interrupts once more>

enable-warnings [procedure]

(enable-warnings [BOOL])

Enables or disables warnings, depending on whether `BOOL` is true or false. If called with no arguments, this procedure returns `#t` if warnings are currently enabled, or `#f` otherwise. Note that this is not a parameter. The current state (whether warnings are enabled or disabled) is global and not thread-local.

error [procedure]

(error [LOCATION] STRING EXP ...)

Prints error message, writes all extra arguments to the value of (`current-error-port`) and invokes the current value of (`error-handler`). This conforms to [SRFI-23](#). If `LOCATION` is given and a symbol, it specifies the “location” (the name of the procedure) where the error occurred.

print-backtrace [procedure]

(print-backtrace [PORT])

Prints a backtrace of the procedure call history to `PORT`, which defaults to (`current-error-port`). Backtrace information is only generated in compiled code, with a `-debug-level >= 1`.

print-error-message [procedure]

(print-error-message EXN [PORT [STRING]])

Prints an appropriate error message to PORT (which defaults to the value of (current-error-port)) for the object EXN. EXN may be a condition, a string or any other object. If the optional argument STRING is given, it is printed before the error-message. STRING defaults to "Error:".

reset [procedure]

(reset)

Reset program (Invokes reset-handler).

5.7.11 Garbage collection

gc [procedure]

(gc [FLAG])

Invokes a garbage-collection and returns the number of free bytes in the heap. The flag specifies whether a minor (**#f**) or major (**#t**) GC is to be triggered. If no argument is given, **#t** is assumed. When the argument is **#t**, all pending finalizers are executed.

memory-statistics [procedure]

(memory-statistics)

Performs a major garbage collection and returns a three element vector containing the total heap size in bytes, the number of bytes currently used and the size of the nursery (the first heap generation). Note that the actual heap is actually twice the size given in the heap size, because CHICKEN uses a copying semi-space collector.

set-finalizer! [procedure]

(set-finalizer! X PROC)

Registers a procedure of one argument PROC, that will be called as soon as the non-immediate data object X is about to be garbage-collected (with that object as its argument). Note that the finalizer will **not** be called when interrupts are disabled.

set-gc-report! [procedure]

(set-gc-report! FLAG)

Print statistics after every GC, depending on FLAG. A value of **#t** shows statistics after every major GC. A true value different from **#t** shows statistics after every minor GC. **#f** switches statistics off.

5.7.12 Other control structures

andmap [procedure]

(andmap PROC LIST1 ...)

Repeatedly calls PROC with arguments taken from LIST1 If any invocation should return **#f**, the result of **andmap** is **#f**. If all invocations return a true result, then the result of **andmap** is **#t**.

ormap [procedure]
 (ormap PROC LIST1 ...)

Repeatedly calls PROC with arguments taken from LIST1 If any invocation should return a value different from #f, then this value is returned as the result of ormap. If all invocations return #f, then the result of ormap is #f.

5.7.13 String utilities

reverse-list->string [procedure]
 (reverse-list->string LIST)

Returns a string with the characters in LIST in reverse order. This is equivalent to (list->string (reverse LIST)), but much more efficient.

5.7.14 Generating uninterned symbols

gensym [procedure]
 (gensym [STRING-OR-SYMBOL])

Returns a newly created uninterned symbol. If an argument is provided, the new symbol is prefixed with that argument.

string->uninterned-symbol [procedure]
 (string->uninterned-symbol STRING)

Returns a newly created, unique symbol with the name STRING.

5.7.15 Standard Input/Output

port? [procedure]
 (port? X)

Returns #t if X is a port object or #f otherwise.

print [procedure]
 (print EXP1 EXP2 ...)

Outputs the arguments EXP1 EXP2 ... using display and writes a newline character to the port that is the value of (current-output-port). Returns its first argument.

print* [procedure]
 (print* EXP1 ...)

Similar to print, but does not output a terminating newline character.

5.7.16 User-defined named characters

char-name [procedure]
 (char-name SYMBOL-OR-CHAR [CHAR])

This procedure can be used to inquire about character names or to define new ones. With a single argument the behavior is as follows: If SYMBOL-OR-CHAR is a symbol,

then `char-name` returns the character with this name, or `#f` if no character is defined under this name. If `SYMBOL-OR-CHAR` is a character, then the name of the character is returned as a symbol, or `#f` if the character has no associated name.

If the optional argument `CHAR` is provided, then `SYMBOL-OR-CHAR` should be a symbol that will be the new name of the given character. If multiple names designate the same character, then the `write` will use the character name that was defined last.

```
(char-name 'space)           ==> #\space
(char-name #\space)          ==> space
(char-name 'bell)            ==> #f
(char-name (integer->char 7)) ==> #f
(char-name 'bell (integer->char 7))
(char-name 'bell)            ==> #\bell
(char->integer (char-name 'bell)) ==> 7
```

5.7.17 Vectors

vector-copy!

[procedure]

```
(vector-copy! VECTOR1 VECTOR2 [COUNT])
```

Copies contents of `VECTOR1` into `VECTOR2`. If the argument `COUNT` is given, it specifies the maximal number of elements to be copied. If not given, the minimum of the lengths of the argument vectors is copied.

Exceptions: (`exn bounds`)

vector-resize

[procedure]

```
(vector-resize VECTOR N [INIT])
```

Creates and returns a new vector with the contents of `VECTOR` and length `N`. If `N` is greater than the original length of `VECTOR`, then all additional items are initialized to `INIT`. If `INIT` is not specified, the contents are initialized to some unspecified value.

5.7.18 The *unspecified* value

void

[procedure]

```
(void)
```

Returns an unspecified value.

5.7.19 call/cc

call/cc

[procedure]

```
(call/cc PROCEDURE)
```

An alias for `call-with-current-continuation`.

5.8 Unit eval

This unit has support for evaluation and macro-handling. This unit is used by default, unless the program is compiled with the `-explicit-use` option.

5.8.1 Loading code

load [procedure]

(load FILE [EVALPROC])

Loads and evaluates expressions from the given source file, which may be either a string or an input port. Each expression read is passed to `EVALPROC` (which defaults to `eval`). On platforms that support it (currently Linux ELF and Solaris), `load` can be used to load compiled programs:

```
% cat x.scm
(define (hello) (print "Hello!"))
% chicken x.scm -quiet -dynamic
% gcc x.c -shared -fPIC 'chicken-config -cflags -shared -libs' -o x.so
% csi -quiet
#;> (load "x.so")
; loading x.so ...
#;> (hello)
Hello!
#;>
```

The second argument to `load` is ignored when loading compiled code. The same compiled object file can not be loaded more than once. If source code is loaded from a port, then that port is closed after all expressions have been read.

load-library [procedure]

(load-library UNIT [LIBRARYFILE])

On platforms that support dynamic loading, `load-library` loads the compiled library unit `UNIT` (which should be a symbol). If the string `LIBRARYFILE` is given, then the given shared library will be loaded and the toplevel code of the contained unit will be executed. If no `LIBRARYFILE` argument is given, then the following libraries are checked for the required unit:

- a file named “<UNIT>.so”
- the files given in the parameter `dynamic-load-libraries`

If the unit is not found, an error is signaled. When the library unit can be successfully loaded, a feature-identifier named `UNIT` is registered. If the feature is already registered before loading, the `load-library` does nothing.

load-noisily [procedure]

(load-noisily FILE [EVALPROC])

As `load` but the result(s) of each evaluated toplevel-expression is written to standard output.

5.8.2 Read-eval-print loop

repl [procedure]

(repl)

Start a new read-eval-print loop. Sets the **reset-handler** so that any invocation of **reset** restarts the read-eval-print loop. Also changes the current **error-handler** to display a message, write any arguments to the value of (**current-error-port**) and **reset**.

5.8.3 Macros

get-line-number [procedure]

(**get-line-number** EXPR)

If EXPR is a pair with the car being a symbol, and line-number information is available for this expression, then this procedure returns the associated line number. If line-number information is not available, then **#f** is returned. Note that line-number information for expressions is only available in the compiler.

macro? [procedure]

(**macro?** SYMBOL)

Returns **#t** if there exists a macro-definition for SYMBOL.

macroexpand [procedure]

(**macroexpand** X)

If X is a macro-form, expand the macro (and repeat expansion until expression is a non-macro form). Returns the resulting expression.

macroexpand-1 [procedure]

(**macroexpand-1** X)

If X is a macro-form, expand the macro. Returns the resulting expression.

undefine-macro! [procedure]

(**undefine-macro!** SYMBOL)

Remove the current macro-definition of the macro named SYMBOL.

syntax-error [procedure]

(**syntax-error** [LOCATION] MESSAGE ARGUMENT ...)

Signals an exception of the kind (**exn syntax**). Otherwise identical to **error**.

5.8.4 Loading extension libraries

This functionality is only available on platforms that support dynamic loading of compiled code. Currently Linux, BSD, Solaris, Windows (with Cygwin) and HP/UX are supported.

repository-path [parameter]

Contains a string naming the path to the extension repository, which defaults to either the value of the environment variable **CHICKEN_REPOSITORY**, the value of the environment variable **CHICKEN_HOME** or the default library path (usually **/usr/local/lib/chicken** on UNIX systems).

extension-info [procedure]

(extension-info ID)

If an extension with the name `ID` is installed and if it has a setup-information list registered in the extension repository, then the info-list is returned. Otherwise **extension-info** returns `#f`.

provide [procedure]

(provide ID ...)

Registers the extension IDs `ID ...` as loaded. This is mainly intended to provide aliases for certain extension identifiers.

provided? [procedure]

(provided? ID ...)

Returns `#t` if the extension with the IDs `ID ...` are currently loaded, or `#f` otherwise. Works also for feature-ids.

require [procedure]

(require ID ...)

If the extension library `ID` is not already loaded into the system, then **require** will lookup the location of the shared extension library and load it. If `ID` names a library-unit of the base system, then it is loaded via **load-library**. If no extension library is available for the given `ID`, then an attempt is made to load the file `ID.so` or `ID.scm` (in that order) from one of the following locations:

1. the current directory
2. the current include path, which defaults to the pathnames given in `CHICKEN_INCLUDE_PATH` and `CHICKEN_HOME`. In case `ID` is a list, it is interpreted as a (relative) pathname.

`ID` may be a symbol, or a list of symbols. See also: **require-for-syntax**.

5.8.5 Reader extensions

define-reader-ctor [procedure]

(define-reader-ctor SYMBOL PROC)

Define new read-time constructor for `#`, read syntax. For further information, see the documentation for [SRFI-10](#).

set-read-syntax! [procedure]

(set-read-syntax! CHAR PROC)

When the reader is encountering the non-whitespace character `CHAR` while reading an expression from a given port, then the procedure `PROC` will be called with that port as its argument. The procedure should return a value that will be returned to the reader:

```
; A simple RGB color syntax:
```

```
(set-read-syntax! #\%
```



```

(lambda (port)
  (apply vector
    (map (cut string->number <> 16)
      (string-chop (read-string 6 port) 2) ) ) ) )

(with-input-from-string "(1 2 %e0e0e0 3)" read)
; ==> (1 2 #(240 240 240) 3)

```

5.8.6 Eval

eval [procedure]
 (eval EXP [ENVIRONMENT])

Evaluates EXP and returns the result of the evaluation. The second argument is optional and defaults to the value of (interaction-environment).

5.9 Unit extras

This unit contains a collection of useful utility definitions. This unit is used by default, unless the program is compiled with the `-explicit-use` option.

5.9.1 Lists

alist-ref [procedure]
 (alist-ref KEY ALIST [TEST [DEFAULT]])

Looks up KEY in ALIST using TEST as the comparison function (or `eqv?` if no test was given) and returns the cdr of the found pair, or DEFAULT (which defaults to `#f`).

alist-update! [procedure]
 (alist-update! KEY VALUE ALIST [TEST])

If the list ALIST contains a pair of the form (KEY . X), then this procedure replaces X with VALUE and returns ALIST. If ALIST contains no such item, then **alist-update!** returns ((KEY . VALUE) . ALIST). The optional argument TEST specifies the comparison procedure to search a matching pair in ALIST and defaults to `eqv?`.

butlast [procedure]
 (butlast LIST)

Returns a fresh list with all elements but the last of LIST.

chop [procedure]
 (chop LIST N)

Returns a new list of sublists, where each sublist contains N elements of LIST. If LIST has a length that is not a multiple of N, then the last sublist contains the remaining elements.

```

(chop '(1 2 3 4 5 6) 2) ==> ((1 2) (3 4) (5 6))
(chop '(a b c d) 3)      ==> ((a b c) (d))

```

compress [procedure]

`(compress BLIST LIST)`

Returns a new list with elements taken from `LIST` with corresponding true values in the list `BLIST`.

```
(define nums '(99 100 110 401 1234))
(compress (map odd? nums) nums)    ==> (99 401)
```

flatten [procedure]

`(flatten LIST1 ...)`

Returns `LIST1 ...` concatenated together, with nested lists removed (flattened).

intersperse [procedure]

`(intersperse LIST X)`

Returns a new list with `X` placed between each element.

join [procedure]

`(join LISTOFLISTS [LIST])`

Concatenates the lists in `LISTOFLISTS` with `LIST` placed between each sublist. `LIST` defaults to the empty list.

```
(join '((a b) (c d) (e)) '(x y)) ==> (a b x y c d x y e)
(join '((p q) ()) (r (s) t)) '(-)) ==> (p q - - r (s) t)
```

shuffle [procedure]

`(shuffle LIST)`

Returns `LIST` with its elements sorted in a random order.

`join` could be implemented as follows:

```
(define (join lstoflsts . lst)
  (apply append (intersperse lstoflsts (:optional lst '())))) )
```

tail? [procedure]

`(tail? X LIST)`

Returns true if `X` is one of the tails (`cdr`'s) of `LIST`.

5.9.2 String-port extensions

call-with-input-string [procedure]

`(call-with-input-string STRING PROC)`

Calls the procedure `PROC` with a single argument that is a string-input-port with the contents of `STRING`.

call-with-output-string [procedure]

`(call-with-output-string PROC)`

Calls the procedure `PROC` with a single argument that is a string-output-port. Returns the accumulated output-string.

with-input-from-string [procedure]

(with-input-from-string STRING THUNK)

Call procedure THUNK with the current input-port temporarily bound to an input-string-port with the contents of STRING.

with-output-to-string [procedure]

(with-output-to-string THUNK)

Call procedure THUNK with the current output-port temporarily bound to a string-output-port and return the accumulated output string.

5.9.3 Formatted output

fprintf [procedure]

printf [procedure]

sprintf [procedure]

(fprintf PORT FORMATSTRING ARG ...)

(printf FORMATSTRING ARG)

(sprintf FORMATSTRING ARG ...)

Simple formatted output to a given port (**fprintf**), the value of (**current-output-port**) (**printf**) or a string (**sprintf**). The **FORMATSTRING** can contain any sequence of characters. The character ‘~’ prefixes special formatting directives:

~%	write newline character
~S	write the next argument
~A	display the next argument
~\n	skip all whitespace in the format-string until the next non-whitespace character
~B	write the next argument as a binary number
~O	write the next argument as an octal number
~X	write the next argument as a hexadecimal number
~C	write the next argument as a character
~~	display ‘~’
~!	flush all pending output
~?	invoke formatted output routine recursively with the next two arguments as format-string and list of parameters

For more powerful output formatting, see the section about the **format** unit.

5.9.4 Hash tables

clear-hash-table! [procedure]

(clear-hash-table! HASH-TABLE)

Erases all entries in the hash-table **HASH-TABLE**.

get [procedure]

(get HASH-TABLE KEY PROP)

Returns the value of property PROP of the item KEY in HASH-TABLE . This facility can be used as a kind of “disembodied” property-list. If no entry named KEY is stored in the hash-table or if no property PROP for that key exists, #f is returned.

hash-table? [procedure]

(hash-table? X)

Returns #t if the argument is a hash-table.

hash-table->list [procedure]

(hash-table->list HASH-TABLE)

Converts HASH-TABLE into an association-list.

hash-table-count [procedure]

(hash-table-count HASH-TABLE)

Returns the number of entries in the given hash-table.

hash-table-size [procedure]

(hash-table-size HASH-TABLE)

Returns the size of the hash-table.

hash-table-for-each [procedure]

(hash-table-for-each PROC HASH-TABLE)

Calls PROC which should expect two arguments. This procedure is called for each entry in the hash-table with the key and the value as parameters.

hash-table-ref [procedure]

(hash-table-ref HASH-TABLE KEY [DEFAULT])

Returns the entry in the given hash-table under KEY. If no entry is stored in the table, #f is returned.

hash-table-remove! [procedure]

(hash-table-remove! HASH-TABLE KEY)

Removes an entry in the given hash-table.

hash-table-set! [procedure]

(hash-table-set! HASH-TABLE KEY VALUE)

Adds or changes an entry in the given hash-table.

make-hash-table [procedure]

(make-hash-table [PRED [SIZE]])

Creates and returns a hash-table with keys compared via PRED, which defaults to eq?. If SIZE is provided it specifies the initial size of the hash-table. If the hash-table fills above a certain size it is automatically resized to accommodate more entries.

put! [procedure]

(put! HASH-TABLE KEY PROP VALUE)

Stores VALUE as property PROP under the item KEY in the given hash-table. Any previously existing value is overwritten.

5.9.5 Queues

list->queue [procedure]

(list->queue LIST)

Returns LIST converted into a queue, where the first element of the list is the same as the first element of the queue. The resulting queue may share memory with the list and the list should not be modified after this operation.

make-queue [procedure]

(make-queue)

Returns a newly created queue.

queue? [procedure]

(queue? X)

Returns #t if X is a queue, or #f otherwise.

queue->list [procedure]

(queue->list QUEUE)

Returns QUEUE converted into a list, where the first element of the list is the same as the first element of the queue. The resulting list may share memory with the queue object and should not be modified.

queue-add! [procedure]

(queue-add! QUEUE X)

Adds X to the rear of QUEUE.

queue-empty? [procedure]

(queue-empty? QUEUE)

Returns #t if QUEUE is empty, or #f otherwise.

queue-first [procedure]

(queue-first QUEUE)

Returns the first element of QUEUE. If QUEUE is empty an error is signaled

queue-last [procedure]

(queue-last QUEUE)

Returns the last element of QUEUE. If QUEUE is empty an error is signaled

queue-remove! [procedure]

(queue-remove! QUEUE)

Removes and returns the first element of QUEUE. If QUEUE is empty an error is signaled

5.9.6 Sorting

merge [procedure]
merge! [procedure]

(merge LIST1 LIST2 LESS?)
 (merge! LIST1 LIST2 LESS?)

Joins two lists in sorted order. **merge!** is the destructive version of **merge**. **LESS?** should be a procedure of two arguments, that returns true if the first argument is to be ordered before the second argument.

sort [procedure]
sort! [procedure]

(sort SEQUENCE LESS?)
 (sort! SEQUENCE LESS?)

Sort **SEQUENCE**, which should be a list or a vector. **sort!** is the destructive version of **sort**.

sorted? [procedure]
 (sorted? SEQUENCE LESS?)

Returns true if the list or vector **SEQUENCE** is already sorted.

5.9.7 Random numbers

random [procedure]
 (random N)

Returns an exact random integer from 0 to N-1.

randomize [procedure]
 (randomize [X])

Set random-number seed. If **X** is not supplied, the current time is used. On startup (when the **extras** unit is initialized), the random number generator is initialized with the current time.

5.9.8 Input/Output extensions

make-input-port [procedure]
 (make-input-port READ READY? CLOSE [PEEK])

Returns a custom input port. Common operations on this port are handled by the given parameters, which should be procedures of no arguments. **READ** is called when the next character is to be read and should return a character or the value of (**end-of-file**). **READY?** is called when **char-ready?** is called on this port and should return **#t** or **#f**. **CLOSE** is called when the port is closed. **PEEK** is called when **peek-char** is called on this port and should return a character or the value of (**end-of-file**). if the argument **PEEK** is not given, then **READ** is used instead and the created port object handles peeking automatically (by calling **READ** and buffering the character).

make-output-port [procedure]

(make-output-port WRITE CLOSE [FLUSH])

Returns a custom output port. Common operations on this port are handled by the given parameters, which should be procedures. **WRITE** is called when output is sent to the port and receives a single argument, a string. **CLOSE** is called when the port is closed and should be a procedure of no arguments. **FLUSH** (if provided) is called for flushing the output port.

pretty-print [procedure]

pp [procedure]

(pretty-print EXP [PORT])

(pp EXP [PORT])

Print expression nicely formatted. **PORT** defaults to the value of (current-output-port).

pretty-print-width [parameter]

Specifies the maximal line-width for pretty printing, after which line wrap will occur.

read-file [procedure]

(read-file [FILE-OR-PORT])

Returns a list containing all toplevel expressions read from the file or port **FILE-OR-PORT**. If no argument is given, input is read from the port that is the current value of (current-input-port). After all expressions are read, and if the argument is a port, then the port will not be closed.

read-line [procedure]

write-line [procedure]

(read-line [PORT [LIMIT]])

(write-line STRING [PORT])

Line-input and -output. **PORT** defaults to the value of (current-input-port) and (current-output-port), respectively. if the optional argument **LIMIT** is given and not **#f**, then **read-line** reads at most **LIMIT** characters per line.

read-lines [procedure]

(read-lines [PORT [MAX]])

Read **MAX** or fewer lines from **PORT**. **PORT** defaults to the value of (current-input-port).

read-string [procedure]

write-string [procedure]

(read-string [NUM [PORT]])

(write-string STRING [NUM [PORT]])

Read or write **NUM** characters from/to **PORT**, which defaults to the value of (current-input-port) or (current-output-port), respectively. If **NUM** is **#f** or not given, then all data up to the end-of-file is read, or, in the case of **write-string** the whole string is written. If no more input is available, **read-string** returns the empty string.

read-token [procedure]

(read-token PREDICATE [PORT])

Reads characters from PORT (which defaults to the value of (current-input-port)) and calls the procedure PREDICATE with each character until PREDICATE returns false.

with-error-output-to-port [procedure]

(with-error-output-to-port PORT THUNK)

Call procedure THUNK with the current error output-port temporarily bound to PORT.

with-input-from-port [procedure]

(with-input-from-port PORT THUNK)

Call procedure THUNK with the current input-port temporarily bound to PORT.

with-output-to-port [procedure]

(with-output-to-port PORT THUNK)

Call procedure THUNK with the current output-port temporarily bound to PORT.

5.9.9 Strings

conc [procedure]

(conc X ...)

Returns a string with the string-representation of all arguments concatenated together. conc could be implemented as

```
(define (conc . args)
  (apply string-append (map ->string args)) )
```

->string [procedure]

(->string X)

Returns a string-representation of X.

string-chop [procedure]

(string-chop STRING LENGTH)

Returns a list of substrings taken by “chopping” STRING every LENGTH characters:

```
(string-chop "one two three" 4) ==> ("one " "two " "thre" "e")
```

string-compare3 [procedure]

(string-compare3 STRING1 STRING2)

string-compare3-ci [procedure]

(string-compare3-ci STRING1 STRING2)

Perform a three-way comparison between the STRING1 and STRING2, returning either -1 if STRING1 is lexicographically less than STRING2, 0 if it is equal, or 1 if it is greater. string-compare3-ci performs a case-insensitive comparison.

string-interperse [procedure]

(string-interperse LIST STRING)

Returns a string that contains all strings in LIST concatenated together. STRING is placed between each concatenated string.


```
(string-interperse '("one" "two") "three")
```

is equivalent to

```
(apply string-append (intersperse '("one" "two") "three"))
```

string-split [procedure]

```
(string-split STRING [DELIMITER-STRING [KEEPEMPTY]])
```

Split string into substrings separated by the given delimiters. If no delimiters are specified, a string comprising the tab, newline and space characters is assumed. If the parameter `KEEPEMPTY` is given and not `#f`, then empty substrings are retained:

```
(string-split "one two three") ==> ("one" "two" "three")
(string-split "foo:bar::baz:" ":" #t) ==> ("foo" "bar" "" "baz" "")
```

string-translate [procedure]

```
(string-translate STRING FROM [TO])
```

Returns a fresh copy of `STRING` with characters matching `FROM` translated to `TO`. If `TO` is omitted, then matching characters are removed. `FROM` and `TO` may be a character, a string or a list. If both `FROM` and `TO` are strings, then the character at the same position in `TO` as the matching character in `FROM` is substituted.

string-translate* [procedure]

```
(string-translate* STRING SMAP)
```

Substitutes elements of `STRING` according to `SMAP`. `SMAP` should be an association-list where each element of the list is a pair of the form `(MATCH \. REPLACEMENT)`. Every occurrence of the string `MATCH` in `STRING` will be replaced by the string `REPLACEMENT`:

```
(string-translate*
  "<h1>this is a \"string\"</h1>"
  '("<" . "&lt;:") (">" . "&gt;:") ("\" . "&quot;:") )

==> "&lt;h1&gt;this is a &quot;string&quot;&lt;/ht&gt;"
```

substring=? [procedure]

substring-ci=? [procedure]

```
(substring=? STRING1 STRING2 [START1 [START2 [LENGTH]]])
```

```
(substring-ci=? STRING1 STRING2 [START1 [START2 [LENGTH]]])
```

Returns `#t` if the strings `STRING1` and `STRING2` are equal, or `#f` otherwise. The comparison starts at the positions `START1` and `START2` (which default to 0), comparing `LENGTH` characters (which defaults to the minimum of the remaining length of both strings).

substring-index [procedure]

substring-index-ci [procedure]

```
(substring-index WHICH WHERE [START])
```

```
(substring-index-ci WHICH WHERE [START])
```

Searches for first index in string `WHERE` where string `WHICH` occurs. If the optional argument `START` is given, then the search starts at that index. `substring-index-ci` is a case-insensitive version of `substring-index`.

5.9.10 Combinators

constantly [procedure]

`(constantly X ...)`

Returns a procedure that always returns the values `X ...` regardless of the number and value of its arguments.

`(constantly X) <=> (lambda args X)`

complement [procedure]

`(complement PROC)`

Returns a procedure that returns the boolean inverse of `PROC`.

`(complement PROC) <=> (lambda (x) (not (PROC x)))`

compose [procedure]

`(compose PROC1 PROC2 ...)`

Returns a procedure that represents the composition of the argument-procedures `PROC1 PROC2`

`(compose F G) <=> (lambda args
 (call-with-values
 (lambda () (apply G args))
 F))`

conjoin [procedure]

`(conjoin PRED ...)`

Returns a procedure that returns `#t` if its argument satisfies the predicates `PRED`

`((conjoin odd? positive?) 33) ==> #t`
`((conjoin odd? positive?) -33) ==> #f`

disjoin [procedure]

`(disjoin PRED ...)`

Returns a procedure that returns `#t` if its argument satisfies any predicate `PRED`

`((disjoin odd? positive?) 32) ==> #t`
`((disjoin odd? positive?) -32) ==> #f`

flip [procedure]

`(flip PROC)`

Returns a two-argument procedure that calls `PROC` with its arguments swapped:

`(flip PROC) <=> (lambda (x y) (PROC y x))`

identity [procedure]

`(identity X)`

Returns its sole argument `X`.

project [procedure]

`(project N)`

Returns a procedure that returns its `N`th argument.

list-of [procedure]
 (list-of PRED)

Returns a procedure of one argument that returns **#t** when applied to a list of elements that all satisfy the predicate procedure **PRED**, or **#f** otherwise.

```
((list-of even?) '(1 2 3)) ==> #f
((list-of number?) '(1 2 3)) ==> #t
```

5.9.11 Binary searching

binary-search [procedure]
 (binary-search SEQUENCE PROC)

Performs a binary search in **SEQUENCE**, which should be a sorted list or vector. **PROC** is called to compare items in the sequence, should accept a single argument and return an exact integer: zero if the searched value is equal to the current item, negative if the searched value is “less” than the current item, and positive otherwise.

5.10 Unit **srfi-1**

List library, see the documentation for [SRFI-1](#)

5.11 Unit **srfi-4**

Homogeneous numeric vectors, see the documentation for [SRFI-4](#) In addition to that, the following procedures are also provided:

u8vector->byte-vector	[procedure]
s8vector->byte-vector	[procedure]
u16vector->byte-vector	[procedure]
s16vector->byte-vector	[procedure]
u32vector->byte-vector	[procedure]
s32vector->byte-vector	[procedure]
f32vector->byte-vector	[procedure]
f64vector->byte-vector	[procedure]

```

(u8vector->byte-vector U8VECTOR)
(s8vector->byte-vector S8VECTOR)
(u16vector->byte-vector U16VECTOR)
(s16vector->byte-vector S16VECTOR)
(u32vector->byte-vector U32VECTOR)
(s32vector->byte-vector S32VECTOR)
(f32vector->byte-vector F32VECTOR)
(f64vector->byte-vector F64VECTOR)

```

Each of these procedures return the contents of the given vector as a ‘packed’ byte-vector. The byte order in that vector is platform-dependent (for example little-endian on an **Intel** processor). The returned byte-vector shares memory with the contents of the vector.

byte-vector->u8vector	[procedure]
byte-vector->s8vector	[procedure]
byte-vector->u16vector	[procedure]
byte-vector->s16vector	[procedure]
byte-vector->u32vector	[procedure]
byte-vector->s32vector	[procedure]
byte-vector->f32vector	[procedure]
byte-vector->f64vector	[procedure]

```

(byte-vector->u8vector BYTE-VECTOR)
(byte-vector->s8vector BYTE-VECTOR)
(byte-vector->u16vector BYTE-VECTOR)
(byte-vector->s16vector BYTE-VECTOR)
(byte-vector->u32vector BYTE-VECTOR)
(byte-vector->s32vector BYTE-VECTOR)
(byte-vector->f32vector BYTE-VECTOR)
(byte-vector->f64vector BYTE-VECTOR)

```

Each of these procedures return a vector where the argument `BYTE-VECTOR` is taken as a 'packed' representation of the contents of the vector. The argument-byte-vector shares memory with the contents of the vector.

subu8vector	[procedure]
subu16vector	[procedure]
subu32vector	[procedure]
subs8vector	[procedure]
subs16vector	[procedure]
subs32vector	[procedure]
subf32vector	[procedure]
subf64vector	[procedure]

```

(subu8vector U8VECTOR FROM TO)
(subu16vector U16VECTOR FROM TO)
(subu32vector U32VECTOR FROM TO)
(subs8vector S8VECTOR FROM TO)
(subs16vector S16VECTOR FROM TO)
(subs32vector S32VECTOR FROM TO)
(subf32vector F32VECTOR FROM TO)
(subf64vector F64VECTOR FROM TO)

```

Creates a number vector of the same type as the argument vector with the elements at the positions `FROM` up to but not including `TO`.

5.12 Unit `srfi-13`

String library, see the documentation for [SRFI-13](#)

The file `srfi-13-syntax.scm` contains macro definitions for `let-string-start+end`.

On systems that support dynamic loading, the `srfi-13` unit can be made available in the interpreter (`csi`) by entering

```
(require-extension srfi-13)
```

5.13 Unit `srfi-14`

Character set library, see the documentation for [SRFI-14](#)

On systems that support dynamic loading, the `srfi-14` unit can be made available in the interpreter (`csi`) by entering

```
(require-extension srfi-14)
```

- This library provides only the Latin-1 character set.

5.14 Unit `srfi-25`

Multi-dimensional array, see the documentation for [SRFI-25](#)

On systems that support dynamic loading, the `srfi-25` unit can be made available in the interpreter (`csi`) by entering

```
(require-extension srfi-25)
```

5.15 Unit `match`

Andrew Wright's pattern matching package. Note that to use the macros in normal compiled code it is not required to declare this unit as used. Only if forms containing these macros are to be expanded at runtime, this is needed.

match	[syntax]
match-lambda	[syntax]
match-lambda*	[syntax]
match-let	[syntax]
match-let*	[syntax]
match-letrec	[syntax]
match-define	[syntax]

```

(match EXP CLAUSE ...)
(match-lambda CLAUSE ...)
(match-lambda* CLAUSE ...)
(match-let ((PAT EXP) ...) BODY)
(match-let* ((PAT EXP) ...) BODY)
(match-letrec ((PAT EXP) ...) BODY)
(match-define PAT EXP)
```

Match expression or procedure arguments with pattern and execute associated expressions. A [Postscript manual](#) is available .

define-structure	[syntax]
define-const-structure	[syntax]

```

(define-structure (ID_0 ID_1 ... ID_N))
(define-structure (ID_0 ID_1 ... ID_N)
  ((IDN+1 EXP1) ...
   (IDN+M EXPM)))
(define-const-structure (ID0 ARG1 ... ARGN))
```

```
(define-const-structure (ID0 ARG1 ... ARGN)
  ((ARGN+1 EXP1) ...
   (ARGN+M EXPM)))
```

Macros for defining record structures that can be decomposed by `match`.

match-error-control [procedure]
 (match-error-control [MODE])

Selects a mode that specifies how `match...` macro forms are to be expanded. With no argument this procedure returns the current mode. A single argument specifies the new mode that decides what should happen if no match-clause applies. The following modes are supported:

#:error

Signal an error. This is the default.

#:match

Signal an error and output the offending form.

#:fail

Omits `pair?` tests when the consequence is to fail in `car` or `cdr` rather than to signal an error.

#:unspecified

Non-matching expressions will either fail in `car` or `cdr` or return an unspecified value. This mode applies to files compiled with the `unsafe` option or declaration.

When an error is signalled, the raised exception will be of kind `(exn match)`.

Note: `match:structure-control` is not available. Structures defined by the macros provided in this unit are always implemented as vectors. `match:runtime-structures` is also not available.

To use the pattern matching macros with the highlevel `(syntax-case)` macro system (`require-extension match`).

5.16 Unit regex

This library unit provides support for regular expressions. The flavor depends on the particular installation platform:

- On UNIX systems that have PCRE (the Perl Compatible Regular Expression package) installed, PCRE is used.
- If PCRE is not available, and the C library provides regular expressions, these are used instead.
- on Windows (or if PCRE and libc regexes are not available), Dorai Sitaram's portable `pregexp` library is used.

grep [procedure]

(grep REGEX LIST)

Returns all items of LIST that match the regular expression REGEX. This procedure could be defined as follows:

```
(define (grep regex lst)
  (filter (lambda (x) (string-match regex x)) lst) )
```

pattern->regexp [procedure]

(pattern->regexp PATTERN)

Converts the file-pattern PATTERN into a regular expression.

```
(pattern->regexp "foo.*") ==> "foo\\..*"
```

regexp [procedure]

(regexp STRING)

Returns a precompiled regular expression object for string.

regexp? [procedure]

(regexp? X)

Returns #t if X is a precompiled regular expression, or #f otherwise.

string-match [procedure]

string-match-positions [procedure]

(string-match REGEXP STRING [START])

(string-match-positions REGEXP STRING [START])

Matches the regular expression in REGEXP (a string or a precompiled regular expression) with STRING and returns either #f if the match failed, or a list of matching groups, where the first element is the complete match. If the optional argument START is supplied, it specifies the starting position in STRING. For each matching group the result-list contains either: #f for a non-matching but optional group; a list of start- and end-position of the match in STRING (in the case of string-match-positions); or the matching substring (in the case of string-match). Note that the exact string is matched. For searching a pattern inside a string, see below.

string-search [procedure]

string-search-positions [procedure]

(string-search REGEXP STRING [START [RANGE]])

(string-search-positions REGEXP STRING [START [RANGE]])

Searches for the first match of the regular expression in REGEXP with STRING. The search can be limited to RANGE characters.

string-split-fields [procedure]

(string-split-fields REGEXP STRING [MODE [START]])

Splits STRING into a list of fields according to MODE, where MODE can be the keyword #:infix (REGEXP matches field separator), the keyword #:suffix (REGEXP matches field terminator) or #t (REGEXP matches field), which is the default.

string-substitute [procedure]

`(string-substitute REGEXP SUBST STRING [INDEX])`

Searches substrings in `STRING` that match `REGEXP` and substitutes them with the string `SUBST`. The substitution can contain references to subexpressions in `REGEXP` with the `\NUM` notation, where `NUM` refers to the `NUM`th parenthesized expression. The optional argument `INDEX` defaults to 1 and specifies the number of the match to be substituted. Any non-numeric index specifies that all matches are to be substituted.

```
(string-substitute "([0-9]+) (eggs|chicks)"
                  "2 (1)" "99 eggs or 99 chicks" 2)
==> "99 eggs or chicks (99)"
```

string-substitute* [procedure]

`(string-substitute* STRING SMAP)`

Substitutes elements of `STRING` according to `SMAP`. `SMAP` should be an association-list where each element of the list is a pair of the form `(MATCH . REPLACEMENT)`. Every occurrence of the regular expression `MATCH` in `STRING` will be replaced by the string `REPLACEMENT`.

```
(string-substitute* "<h1>Hello, world!</h1>"
                    '(("<[/A-Za-z0-9]+>" . "")))

==> "Hello, world!"
```

5.17 Unit syntax-case

Hieb's and Dybvig's hygienic macro package. Provides `syntax-case` and `syntax-rules`. A postscript manual can be found here: [Technical Report #356](#)

Notes:

- The alternative form
`(define-syntax (keyword var) ...)`
 is allowed for `define-syntax`.
- The module system described in the *Chez Scheme Uses Manual* is supported (including separate compilation). When `import` or `import-only` is used with an argument that names a module that is currently not defined, then the current `include-path` (and the `repository-path` as well) is searched for a source-file of the same name (possibly with the extension `.scm`), which (if found) will be “visited” (it's module- and syntax-definitions are processed) using the procedure `visit`. Note that exported identifiers must be defined via `define` or `define-syntax`. Other defining forms (like `define-values`) are not recognized as exporting definitions.
 There are currently no built-in modules.
- To use the macro-system in compiled or interpreted code, just give the `-hygienic` option to the compiler or interpreter. The `syntax-case` unit has only to be declared as used if compiled code invokes `macroexpand` or `eval` with high-level macro syntax forms.
- `define-syntax` can not be used inside an `eval-when` form.

Here is a small example that demonstrates separate compilation:

Let's say we have one file `foo.scm` that defines a module:

```
(module foo (pr (bar baz))
  (define pr print)
  (define baz 99)
  (define-syntax bar
    (syntax-rules ()
      [(_ x) (list baz 'x)] ) ) )
```

and another that uses it (`use-foo.scm`):

```
(load "foo.so")    ; (require 'foo) would also work

(import foo)
(pr (bar hello))
```

Compiling the files like this will lead to one dynamically loadable library and a plain executable:

```
$ csc -s -hygienic foo.scm
$ csc -hygienic use-foo.scm
$ use-foo
$ (99 hello)
```

The `export` declaration can be used to export identifiers exported from modules defined in a given source file. These exports will then be visible as normal toplevel variables in external code that loads or links with this file. The rationale behind this is to make it possible to create libraries and extensions that use modules internally, but still can be used in client code that doesn't use modules.

visit

[procedure]

```
(visit FILENAME)
```

Reads all toplevel expressions from the given file and expands all syntax, extracting module- and syntax-information to be subsequently used during the current compilation or interpretation of modules.

5.18 Unit `srfi-18`

A simple multithreading package. This threading package follows largely the specification of SRFI-18. For more information see the documentation for [SRFI-18](#)

Notes:

- When an uncaught exception (i.e. an error) is signalled in a thread other than the primordial thread and warnings are enabled (see: `enable-warnings`, then a warning message is written to the port that is the value of `(current-error-port)`.
- Blocking I/O will block all threads, except for some socket operations (see the section about the `tcp` unit).
- It is generally not a good idea for one thread to call a continuation created by another thread, if `dynamic-wind` is involved.

- When more than one thread compete for the current time-slice, the thread that was waiting first will become the next runnable thread.
- The dynamic environment of a thread consists of the following state:
 - The current input-, output- and error-port
 - The current exception handler
 - The values of all current parameters (created by `make-parameter`)
 - Any pending `dynamic-wind` thunks.

The following procedures are provided, in addition to the procedures defined in SRFI-18:

thread-deliver-signal! [procedure]

(thread-deliver-signal! THREAD X)

This will cause `THREAD` to signal the condition `X` once it is scheduled for execution. After signalling the condition, the thread continues with its normal execution.

thread-quantum [procedure]

(thread-quantum THREAD)

Returns the quantum of `THREAD`, which is an exact integer specifying the approximate time-slice of the thread.

thread-quantum-set! [procedure]

(thread-quantum-set! THREAD QUANTUM)

Sets the quantum of `THREAD` to `QUANTUM`.

5.19 Unit format

format [procedure]

(format DESTINATION FORMAT-STRING . ARGUMENTS)

An almost complete implementation of Common LISP format description according to the CL reference book **Common LISP** from Guy L. Steele, Digital Press. This code was originally part of SLIB. The author is Dirk Lutzebaeck.

Returns `#t`, `#f` or a string; has side effect of printing according to `FORMAT-STRING`. If `DESTINATION` is `#t`, the output is to the current output port and `#t` is returned. If `DESTINATION` is `#f`, a formatted string is returned as the result of the call. If `DESTINATION` is a string, `DESTINATION` is regarded as the format string; `FORMAT-STRING` is then the first argument and the output is returned as a string. If `DESTINATION` is a number, the output is to the value of (`current-error-port`). Otherwise `DESTINATION` must be an output port and `#t` is returned.

`FORMAT-STRING` must be a string. In case of a formatting error `format` returns `#f` and prints a message on the value of (`current-error-port`). Characters are output as if the string were output by the `display` function with the exception of those prefixed by a tilde (~). For a detailed description of the `FORMAT-STRING` syntax please consult a Common LISP format reference manual. A list of all supported, non-supported and extended directives can be found in `format.txt`.

This unit uses definitions from the `extras` unit.

`format` implements [SRFI-28](#)

5.20 Unit `posix`

This unit provides services as used on many UNIX-like systems. Note that the following definitions are not available on non-UNIX systems like Windows or DOS.

This unit uses the `regex` and `extras` units.

All errors related to failing file-operations will signal a condition of kind `(exn i/o file)`.

5.20.1 Directories

change-directory [procedure]
 `(change-directory NAME)`

Changes the current working directory to `NAME`.

current-directory [procedure]
 `(current-directory)`

Returns the name of the current working directory.

create-directory [procedure]
 `(create-directory NAME)`

Creates a directory with the pathname `NAME`.

delete-directory [procedure]
 `(delete-directory NAME)`

Deletes the directory with the pathname `NAME`. The directory has to be empty.

directory [procedure]
 `(directory PATHNAME)`

Returns a list with all files that are contained in the directory with the name `PATHNAME`.

directory? [procedure]
 `(directory? NAME)`

Returns `#t` if there exists a file with the name `NAME` and if that file is a directory, or `#f` otherwise.

glob [procedure]
 `(glob PATTERN1 ...)`

Returns a list of the pathnames of all existing files matching `PATTERN1 ...`, which should be strings containing the usual file-patterns (with `*` matching zero or more characters and `?` matching zero or one character).

5.20.2 Pipes

call-with-input-pipe [procedure]

call-with-output-pipe [procedure]

(call-with-input-pipe CMDLINE PROC [MODE])

(call-with-output-pipe CMDLINE PROC [MODE])

Call PROC with a single argument: a input- or output port for a pipe connected to the subprocess named in CMDLINE. If PROC returns normally, the pipe is closed and any result values are returned.

close-input-pipe [procedure]

close-output-pipe [procedure]

(close-input-pipe PORT)

(close-output-pipe PORT)

Closes the pipe given in PORT and waits until the connected subprocess finishes.

create-pipe [procedure]

(create-pipe)

The fundamental pipe-creation operator. Calls the C function `pipe()` and returns 2 values: the file-descriptors of the input- and output-ends of the pipe.

open-input-pipe [procedure]

(open-input-pipe CMDLINE [MODE])

Spawns a subprocess with the command-line string CMDLINE and returns a port, from which the output of the process can be read. If MODE is specified, it should be the keyword `#:text` (the default) or `#:binary`.

open-output-pipe [procedure]

(open-output-pipe CMDLINE [MODE])

Spawns a subprocess with the command-line string CMDLINE and returns a port. Anything written to that port is treated as the input for the process. If MODE is specified, it should be the keyword `#:text` (the default) or `#:binary`.

pipe/buf [limit]

This variable contains the maximal number of bytes that can be written atomically into a pipe or FIFO.

with-input-from-pipe [procedure]

with-output-to-pipe [procedure]

(with-input-from-pipe CMDLINE THUNK [MODE])

(with-output-to-pipe CMDLINE THUNK [MODE])

Temporarily set the value of `current-input-port/current-output-port` to a port for a pipe connected to the subprocess named in CMDLINE and call the procedure THUNK with no arguments. After THUNK returns normally the pipe is closed and the standard input-/output port is restored to its previous value and any result values are returned.

```
(with-output-to-pipe
  "gs -dNOPAUSE -sDEVICE=jpeg -dBATCH -sOutputFile=signballs.jpg -g600x600 -q -"
  (lambda ()
    (print #<<EOF
%!IOPSC-1993 %%Creator: HAYAKAWA Takashi<xxxxxxxx@xx.xxxxxx.xx.xx>
/C/neg/d/mul/R/rlneto/E/exp/H{{cvx def}repeat}def/T/dup/g/gt/r/roll/J/iffalse 8
H/A/copy(z&v4QX&93r9AXYQOZomQalxS2w!!O&vMYa43d6r93rMYvx2dca!D&cjSnjSnjjS3o!v&6A
X&55SAXM1CD7AjYxTTd62rmxCnTdSST0g&12wECST!&!J0g&D1!&xM0!J0g!l&544dC2Ac96ra!m&3A
F&&vGoGSnCT0g&wDmlvGoS8wpn6wpS2wTCpS1Sd7ov7Uk7o4Qkdw!&Mv1x1S7oZES3w!J!J!Q&7185d
Z&l1x1CS9d9nE4!k&X&MY7!&1!J!x&jdnjdS3odS!N&mmx1C2wEc!G&150Nx4!n&2o!j&43r!U&0777d
]&2AY2A776ddT4oS3oSnmVC00VVORRR45E42063rNz&v7UX&UOzF!F!J! [&44ETCnVn!a&1CDN!Y&0M
V1c&j2AYdjMjdjd!o&1r!M){( )T 0 4 3 r put T(/)g{T(9)g{cvn}{cvi}J}{($)g[]J}J
cvx}forall/moveto/p/floor/w/div/S/add 29 H{[{}setgray fill}for Y}for showpage
EOF
) ) )
```

5.20.3 Fifos

create-fifo [procedure]

(create-fifo FILENAME [MODE])

Creates a FIFO with the name FILENAME and the permission bits MODE, which defaults to

(+ perm/irwxu perm/irwxg perm/irwxo)

fifo? [procedure]

(fifo? FILENAME)

Returns #t if the file with the name FILENAME names a FIFO.

5.20.4 File descriptors and low-level I/O

duplicate-filen [procedure]

(duplicate-filen OLD [NEW])

If NEW is given, then the file-descriptor NEW is opened to access the file with the file-descriptor OLD. Otherwise a fresh file-descriptor accessing the same file as OLD is returned.

file-close [procedure]

(file-close FILENO)

Closes the input/output file with the file-descriptor FILENO.

file-open [procedure]

(file-open FILENAME FLAGS [MODE])

Opens the file specified with the string FILENAME and open-flags FLAGS using the C function `open()`. On success a file-descriptor for the opened file is returned. FLAGS should be a bitmask containing one or more of the `open/...` values `ored` together using `bitwise-ior` (or simply added together). The optional MODE should be a bitmask

composed of one or more permission values like `perm/irusr` and is only relevant when a new file is created. The default mode is `perm/irwxu | perm/irgrp | perm/iroth`.

file-mkstemp

[procedure]

`(file-mkstemp TEMPLATE-FILENAME)`

Create a file based on the given `TEMPLATE-FILENAME`, in which the six last characters must be “XXXXXX”. These will be replaced with a string that makes the filename unique. The file descriptor of the created file and the generated filename is returned. See the `mkstemp(3)` manual page for details on how this function works. The template string given is not modified.

Example usage:

```
(let-values (((fd temp-path) (file-mkstemp "/tmp/mytemporary.XXXXXX"))
  (let ((temp-port (open-output-file* fd)))
    (format temp-port "This file is ~A.~%" temp-path)
    (close-output-port temp-port)))
```

file-read

[procedure]

`(file-read FILENO SIZE [BUFFER])`

Reads `SIZE` bytes from the file with the file-descriptor `FILENO`. If a string or bytevector is passed in the optional argument `BUFFER`, then this string will be destructively modified to contain the read data. This procedure returns a list with two values: the buffer containing the data and the number of bytes read.

file-select

[procedure]

`(file-select READFDLIST WRITEFDLIST [TIMEOUT])`

Waits until any of the file-descriptors given in the lists `READFDLIST` and `WRITEFDLIST` is ready for input or output, respectively. If the optional argument `TIMEOUT` is given and not false, then it should specify the number of seconds after which the wait is to be aborted. This procedure returns two values: the lists of file-descriptors ready for input and output, respectively. `READFDLIST` and **`WRITEFDLIST`** may also be file-descriptors instead of lists. In this case the returned values are booleans indicating whether input/output is ready by `#t` or `#f` otherwise. You can also pass `#f` as `READFDLIST` or `WRITEFDLIST` argument, which is equivalent to `()`.

file-write

[procedure]

`(file-write FILENO BUFFER [SIZE])`

Writes the contents of the string or bytevector `BUFFER` into the file with the file-descriptor `FILENO`. If the optional argument `SIZE` is given, then only the specified number of bytes are written.

fileno/stdin

[file descriptor]

fileno/stdout

[file descriptor]

fileno/stderr

[file descriptor]

These variables contain file-descriptors for the standard I/O files.

open/rdonly	[flag]
open/wronly	[flag]
open/rdwr	[flag]
open/read	[flag]
open/write	[flag]
open/creat	[flag]
open/append	[flag]
open/excl	[flag]
open/noctty	[flag]
open/nonblock	[flag]
open/trunc	[flag]
open/sync	[flag]
open/fsync	[flag]
open/binary	[flag]
open/text	[flag]

Flags for use with `file-open`.

open-input-file*	[procedure]
open-output-file*	[procedure]

(`open-input-file* FILENO [OPENMODE]`)
 (`open-output-file* FILENO [OPENMODE]`)

Opens file for the file-descriptor `FILENO` for input or output and returns a port. `FILENO` should be a positive exact integer. `OPENMODE` specifies an additional mode for opening the file (currently only the keyword `#:append` is supported, which opens an output-file for appending).

port->fileno	[procedure]
------------------------	-------------

(`port->fileno PORT`)

If `PORT` is a file-port, then a file-descriptor is returned for this port. Otherwise an error is signaled.

5.20.5 Retrieving file attributes

file-modification-time	[procedure]
-------------------------------	-------------

(`file-modification-time FILE`)

Returns time (in seconds) of the last modification of `FILE`. `FILE` may be a filename or a file-descriptor. If the file does not exist, an error is signaled.

file-position	[procedure]
----------------------	-------------

(`file-position FILE`)

Returns the current file position of `FILE`, which should be a port or a file-descriptor.

file-size	[procedure]
------------------	-------------

(`file-size FILENAME`)

Returns the size of the file designated by `FILE`. `FILE` may be a filename or a file-descriptor. If the file does not exist, an error is signaled.

5.20.6 Changing file attributes

file-truncate [procedure]

(file-truncate FILE OFFSET)

Truncates the file **FILE** to the length **OFFSET**, which should be an integer. If the file-size is smaller or equal to **OFFSET** then nothing is done. **FILE** should be a filename or a file-descriptor.

set-file-position! [procedure]

(set-file-position! FILE POSITION [WHENCE])

Sets the current read/write position of **FILE** to **POSITION**, which should be an exact integer. **FILE** should be a port or a file-descriptor. **WHENCE** specifies how the position is to interpreted and should be one of the values **seek/set**, **seek/cur** and **seek/end**. It defaults to **seek/set**.

Exceptions: (exn bounds), (exn i/o file)

5.20.7 Processes

current-process-id [procedure]

(current-process-id)

Returns the process ID of the current process.

parent-process-id [procedure]

(parent-process-id)

Returns the process ID of the parent of the current process.

process-execute [procedure]

(process-execute PATHNAME [LIST])

Creates a new child process and replaces the running process with it using the UNIX system call **execv()**. If the optional argument **LIST** is given, then it should contain a list of strings which are passed as arguments to the subprocess.

process-fork [procedure]

(process-fork [THUNK])

Creates a new child process with the UNIX system call **fork()**. Returns either the PID of the child process or 0. If **THUNK** is given, then the child process calls it as a procedure with no arguments and terminates.

process-run [procedure]

(process-run PATHNAME [LIST])

Creates a new child process using the UNIX system call **fork()** that executes the program given by the string **PATHNAME** using the UNIX system call **execv()**. The PID of the new process is returned. If **LIST** is not specified, then **PATHNAME** is passed to a program named by the environment variable **SHELL** (or **/bin/sh**, if the variable is not defined), so usual argument expansion can take place.

process-signal [procedure]
 (process-signal PID [SIGNAL])

Sends **SIGNAL** to the process with the id **PID** using the UNIX system call **kill()**. **SIGNAL** defaults to the value of the variable **signal/term**.

process-wait [procedure]
 (process-wait [PID [NOHANG]])

Suspends the current process until the child process with the id **PID** has terminated using the UNIX system call **waitpid()**. If **PID** is not given, then this procedure waits for any child process. If **NOHANG** is given and not **#f** then the current process is not suspended. This procedure returns three values:

- **PID** or 0, if **NOHANG** is true and the child process has not terminated yet;
- **#t** if the process exited normally or **#f** otherwise;
- either the exit status, if the process terminated normally or the signal number that terminated/stopped the process.

process [procedure]
 (process COMMANDLINE)

Passes the string **COMMANDLINE** to the host-system's shell that is invoked as a sub-process and returns three values: an input port from which data written by the sub-process can be read, an output port from which any data written to will be received as input in the sub-process and the process-id of the started sub-process. All I/O from/to ports returned by **process** is fully nonblocking.

sleep [procedure]
 (sleep SECONDS)

Puts the process to sleep for **SECONDS**. Returns either 0 if the time has completely elapsed, or the number of remaining seconds, if a signal occurred.

5.20.8 Symbolic links

create-symbolic-link [procedure]
 (create-symbolic-link OLDNAME NEWNAME)

Creates a symbolic link with the filename **NEWNAME** that points to the file named **OLDNAME**.

read-symbolic-link [procedure]
 (read-symbolic-link FILENAME)

Returns the filename to which the symbolic link **FILENAME** points.

5.20.9 Permissions, owners, users and groups

file-owner [procedure]
 (file-owner FILE)

Returns the user-id of **FILE**. **FILE** may be a filename or a file-descriptor.

file-permissions [procedure]

(file-permissions FILE)

Returns the permission bits for FILE. You can test this value by performing bitwise operations on the result and the `perm/...` values. FILE may be a filename or a file-descriptor.

file-read-access? [procedure]**file-write-access?** [procedure]**file-execute-access?** [procedure]

(file-read-access? FILENAME)

(file-write-access? FILENAME)

(file-execute-access? FILENAME)

These procedures return `#t` if the current user has read, write or execute permissions on the file named FILENAME.

change-file-mode [procedure]

(change-file-mode FILENAME MODE)

Changes the current file mode of the file named FILENAME to MODE using the `chmod()` system call. The `perm/...` variables contain the various permission bits and can be combined with the `bitwise-ior` procedure.

change-file-owner [procedure]

(change-file-owner FILENAME UID GID)

Changes the owner information of the file named FILENAME to the user- and group-ids UID and GID (which should be exact integers) using the `chown()` system call.

current-user-id [procedure]**current-group-id** [procedure]**current-effective-user-id** [procedure]**current-effective-group-id** [procedure]

(current-user-id)

(current-group-id)

(current-effective-user-id)

(current-effective-group-id)

Return the user- and group-ids of the current process.

group-information [procedure]

(group-information GROUP)

If GROUP specifies a valid group-name or group-id, then this procedure returns four values: the group-name, the encrypted group password, the group ID and a list of the names of all group members. If no group with the given name or ID exists, then `#f` is returned.

get-groups [procedure]

(get-groups)

Returns a list with the supplementary group IDs of the current user.

set-groups! [procedure]

(set-groups! GIDLIST)

Sets the supplementary group IDs of the current user to the IDs given in the list GIDLIST.

Only the superuser may invoke this procedure.

initialize-groups [procedure]

(initialize-groups USERNAME BASEGID)

Sets the supplementary group IDs of the current user to the IDs from the user with name USERNAME (a string), including BASEGID.

Only the superuser may invoke this procedure.

perm/irusr	[permission bits]
perm/iwusr	[permission bits]
perm/ixusr	[permission bits]
perm/irgrp	[permission bits]
perm/iwgrp	[permission bits]
perm/ixgrp	[permission bits]
perm/iroth	[permission bits]
perm/iwoth	[permission bits]
perm/ixoth	[permission bits]
perm/irwxu	[permission bits]
perm/irwxg	[permission bits]
perm/irwxo	[permission bits]
perm/isvtx	[permission bits]
perm/isuid	[permission bits]
perm/isgid	[permission bits]

These variables contain permission bits as used in `change-file-mode`.

set-user-id! [procedure]

(set-user-id! UID)

Sets the effective user id of the current process to UID, which should be a positive integer.

user-information [procedure]

(user-information USER)

If USER specifies a valid username (as a string) or user ID, then the user database is consulted and a list of 7 values are returned: the user-name, the encrypted password, the user ID, the group ID, a user-specific string, the home directory and the default shell. If no user with this name or ID can be found, then **#f** is returned.

5.20.10 Record locking

file-lock [procedure]

(file-lock PORT [START [LEN]])

Locks the file associated with PORT for reading or writing (according to whether PORT is an input- or output-port). START specifies the starting position in the file to be

locked and defaults to 0. `LEN` specifies the length of the portion to be locked and defaults to `#t`, which means the complete file. `file-lock` returns a “lock”-object.

file-lock/blocking [procedure]
`(file-lock/blocking PORT [START [LEN]])`

Similar to `file-lock`, but if a lock is held on the file, the current process blocks (including all threads) until the lock is released.

file-test-lock [procedure]
`(file-test-lock PORT [START [LEN]])`

Tests whether the file associated with `PORT` is locked for reading or writing (according to whether `PORT` is an input- or output-port) and returns either `#f` or the process-id of the locking process.

file-unlock [procedure]
`(file-unlock LOCK)`

Unlocks the previously locked portion of a file given in `LOCK`.

5.20.11 Signal handling

set-alarm! [procedure]
`(set-alarm! SECONDS)`

Sets an internal timer to raise the `signal/alrm` after `SECONDS` are elapsed. You can use the `set-signal-handler!` procedure to write a handler for this signal.

set-signal-handler! [procedure]
`(set-signal-handler! SIGNAL PROC)`

Establishes the procedure of one argument `PROC` as the handler for the signal with the code `SIGNAL`. `PROC` is called with the signal number as its sole argument. If the argument `PROC` is `#f` then this signal will be ignored.

set-signal-mask! [procedure]
`(set-signal-mask! SIGLIST)`

Sets the signal mask of the current process to block all signals given in the list `SIGLIST`. Signals masked in that way will not be delivered to the current process.

signal/term	[signal code]
signal/kill	[signal code]
signal/int	[signal code]
signal/hup	[signal code]
signal/fpe	[signal code]
signal/ill	[signal code]
signal/segv	[signal code]
signal/abrt	[signal code]
signal/trap	[signal code]
signal/quit	[signal code]
signal/alarm	[signal code]
signal/vtalm	[signal code]
signal/prof	[signal code]
signal/io	[signal code]
signal/urg	[signal code]
signal/chld	[signal code]
signal/cont	[signal code]
signal/stop	[signal code]
signal/tstp	[signal code]
signal/pipe	[signal code]
signal/xcpu	[signal code]
signal/xfsz	[signal code]
signal/usr1	[signal code]
signal/usr2	[signal code]
signal/winch	[signal code]

These variables contain signal codes for use with `process-signal` or `set-signal-handler!`.

5.20.12 Environment access

current-environment [procedure]
 (current-environment)

Returns a association list of the environment variables and their current values.

Note: Under Mac OS X, this procedure always returns the empty list.

setenv [procedure]
 (setenv VARIABLE VALUE)

Sets the environment variable named `VARIABLE` to `VALUE`. Both arguments should be strings. If the variable is not defined in the environment, a new definition is created.

unsetenv [procedure]
 (unsetenv VARIABLE)

Removes the definition of the environment variable `VARIABLE` from the environment of the current process. If the variable is not defined, nothing happens.

5.20.13 Memory mapped I/O

map-file-to-memory [procedure]

(map-file-to-memory ADDRESS LEN PROTECTION FLAG FILENO [OFFSET])

Maps a section of a file to memory using the C function `mmap()`. ADDRESS should be a foreign pointer object or `#f`; LEN specifies the size of the section to be mapped; PROTECTION should be one or more of the flags `prot/read`, `prot/write`, `prot/exec` or `prot/none` **bitwise-ored** together; FLAG should be one or more of the flags `map/fixed`, `map/shared`, `map/private`, `map/anonymous` or `map/file`; FILENO should be the file-descriptor of the mapped file. The optional argument OFFSET gives the offset of the section of the file to be mapped and defaults to 0. This procedure returns an object representing the mapped file section. The procedure `move-memory!` can be used to access the mapped memory.

memory-mapped-file-pointer [procedure]

(memory-mapped-file-pointer MMAP)

Returns a machine pointer to the start of the memory region to which the file is mapped.

unmap-file-from-memory [procedure]

(unmap-file-from-memory MMAP [LEN])

Unmaps the section of a file mapped to memory using the C function `munmap()`. MMAP should be a mapped file as returned by the procedure `map-file-to-memory`. The optional argument LEN specifies the length of the section to be unmapped and defaults to the complete length given when the file was mapped.

5.20.14 Time routines

seconds->local-time [procedure]

(seconds->local-time SECONDS)

Breaks down the time value represented in SECONDS into a 10 element vector of the form `#(seconds minutes hours mday month year wday yday dstflag timezone)`, in the following format:

- seconds: the number of seconds after the minute (0 - 59)
- minutes: the number of minutes after the hour (0 - 59)
- hours: the number of hours past midnight (0 - 23)
- mday: the day of the month (1 - 31)
- month: the number of months since january (0 - 11)
- year: the number of years since 1900
- wday: the number of days since Sunday (0 - 6)
- yday: the number of days since January 1 (0 - 365)
- dstflag: a flag that is true if Daylight Saving Time is in effect at the time described.
- timezone: the difference between UTC and the latest local standard time, in seconds west of UTC.

seconds->string [procedure]
 (seconds->string SECONDS)

Converts the local time represented in SECONDS into a string of the form "Tue May 21 13:46:22 1991\n".

seconds->utc-time [procedure]
 (seconds->utc-time SECONDS)

Similar to seconds->local-time, but interpretes SECONDS as UTC time.

time->string [procedure]
 (time->string VECTOR)

Converts the broken down time represented in the 10 element vector VECTOR into a string of the form "Tue May 21 13:46:22 1991\n".

5.20.15 *Raw* exit

_exit [procedure]
 (_exit [CODE])

Exits the current process without flushing any buffered output (using the C function `_exit`). Note that the `exit-handler` is not called when this procedure is invoked. The optional return-code CODE defaults to 0.

5.20.16 ERRNO values

errno/perm	[error code]
errno/noent	[error code]
errno/srch	[error code]
errno/intr	[error code]
errno/io	[error code]
errno/noexec	[error code]
errno/badf	[error code]
errno/child	[error code]
errno/nomem	[error code]
errno/acces	[error code]
errno/fault	[error code]
errno/busy	[error code]
errno/notdir	[error code]
errno/isdir	[error code]
errno/INVAL	[error code]
errno/mfile	[error code]
errno/nospc	[error code]
errno/spipe	[error code]
errno/pipe	[error code]
errno/again	[error code]
errno/rofs	[error code]
errno/wouldblock	[error code]

These variables contain error codes as returned by `errno`.

5.20.17 Finding files

find-files [procedure]

(find-files DIRECTORY PREDICATE [ACTION [IDENTITY [LIMIT]]])

Recursively traverses the contents of **DIRECTORY** (which should be a string) and invokes the procedure **ACTION** for all files for which the procedure **PREDICATE** is true. **PREDICATE** may be a procedure of one argument or a regular-expression string. **ACTION** should be a procedure of two arguments: the currently encountered file and the result of the previous invocation of **ACTION**, or, if this is the first invocation, the value of **IDENTITY**. **ACTION** defaults to **cons**, **IDENTITY** defaults to **()**. **LIMIT** should be a procedure of one argument that is called for each nested directory and which should return true, if that directory is to be traversed recursively. **LIMIT** may also be an exact integer that gives the maximum recursion depth. A depth of 0 means the files in the specified directory are traversed but not any nested directories. **LIMIT** may also be **#f** (the default), which is equivalent to **(constantly #t)**.

Note that **ACTION** is called with the full pathname of each file, including the directory prefix.

5.20.18 Getting the hostname and system information

get-host-name [procedure]

(get-host-name)

Returns the hostname of the machine that this process is running on.

system-information [procedure]

(system-information)

Invokes the UNIX system call **uname()** and returns 5 values: system-name, node-name, OS release, OS version and machine.

5.20.19 Setting a files buffering mode

set-buffering-mode! [procedure]

(set-buffering-mode! PORT MODE [BUFSIZE])

Sets the buffering-mode for the file associated with **PORT** to **MODE**, which should be one of the keywords **#:full**, **#:line** or **#:none**. If **BUFSIZE** is specified it determines the size of the buffer to be used (if any).

5.20.20 Terminal ports

terminal-name [procedure]

(terminal-name PORT)

Returns the name of the terminal that is connected to **PORT**.

terminal-port? [procedure]

(terminal-port? PORT)

Returns **#t** if **PORT** is connected to a terminal and **#f** otherwise.

5.20.21 How Scheme procedures relate to UNIX C functions

change-directory	chdir
change-file-mode	chmod
change-file-owner	chown
create-directory	mkdir
create-fifo	mkfifo
create-pipe	pipe
create-symbolic-link	link
current-directory	curdir
current-effective-groupd-id	getegid
current-effective-user-id	geteuid
current-group-id	getgid
current-parent-id	getppid
current-process-id	getpid
current-user-id	getuid
delete-directory	rmdir
duplicate-fileno	dup/dup2
_exit	_exit
file-close	close
file-execute-access?	access

file-open	open
file-lock	fcntl
file-position	ftell/lseek
file-read	read
file-read-access?	access
file-select	select
file-test-lock	fcntl
file-truncate	truncate/ftruncate
file-unlock	fcntl
file-write	write
file-write-access?	access
get-groups	getgroups
get-host-name	gethostname
initialize-groups	initgroups
map-file-to-memory	mmap
open-input-file*	fdopen
open-output-file*	fdopen
open-input-pipe	popen
open-output-pipe	popen

```
port->fileno
    fileno

process-execute
    execvp

process-fork
    fork

process-signal
    kill

process-wait
    waitpid

close-input-pipe
    pclose

close-output-pipe
    pclose

read-symbolic-link
    readlink

seconds->local-time
    localtime

seconds->string
    ctime

seconds->utc-time
    gmtime

set-alarm!
    alarm

set-buffering-mode!
    setvbuf

set-file-position!
    fseek/seek

set-groups!
    setgroups

set-signal-mask!
    sigprocmask

set-user-id!
    setuid

setenv    setenv/putenv

sleep    sleep

system-information
    uname
```

```

terminal-name
    ttyname

terminal-port?
    isatty

time->string
    asctime

unsetenv  putenv

unmap-file-from-memory
    munmap

user-information
    getpwnam/getpwuid

```

5.21 Unit `utils`

This unit contains some utility procedures for Shell scripting and for some file operations.

This unit uses the `extras` and `regex` units.

5.21.1 Pathname operations

absolute-pathname? [procedure]
 (absolute-pathname? PATHNAME)

Returns `#t` if the string `PATHNAME` names an absolute pathname, and returns `#f` otherwise.

decompose-pathname [procedure]
 (decompose-pathname PATHNAME)

Returns three values: the directory-, filename- and extension-components of the file named by the string `PATHNAME`. For any component that is not contained in `PATHNAME`, `#f` is returned.

make-pathname [procedure]
make-absolute-pathname [procedure]
 (make-pathname DIRECTORY FILENAME [EXTENSION])
 (make-absolute-pathname DIRECTORY FILENAME [EXTENSION])

Returns a string that names the file with the components `DIRECTORY`, `FILENAME` and (optionally) `EXTENSION`. `DIRECTORY` can be `#f` (meaning no directory component), a string or a list of strings. `FILENAME` and `EXTENSION` should be strings or `#f`. `make-absolute-pathname` returns always an absolute pathname.

pathname-directory [procedure]
 (pathname-directory PATHNAME)

pathname-file [procedure]
 (pathname-file PATHNAME)

pathname-extension [procedure]
 (pathname-extension PATHNAME)

Accessors for the components of PATHNAME. If the pathname does not contain the accessed component, then #f is returned.

pathname-replace-directory [procedure]
 (pathname-replace-directory PATHNAME DIRECTORY)

pathname-replace-file [procedure]
 (pathname-replace-file PATHNAME FILENAME)

pathname-replace-extension [procedure]
 (pathname-replace-extension PATHNAME EXTENSION)

Return a new pathname with the specified component of PATHNAME replaced by a new value.

pathname-strip-directory [procedure]
 (pathname-strip-directory PATHNAME)

pathname-strip-extension [procedure]
 (pathname-strip-extension PATHNAME)

Return a new pathname with the specified component of PATHNAME stripped.

5.21.2 Temporary files

create-temporary-file [procedure]
 (create-temporary-file [EXTENSION])

Creates an empty temporary file and returns its pathname. If EXTENSION is not given, then .tmp is used. If the environment variable TMPDIR, TEMP or TMP is set, then the pathname names a file in that directory.

5.21.3 Deleting a file without signalling an error

delete-file* [procedure]
 (delete-file* FILENAME)

If the file FILENAME exists, it is deleted and #t is returned. If the file does not exist, nothing happens and #f is returned.

5.21.4 Iterating over input lines and files

for-each-line [procedure]
 (for-each-line PROCEDURE [PORT])

Calls PROCEDURE for each line read from PORT (which defaults to the value of (current-input-port)). The argument passed to PROCEDURE is a string with the contents of the line, excluding any line-terminators. When all input has been read from the port, for-each-line returns some unspecified value.

for-each-argv-line [procedure]
 (for-each-argv-line PROCEDURE)

Opens each file listed on the command line in order, passing one line at a time into PROCEDURE. The filename - is interpreted as (current-input-port). If no arguments are given on the command line it again uses the value of (current-input-port).

This code will act as a simple Unix cat(1) command:

```
(for-each-argv-line print)
```

5.21.5 Executing shell commands with formatstring and error checking

system* [procedure]
 (system* FORMATSTRING ARGUMENT1 ...)

Similar to (system (sprintf FORMATSTRING ARGUMENT1 ...)), but signals an error if the invoked program should return a nonzero exit status.

5.21.6 Reading a file's contents

read-all [procedure]
 (read-all [FILE-OR-PORT])

If FILE-OR-PORT is a string, then this procedure returns the contents of the file as a string. If FILE-OR-PORT is a port, all remaining input is read and returned as a string. The port is not closed. If no argument is provided, input will be read from the port that is the current value of (current-input-port).

5.22 Unit tcp

This unit provides basic facilities for communicating over TCP sockets. The socket interface should be mostly compatible to the one found in PLT Scheme.

This unit uses the **extras** unit.

All errors related to failing network operations will raise a condition of kind (exn i/o network).

tcp-listen [procedure]
 (tcp-listen TCPPOINT [BACKLOG [HOST]])

Creates and returns a TCP listener object that listens for connections on TCPPOINT, which should be an exact integer. BACKLOG specifies the number of maximally pending connections (and defaults to 4). If the optional argument HOST is given and not #f, then only incoming connections for the given host (or IP) are accepted.

tcp-listener? [procedure]
 (tcp-listener? X)

Returns #t if X is a TCP listener object, or #f otherwise.

tcp-close [procedure]

(tcp-close LISTENER)

Reclaims any resources associated with LISTENER.

tcp-accept [procedure]

(tcp-accept LISTENER)

Waits until a connection is established on the port on which LISTENER is listening and returns two values: an input- and output-port that can be used to communicate with the remote process.

Note: this operation and any I/O on the ports returned will not block other running threads.

tcp-accept-ready? [procedure]

(tcp-accept-ready? LISTENER)

Returns **#t** if there are any connections pending on LISTENER, or **#f** otherwise.

tcp-listener-port [procedure]

(tcp-listener-port LISTENER)

Returns the port number assigned to LISTENER (If you pass 0 to **tcp-listen**, then the system will choose a port-number for you).

tcp-connect [procedure]

(tcp-connect HOSTNAME [TCPPOINT])

Establishes a client-side TCP connection to the machine with the name HOSTNAME (a string) at TCPPOINT (an exact integer) and returns two values: an input- and output-port for communicating with the remote process.

Note: any I/O on the ports returned will not block other running threads.

tcp-addresses [procedure]

(tcp-addresses PORT)

Returns two values for the input- or output-port PORT (which should be a port returned by either **tcp-accept** or **tcp-connect**): the IP address of the local and the remote machine that are connected over the socket associated with PORT. The returned addresses are strings in XXX.XXX.XXX.XXX notation.

tcp-abandon-port [procedure]

(tcp-abandon-port PORT)

Marks the socket port PORT as abandoned. This is mainly useful to close down a port without breaking the connection.

A very simple example follows. Say we have the two files **client.scm** and **server.scm**:

```
; client.scm
(define-values (i o) (tcp-connect "localhost" 4242))
(write-line "Good Bye!" o)
(print (read-line i))
```

```
; server.scm
(define l (tcp-listen 4242))
(define-values (i o) (tcp-accept l))
(write-line "Hello!" o)
(print (read-line i))
(close-input-port i)
(close-output-port o)
```

```
% csi -script server.scm &
[1] 1409
% csi -script client.scm
Good Bye!
Hello!
```

5.23 Unit `srfi-37`

Copyright (c) 2002 Anthony Carrico

A simple and flexible command-line option parsing facility. Options may be either short one-character options of the form `-X[ARGUMENT]` or long multicharacter ones of the form `--XXX[=ARGUMENT]`. Short options may be coalesced. An argument of the form `--` stops option processing. For more information take a look at the [SRFI-37 documentation](#).

An example:

```
#!/usr/local/bin/csi -script
;;; secho - display command-line arguments
```

```
(define nl 1)

(define help
  (option
    '(#\h "help") #f #f
    (lambda _
      (print "Usage: secho [OPTION] ARG ...
-h --help          show this text
-n --newline N      add N newline characters (default: 1)")
      (exit) ) ) )

(define newlines
  (option
    '(#\n "newline") #t #f
    (lambda (o n x vals)
      (set! nl (string->number x))
      vals) ) )

(for-each
  (lambda (x) (print* x #\space))
  (reverse
```



```

(args-fold
  (command-line-arguments)
  (list help newlines)
  (lambda (o n x vals)
    (error "unrecognized option" n) )
  cons
  '() ) ) )

(display (make-string nl #\newline))

```

5.24 Unit `lolevel`

This unit provides a number of handy low-level operations. **Use at your own risk.**

This unit uses the `srfi-4` and `extras` units.

5.24.1 Foreign pointers

address->pointer [procedure]

(address->pointer ADDRESS)

Creates a new foreign pointer object initialized to point to the address given in the integer ADDRESS.

allocate [procedure]

(allocate BYTES)

Returns a pointer to a freshly allocated region of static memory. This procedure could be defined as follows:

```
(define allocate (foreign-lambda c-pointer "malloc" integer))
```

free [procedure]

(free POINTER)

Frees the memory pointed to by POINTER. This procedure could be defined as follows:

```
(define free (foreign-lambda c-pointer "free" integer))
```

null-pointer [procedure]

(null-pointer)

Another way to say (address->pointer 0).

null-pointer? [procedure]

(null-pointer? PTR)

Returns `#t` if PTR contains a NULL pointer, or `#f` otherwise.

object->pointer [procedure]

(object->pointer X)

Returns a pointer pointing to the Scheme object X, which should be a non-immediate object. Note that data in the garbage collected heap moves during garbage collection.

pointer?	[procedure]
(pointer? X)	
Returns #t if X is a foreign pointer object, and #f otherwise.	
pointer->address	[procedure]
(pointer->address PTR)	
Returns the address, to which the pointer PTR points.	
pointer->object	[procedure]
(pointer->object PTR)	
Returns the Scheme object pointed to by the pointer PTR.	
pointer-offset	[procedure]
(pointer-offset PTR N)	
Returns a new pointer representing the pointer PTR increased by N.	
pointer-u8-ref	[procedure]
(pointer-u8-ref PTR)	
Returns the unsigned byte at the address designated by PTR.	
pointer-s8-ref	[procedure]
(pointer-s8-ref PTR)	
Returns the signed byte at the address designated by PTR.	
pointer-u16-ref	[procedure]
(pointer-u16-ref PTR)	
Returns the unsigned 16-bit integer at the address designated by PTR.	
pointer-s16-ref	[procedure]
(pointer-s16-ref PTR)	
Returns the signed 16-bit integer at the address designated by PTR.	
pointer-u32-ref	[procedure]
(pointer-u32-ref PTR)	
Returns the unsigned 32-bit integer at the address designated by PTR.	
pointer-s32-ref	[procedure]
(pointer-s32-ref PTR)	
Returns the signed 32-bit integer at the address designated by PTR.	
pointer-f32-ref	[procedure]
(pointer-f32-ref PTR)	
Returns the 32-bit float at the address designated by PTR.	
pointer-f64-ref	[procedure]
(pointer-f64-ref PTR)	
Returns the 64-bit double at the address designated by PTR.	

pointer-u8-set! [procedure]

(pointer-u8-set! PTR N)

Stores the unsigned byte N at the address designated by PTR.

pointer-s8-set! [procedure]

(pointer-s8-set! PTR N)

Stores the signed byte N at the address designated by PTR.

pointer-u16-set! [procedure]

(pointer-u16-set! PTR N)

Stores the unsigned 16-bit integer N at the address designated by PTR.

pointer-s16-set! [procedure]

(pointer-s16-set! PTR N)

Stores the signed 16-bit integer N at the address designated by PTR.

pointer-u32-set! [procedure]

(pointer-u32-set! PTR N)

Stores the unsigned 32-bit integer N at the address designated by PTR.

pointer-s32-set! [procedure]

(pointer-s32-set! PTR N)

Stores the 32-bit integer N at the address designated by PTR.

pointer-f32-set! [procedure]

(pointer-f32-set! PTR N)

Stores the 32-bit floating-point number N at the address designated by PTR.

pointer-f64-set! [procedure]

(pointer-f64-set! PTR N)

Stores the 64-bit floating-point number N at the address designated by PTR.

align-to-word [procedure]

(align-to-word PTR-OR-INT)

Accepts either a machine pointer or an integer as argument and returns a new pointer or integer aligned to the native word size of the host platform.

5.24.2 Tagged pointers

“Tagged” pointers are foreign pointer objects with an extra tag object.

tag-pointer [procedure]

(tag-pointer PTR TAG)

Creates a new tagged pointer object from the foreign pointer PTR with the tag TAG, which may be an arbitrary Scheme object.

tagged-pointer? [procedure]

(tagged-pointer? X TAG)

Returns **#t**, if X is a tagged pointer object with the tag TAG (using an **eq?** comparison), or **#f** otherwise.

pointer-tag [procedure]

(pointer-tag PTR)

If PTR is a tagged pointer object, its tag is returned. If PTR is a normal, untagged foreign pointer object **#f** is returned. Otherwise an error is signalled.

5.24.3 Extending procedures with data

extend-procedure [procedure]

(extend-procedure PROCEDURE X)

Returns a copy of the procedure PROCEDURE which contains an additional data slot initialized to X. If PROCEDURE is already an extended procedure, then its data slot is changed to contain X and the same procedure is returned.

extended-procedure? [procedure]

(extended-procedure? PROCEDURE)

Returns **#t** if PROCEDURE is an extended procedure, or **#f** otherwise.

procedure-data [procedure]

(procedure-data PROCEDURE)

Returns the data object contained in the extended procedure PROCEDURE.

set-procedure-data! [procedure]

(set-procedure-data! PROCEDURE X)

Changes the data object contained in the extended procedure PROCEDURE to X.

```
(define foo
  (letrec ((f (lambda () (procedure-data x)))
            (x #f) )
    (set! x (extend-procedure f 123))
    x) )
(foo)                                ==> 123
(set-procedure-data! foo 'hello)
(foo)                                ==> hello
```

5.24.4 Bytevectors

byte-vector [procedure]

(byte-vector FIXNUM ...)

Returns a freshly allocated byte-vector with FIXNUM ... as its initial contents.

byte-vector? [procedure]

(byte-vector? X)

Returns **#t** if X is a byte-vector object, or **#f** otherwise.

byte-vector-fill! [procedure]

(byte-vector-fill! BYTE-VECTOR N)

Sets each element of BYTE-VECTOR to N, which should be an exact integer.

byte-vector->list [procedure]

(byte-vector->list BYTE-VECTOR)

Returns a list with elements taken from BYTE-VECTOR.

byte-vector->string [procedure]

(byte-vector->string BYTE-VECTOR)

Returns a string with the contents of BYTE-VECTOR.

byte-vector-length [procedure]

(byte-vector-length BYTE-VECTOR)

Returns the number of elements in BYTE-VECTOR.

byte-vector-ref [procedure]

(byte-vector-ref BYTE-VECTOR INDEX)

Returns the byte at the INDEXth position of BYTE-VECTOR.

byte-vector-set! [procedure]

(byte-vector-set! BYTE-VECTOR INDEX N)

Sets the byte at the INDEXth position of BYTE-VECTOR to the value of the exact integer n.

executable-byte-vector->procedure [procedure]

(executable-byte-vector->procedure PBYTE-VECTOR)

Returns a procedure that on invocation will execute the code in PBYTE-VECTOR, which should have been allocated using `make-executable-byte-vector`. The procedure follows the native C calling convention, and will be called as if declared with the following prototype:

```
void <procedure>(int argc, C_word closure, C_word k, C_word arg1, ...)
```

- `argc` contains the number of arguments `arg1, ...` that are passed plus 2 (including `closure` and `k`).
- `closure` is the procedure object itself.
- `k` is a continuation closure that should be called when the code is about to return.

```
typedef void (*CONTINUATION)(int argc, C_word closure,
                             C_word result);
```

```
((CONTINUATION)k[ 1 ])(2, k, result)
```

(`k` is a data object with the second word being the actual code pointer)

An example:

```
(define x (make-executable-byte-vector 17))
```

```
(move-memory!
```

```
  '#u8(#x8b #x44 #x24 #x0c ; movl 12(%esp), %eax - 'k'
```

```
      #x8b #x5c #x24 #x10 ; movl 16(%esp), %ebx - 'arg1'
```

```

    #x53                ; pushl %ebx          - push result
    #x50                ; pushl %eax          - push k
    #x6a #x02           ; pushl $2           - push argument count
    #x8b #x40 #x04       ; movl 4(%eax), %eax - fetch code pointer
    #xff #xd0           ; call *%eax
  x)
(define y (executable-byte-vector->procedure x))
(y 123)                                     ==> 123

```

The result of calling `executable-byte-vector->procedure` with a non-executable statically allocated byte-vector is undefined.

invoke-executable-byte-vector [procedure]

(invoke-executable-byte-vector PBYTE-VECTOR ARG1 ...)

Invokes the machine code stored in the executable byte-vector `PBYTE-VECTOR`. The native C calling conventions are used, but the invoked code is passed a single argument containing a pointer to an array of the Scheme objects `ARG1 ...`.

```

(define v (make-executable-byte-vector 7))
(move-memory!
  'u8(#x8b #x44 #x24 #x04      ; movl 4(%esp), %eax
    #x8b #x00                  ; movl 0(%eax), %eax
    #xc3)                      ; ret
  v)
(invoke-executable-byte-vector v "hello!") ==> "hello!"

```

list->byte-vector [procedure]

(list->byte-vector LIST)

Returns a byte-vector with elements taken from `LIST`, where the elements of `LIST` should be exact integers.

make-byte-vector [procedure]

(make-byte-vector SIZE [INIT])

Creates a new byte-vector of size `SIZE`. If `INIT` is given, then it should be an exact integer with which every element of the byte-vector is initialized.

make-executable-byte-vector [procedure]

(make-executable-byte-vector SIZE [INIT])

As `make-static-byte-vector`, but the code is suitable for execution. **Note:** this feature is currently only available on **x86** platforms.

Exceptions: (exn bounds), (exn runtime)

make-static-byte-vector [procedure]

(make-static-byte-vector SIZE [INIT])

As `make-byte-vector`, but allocates the byte-vector in storage that is not subject to garbage collection. To free the allocated memory, one has to call `object-release` explicitly.

Exceptions: (exn bounds), (exn runtime)

static-byte-vector->pointer [procedure]
 (static-byte-vector->pointer PBYTE-VECTOR)

Returns a pointer object pointing to the data in the statically allocated byte-vector PBYTE-VECTOR.

string->byte-vector [procedure]
 (string->byte-vector STRING)

Returns a byte-vector with the contents of STRING.

5.24.5 Data in unmanaged memory

object-evict [procedure]
 (object-evict X [ALLOCATOR])

Copies the object X recursively into the memory pointed to by the foreign pointer object returned by ALLOCATOR, which should be a procedure of a single argument (the number of bytes to allocate). The freshly copied object is returned. This facility allows moving arbitrary objects into static memory, but care should be taken when mutating evicted data: setting slots in evicted vector-like objects to non-evicted data is not allowed. It **is** possible to set characters/bytes in evicted strings or byte-vectors, though. It is advisable **not** to evict ports, because they might be mutated by certain file-operations. **object-evict** is able to handle circular and shared structures, but evicted symbols are no longer unique: a fresh copy of the symbol is created, so

```
(define x 'foo)
(define y (object-evict 'foo))
y                               ==> foo
(eq? x y)                       ==> #f
(define z (object-evict '(bar bar)))
(eq? (car z) (cadr z))          ==> #t
```

The ALLOCATOR defaults to `allocate`.

object-evict-to-location [procedure]
 (object-evict-to-location X PTR [LIMIT])

As **object-evict** but moves the object at the address pointed to by the machine pointer PTR. If the number of copied bytes exceeds the optional LIMIT then an error is signalled. Two values are returned: the evicted object and a new pointer pointing to the first free address after the evicted object.

object-evicted? [procedure]
 (object-evicted? X)

Returns `#t` if X is a non-immediate evicted data object, or `#f` otherwise.

object-size [procedure]
 (object-size X)

Returns the number of bytes that would be needed to evict the data object X.

object-release [procedure]

(object-release X [RELEASER])

Frees memory occupied by the evicted object **X** recursively. **RELEASER** should be a procedure of a single argument (a foreign pointer object to the static memory to be freed) and defaults to the C-library **free()**.

object-unevict [procedure]

(object-unevict X)

Copies the object **X** and nested objects back into the normal Scheme heap. Symbols are re-interned into the symbol table. Strings and byte-vectors are **not** copied.

5.24.6 Locatives

A *locative* is an object that points to an element of a containing object, much like a “pointer” in low-level, imperative programming languages like “C”. The element can be accessed and changed indirectly, by performing access or change operations on the locative. The container object can be computed by calling the **location->object** procedure.

Locatives may be passed to foreign procedures that expect pointer arguments. The effect of creating locatives for evicted data (see **object-evict**) is undefined.

make-locative [procedure]

(make-locative EXP [INDEX])

Creates a locative that refers to the element of the non-immediate object **EXP** at position **INDEX**. **EXP** may be a vector, symbol, pair, string, byte-vector, SRFI-4 number-vector, SRFI-25 array, or record. **INDEX** should be a fixnum, or a valid index into a SRFI-25 array. **INDEX** defaults to 0.

make-weak-locative [procedure]

(make-weak-locative EXP [INDEX])

Creates a “weak” locative. Even though the locative refers to an element of a container object, the container object will still be reclaimed by garbage collection if no other references to it exist.

locative? [procedure]

(locative? X)

Returns **#t** if **X** is a locative, or **#f** otherwise.

locative-ref [procedure]

(locative-ref LOC)

Returns the element to which the locative **LOC** refers. If the containing object has been reclaimed by garbage collection, an error is signalled.

locative-set! [procedure]

(locative-set! LOC X)

Changes the element to which the locative **LOC** refers to **X**. If the containing object has been reclaimed by garbage collection, an error is signalled.

locative->object [procedure]
 (locative->object LOC)

Returns the object that contains the element referred to by `LOC` or `#f` if the container has been reclaimed by garbage collection.

5.24.7 Accessing toplevel variables

global-bound? [procedure]
 (global-bound? SYMBOL)

Returns `#t`, if the global (“toplevel”) variable with the name `SYMBOL` is bound to a value, or `#f` otherwise.

global-ref [procedure]
 (global-ref SYMBOL)

Returns the value of the global variable `SYMBOL`. If no variable under that name is bound, an error is signalled.

global-set! [procedure]
 (global-set! SYMBOL X)

Sets the global variable named `SYMBOL` to the value `X`.

5.24.8 Low-level data access

block-ref [procedure]
 (block-ref BLOCK INDEX)

Returns the contents of the `INDEX`th slot of the object `BLOCK`. `BLOCK` may be a vector, record structure, pair or symbol.

block-set! [procedure]
 (block-set! BLOCK INDEX X)

Sets the contents of the `INDEX`th slot of the object `BLOCK` to the value of `X`. `BLOCK` may be a vector, record structure, pair or symbol.

object-copy [procedure]
 (object-copy X)

Copies `X` recursively and returns the fresh copy. Objects allocated in static memory are copied back into garbage collected storage.

make-record-instance [procedure]
 (make-record-instance SYMBOL ARG1 ...)

Returns a new instance of the record type `SYMBOL`, with its slots initialized to `ARG1` To illustrate:

```
(define-record point x y)
```

expands into something quite similar to:

```
(begin
  (define (make-point x y)
    (make-record-instance 'point x y) )
  (define (point? x)
    (and (record-instance? x)
         (eq? 'point (block-ref x 0)) ) )
  (define (point-x p) (block-ref p 1))
  (define (point-x-set! p x) (block-set! p 1 x))
  (define (point-y p) (block-ref p 2))
  (define (point-y-set! p y) (block-set! p 1 y)) )
```

move-memory! [procedure]
 (move-memory! FROM TO [BYTES])

Copies BYTES bytes of memory from FROM to TO. FROM and TO may be strings, primitive byte-vectors, SRFI-4 byte-vectors (see: [Section 5.11 \[Unit srfi-4\], page 61](#)), memory mapped files, foreign pointers (as obtained from a call to `foreign-lambda`, for example) or locatives. If BYTES is not given and the size of the source or destination operand is known then the maximal number of bytes will be copied. Moving memory to the storage returned by locatives will cause havoc, if the locative refers to containers of non-immediate data, like vectors or pairs.

number-of-bytes [procedure]
 (number-of-bytes BLOCK)

Returns the number of bytes that the object BLOCK contains. BLOCK may be any non-immediate value.

number-of-slots [procedure]
 (number-of-slots BLOCK)

Returns the number of slots that the object BLOCK contains. BLOCK may be a vector, record structure, pair or symbol.

record-instance? [procedure]
 (record-instance? X)

Returns #t if X is an instance of a record type. See also: `make-record-instance`.

record->vector [procedure]
 (record->vector BLOCK)

Returns a new vector with the type and the elements of the record BLOCK.

5.24.9 Procedure-call- and variable reference hooks

invalid-procedure-call-handler [procedure]
 (invalid-procedure-call-handler PROC)

Sets an internal hook that is invoked when a call to an object other than a procedure is executed at runtime. The procedure PROC will in that case be called with two arguments: the object being called and a list of the passed arguments.

```
;;; Access sequence-elements as in ARC:

(invalid-procedure-call-handler
 (lambda (proc args)
  (cond [(string? proc) (apply string-ref proc args)]
        [(vector? proc) (apply vector-ref proc args)]
        [else (error "call of non-procedure" proc)] ) ) )

("hello" 4)    ==>  #\o
```

This facility does not work in code compiled with the “unsafe” setting.

unbound-variable-value [procedure]
 (unbound-variable-value [X])

Defines the value that is returned for unbound variables. Normally an error is signalled, use this procedure to override the check and return *X* instead. To set the default behavior (of signalling an error), call **unbound-variable-value** with no arguments.

This facility does not work in code compiled with the “unsafe” setting.

5.24.10 Magic

object-become! [procedure]
 (object-become! ALIST)

Changes the identity of the value of the car of each pair in **ALIST** to the value of the cdr. Both values may not be immediate (i.e. exact integers, characters, booleans or the empty list).

```
(define x "i used to be a string")
(define y '#(and now i am a vector))
(object-become! (list (cons x y)))
x                ==> #(and now i am a vector)
y                ==> #(and now i am a vector)
(eq? x y)        ==> #t
```

Note: this operation invokes a major garbage collection.

The effect of using **object-become!** on evicted data (see **object-evict**) is undefined.

5.25 Unit tinyclos

This unit is a port of Gregor Kiczales **TinyCLOS** with numerous modifications.

This unit uses the **extras** unit.

5.25.1 Defining forms

define-class [syntax]
 (define-class NAME (SUPERCLASS1 ...) (SLOTNAME1 ...) [METACLASS])

Sets the variable `NAME` to a new class (a new instance of the class `<class>`). `SUPERCLASS1 ...` is a list of superclasses of the newly created class. If no superclasses are given, then `<object>` is assumed. `SLOTNAME1 ...` are the names of the direct slots of the class. if `METAClass` is provided, then the new class-instance is an instance of `METAClass` instead of `<class>`.

```
(define-class NAME (SUPER) (SLOT1 SLOT2) META)
```

is equivalent to

```
(define NAME
  (make META
    'name 'NAME
    'direct-supers (list SUPER)
    'direct-slots (list 'SLOT1 'SLOT2)) )
```

Note that slots-names are not required to be symbols, so the following is perfectly valid:

```
(define hidden-slot (list 'hidden))
(define <myclass>
  (make <class>
    'direct-supers (list <object>)
    'direct-slots (list hidden-slot) ) )
(define x1 (make <myclass>))
(slot-set! x1 hidden-slot 99)
```

define-generic

[syntax]

```
(define-generic NAME [CLASS])
```

Sets the variable `NAME` to contain a fresh generic function object without associated methods. If the optional argument `CLASS` is given, then the generic function will be an instance of that class.

define-method

[syntax]

```
(define-method (NAME (VARIABLE1 CLASS1) ... PARAMETERS ...) BODY ...)■
```

Adds a new method with the code `BODY ...` to the generic function that was assigned to the variable `name`. `CLASS1 ...` is a list of classes that specialize this particular method. The method can have additional parameters `PARAMETERS`, which do not specialize the method any further. Inside the body of the method the identifier `call-next-method` names a procedure of zero arguments that can be invoked to call the next applicable method with the same arguments. If no generic function is defined under this name, then a fresh generic function object is created and assigned to `NAME`. Note that only `define-generic` expands into a valid definition, so for internal lexically scoped definitions or for definitions for module exports (see `syntax-case`) use `define-generic`.

5.25.2 Base language

add-method

[procedure]

```
(add-method GENERIC METHOD)
```

Adds the method object `METHOD` to the list of applicable methods for the generic function `GENERIC`.

instance? [procedure]

`(instance? X)`

Returns `#t` if `X` is an instance of a non-primitive class.

make [procedure]

`(make CLASS INITARG ...)`

Creates a new instance of `CLASS` and passes `INITARG ...` to the `initialize` method of this class.

make-class [procedure]

`(make-class SUPERCLASSES SLOTNAMES)`

Creates a new class object, where `SUPERCLASSES` should be the list of direct superclass objects and `SLOTNAMES` should be a list of symbols naming the slots of this class.

make-generic [procedure]

`(make-generic [NAME])`

Creates a new generic function object. If `NAME` is specified, then it should be a string.

make-method [procedure]

`(make-method SPECIALIZERS PROC)`

Creates a new method object specialized to the list of classes in `SPECIALIZERS`.

`(define-method (foo (x <bar>)) 123)`

```
<=> (add-method foo
      (make-method
        (list <bar>)
        (lambda (call-next-method x) 123)))
```

slot-ref [procedure]

`(slot-ref INSTANCE SLOTNAME)`

Returns the value of the slot `SLOTNAME` of the object `INSTANCE`.

slot-set! [procedure]

`(slot-set! INSTANCE SLOTNAME VALUE)`

Sets the value of the slot `SLOTNAME` of the object `INSTANCE` to `VALUE`.

5.25.3 Introspection

class-cpl [procedure]

`(class-cpl CLASS)`

Returns the class-precedence-list of `CLASS` as a list of classes.

class-direct-slots [procedure]

`(class-direct-slots CLASS)`

Returns the list of direct slots of `CLASS` as a list of lists, where each sublist contains the name of the slot.

class-direct-supers [procedure]

(class-direct-supers CLASS)

Returns the list of direct superclasses of CLASS.

class-of [procedure]

(class-of X)

Returns the class that the object X is an instance of.

class-name [procedure]

(class-name CLASS)

Returns name of CLASS.

class-slots [procedure]

(class-slots CLASS)

Returns the list of all slots of CLASS and its superclasses as a list of lists, where each sublist contains the name of the slot.

generic-methods [procedure]

(generic-methods GENERIC)

Returns the list of all methods associated with the generic function GENERIC.

method-specializers [procedure]

(method-specializers METHOD)

Returns the list of classes that specialize METHOD.

method-procedure [procedure]

(method-procedure METHOD)

Returns the procedure that contains the body of METHOD.

subclass? [procedure]

(subclass? CLASS1 CLASS2)

Returns #t if CLASS1 is a subclass of CLASS2, or #f otherwise. Note that the following holds:

(subclass? X X) ==> #t

5.25.4 Intercessory protocol

These definitions allow interfacing to the Meta Object Protocol of TinyCLOS. For serious use, it is recommended to consult the source code (`tinyclos.scm`).

allocate-instance [generic]

(allocate-instance CLASS)

Allocates storage for an instance of CLASS and returns the instance.

compute-apply-generic [generic]

(compute-apply-generic GENERIC)

Returns a procedure that will be called to apply the generic function methods to the arguments.

compute-apply-methods [generic]`(compute-apply-methods GENERIC)`

Returns a procedure of two arguments, a list of applicable methods and a list of arguments and applies the methods.

compute-methods [generic]`(compute-methods GENERIC)`

Returns a procedure of one argument. The procedure is called with the list of actual arguments passed to the generic function and should return a list of applicable methods, sorted by precedence.

compute-cpl [generic]`(compute-cpl CLASS)`

Computes and returns the class-precedence-list of `CLASS`.

compute-getter-and-setter [generic]`(compute-getter-and-setter CLASS SLOT ALLOCATOR)`

Returns two values, the procedures that get and set the contents of the slot `SLOT`. `ALLOCATOR` is a procedure of one argument (*I currently don't know what it does*).

compute-method-more-specific? [generic]`(compute-method-more-specific? GENERIC)`

Returns a procedure of three arguments (two methods and a list of arguments) that returns `#t` if the first method is more specific than the second one with respect to the list of arguments. Otherwise the returned predicate returns `#f`.

compute-slots [generic]`(compute-slots CLASS)`

Computes and returns the list of slots of `CLASS`.

initialize [generic]`(initialize INSTANCE INITARGS)`

Initializes the object `INSTANCE`. `INITARGS` is the list of initialization arguments that were passed to the `make` procedure.

5.25.5 Additional protocol**describe-object** [generic]`(describe-object INSTANCE PORT)`

Writes a description of `INSTANCE` to `PORT`. Execution of the interpreter command `,d` will invoke this generic function.

print-object [generic]`(print-object INSTANCE PORT)`

Writes a textual representation of `INSTANCE` to `PORT`. Any output of an instance with `display`, `write` and `print` will invoke this generic function.

5.25.6 Utility procedures

initialize-slots

[procedure]

```
(initialize-slots INSTANCE INITARGS)
```

This procedure takes a sequence of alternating slot-names and initialization values in INITARGS and initializes the corresponding slots in INSTANCE.

```
(define-class <pos> () (x y))
```

```
(define-method (initialize (pos <pos>) initargs)
  (call-next-method)
  (initialize-slots pos initargs))
```

```
(define p1 (make <pos> 'x 1 'y 2))
(define p2 (make <pos> 'x 3 'y 5))
```

5.25.7 Builtin classes

The class hierarchy of builtin classes looks like this:

```
<top>
  <object>
    <class>
      <procedure-class>
      <procedure>
      <entity-class>
      <generic>
      <primitive-class>
    <c++-object>
  <primitive>
    <void>
    <boolean>
    <symbol>
    <char>
    <vector>
    <pair>
    <number>
      <integer>
      <exact>
      <inexact>
    <string>
    <port>
      <input-port>
      <output-port>
    <pointer>
      <tagged-pointer>
    <locative>
    <byte-vector>
```



```

<u8vector>
<s8vector>
<u16vector>
<s16vector>
<u32vector>
<s32vector>
<f32vector>
<f64vector>
<structure>
  <array>
  <char-set>
  <condition>
  <environment>
  <hash-table>
  <lock>
  <mmap>
  <promise>
  <queue>
  <tcp-listener>
  <time>
<end-of-file>

```

<primitive> → <top> [class]

The parent class of the classes of all primitive Scheme objects.

<boolean> → <primitive>	[class]
<symbol> → <primitive>	[class]
<char> → <primitive>	[class]
<vector> → <primitive>	[class]
<null> → <primitive>	[class]
<pair> → <primitive>	[class]
<number> → <primitive>	[class]
<integer> → <primitive>	[class]
<exact> → <integer>	[class]
<inexact> → <number>	[class]
<string> → <primitive>	[class]
<port> → <primitive>	[class]
<environment> → <structure>	[class]
<end-of-file> → <primitive>	[class]
<input-port> → <port>	[class]
<output-port> → <port>	[class]
<procedure> → <procedure-class>	[class]

The classes of primitive Scheme objects.

<byte-vector> → <primitive> [class]

<structure> → <primitive> [class]

<hash-table> → <structure> [class]

<queue> → <structure> [class]

The classes of extended data types provided by the various library units.

<class> → <object> [class]

The parent class of all class objects.

<entity-class> → <class> [class]

The parent class of objects that can be invoked as a procedure and have slots.

<generic> → <entity-class> [class]

The parent class of generic function objects.

<method> → <class> [class]

The parent class of method objects.

<object> → <class> [class]

The parent class of all objects.

<procedure-class> → <class> [class]

The parent class of objects that can be invoked as a procedure.

<condition> → <structure> [class]

Class of condition objects.

<array> → <structure> [class]

<char-set> → <structure> [class]

<time> → <structure> [class]

<u8vector> → <byte-vector> [class]

<s8vector> → <byte-vector> [class]

<u16vector> → <byte-vector> [class]

<s16vector> → <byte-vector> [class]

<u32vector> → <byte-vector> [class]

<s32vector> → <byte-vector> [class]

<f32vector> → <byte-vector> [class]

<f64vector> → <byte-vector> [class]

The classes of data objects provided by the various supported SRFIs.

<lock> → <structure> [class]

<mmap> → <structure> [class]

Classes of objects used in the `posix` library unit.

<pointer> → <primitive> [class]

<tagged-pointer> → <pointer> [class]

A machine pointer (untagged, or tagged).

<locative> → <primitive> [class]

A locative.

<promise> → <structure> [class]

The class of objects returned by **delay**.

<tcp-listener> → <structure> [class]

The class of an object returned by **tcp-listen**.

<c++-class> → <object> [class]

The class of generated wrappers for C++ classes parsed by the “easy” Foreign Function interface.

The CHICKEN distribution provides several examples in the file **tinyclos-examples.scm**.

6 Interface to external functions and variables

6.1 Accessing external objects

foreign-code [syntax]

(foreign-code STRING)

Executes the embedded C/C++ code `STRING`, which should be a sequence of C statements, which are executed and return an unspecified result.

(foreign-code "doSomeInitStuff();") ==> #<unspecified>

foreign-value [syntax]

(foreign-value STRING TYPE)

Evaluates the embedded C/C++ expression `STRING`, returning a value of type given in the foreign-type specifier `TYPE`.

(print (foreign-value "my_version_string" c-string))

define-foreign-type [syntax]

(define-foreign-type NAME TYPE [ARGCONVERT [RETCONVERT]])

Defines an alias for `TYPE` with the name `NAME` (a symbol). `TYPE` may be a type-specifier or a string naming a C type. The namespace of foreign type specifiers is separate from the normal Scheme namespace. The optional arguments `ARGCONVERT` and `RETCONVERT` should evaluate to procedures that map argument- and result-values to a value that can be transformed to `TYPE`:

(require-extension extras)

```
(define-foreign-type char-vector
  nonnull-c-string
  (compose list->string vector->list)
  (compose list->vector string->list) )
```

```
(define strlen
  (foreign-lambda int "strlen" char-vector) )
```

```
(strlen '#(#\a #\b #\c)) ==> 3
```

```
(define memset
  (foreign-lambda char-vector "memset" char-vector char int) )
```

```
(memset '#(#_ #_ #_) #\X 3) ==> #(#\X #\X #\X)
```

Foreign type-definitions are only visible in the compilation-unit in which they are defined, so use `include` to use the same definitions in multiple files.

define-foreign-variable [syntax]

(define-foreign-variable NAME TYPE [STRING])

Defines a foreign variable of name **NAME** (a symbol). **STRING** should be the real name of a foreign variable or parameterless macro. If **STRING** is not given, then the variable name **NAME** will be converted to a string and used instead. All references and assignments (via **set!**) are modified to correctly convert values between Scheme and C representation. This foreign variable can only be accessed in the current compilation unit, but the name can be lexically shadowed. Note that **STRING** can name an arbitrary C expression. If no assignments are performed, then **STRING** doesn't even have to specify an lvalue.

```
#>
enum { abc=3, def, ghi };
<#

(define-macro (define-foreign-enum . items)
  '(begin
    ,@(map (match-lambda
            [(name realname) '(define-foreign-variable ,name int ,realname)]
            [name '(define-foreign-variable ,name int)] )
          items) ) )

(define-foreign-enum abc def ghi)

ghi                                ==> 5
```

define-foreign-record [syntax]

(define-foreign-record NAME SLOT ...)

Defines accessor procedures for a C structure definition. **NAME** should either be a symbol or a list of the form (TYPE**NAME** FOREIGN**NAME**). If **NAME** is a symbol, then a C declaration will be generated that defines a C struct named **struct NAME**. If **NAME** is a list, then no struct declaration will be generated. A foreign-type specifier named **NAME** (or TYPE**NAME**) will be defined as a pointer to the given C structure. A **SLOT** definition should be a list of one of the following forms:

(TYPE SLOT**NAME**)

or

(TYPE SLOT**NAME** SIZE)

The latter form defines an array of **SIZE** elements of the type **TYPE** embedded in the structure. For every slot, the following accessor procedures will be generated:

TYPENAME**-SLOT**NAME**** [procedure]

(TYPE**NAME**-SLOT**NAME** FOREIGN-RECORD-POINTER [INDEX])

A procedure of one argument (a pointer to a C structure), that returns the slot value of the slot **SLOTNAME**. If a **SIZE** has been given in the slot definition, then an additional argument **INDEX** is required that specifies the index of an array-element.

TYPENAME**-SLOT**NAME**-set!** [procedure]

(TYPE**NAME**-SLOT**NAME**-set! FOREIGN-RECORD-POINTER [INDEX] VALUE)

A procedure of two arguments (a pointer to a C structure) and a value, that sets the slot value of the slot `SLOTNAME` in the structure. If a `SIZE` has been given in the slot definition, then an additional argument `INDEX` is required for the array index.

If a slot type is of the form `(const ...)`, then no setter procedure will be generated. Slots of the types `(struct ...)` or `(union ...)` are accessed as pointers to the embedded struct (or union) and no setter will be generated.

foreign-callback-lambda [syntax]

```
(foreign-callback-lambda RETURNTYPE NAME ARGTYPE ...)
```

This is similar to `foreign-lambda`, but also allows the called function to call Scheme functions. See [Section 6.4 \[Callbacks\]](#), page 121.

foreign-callback-lambda* [syntax]

```
(foreign-callback-lambda* RETURNTYPE ((ARGTYPE VARIABLE)...) STRING ...)■
```

This is similar to `foreign-lambda*`, but also allows the called function to call Scheme functions. See [Section 6.4 \[Callbacks\]](#), page 121.

foreign-lambda [syntax]

```
(foreign-lambda RETURNTYPE NAME ARGTYPE ...)
```

Represents a binding to an external routine. This form can be used in the position of an ordinary `lambda` expression. `NAME` specifies the name of the external procedure and should be a string or a symbol.

foreign-lambda* [syntax]

```
(foreign-lambda* RETURNTYPE ((ARGTYPE VARIABLE) ...) STRING ...)
```

Similar to `foreign-lambda`, but instead of generating code to call an external function, the body of the C procedure is directly given in `STRING ...`:

```
(define my-strlen
  (foreign-lambda* int ((c-string str))
    "int n = 0;
    while(*(str++)) ++n;
    return(n);") )
```

```
(my-strlen "one two three")          ==> 13
```

For obscure technical reasons any use of the `return` statement should enclose the result value in parentheses. For the same reasons `return` without an argument is not allowed.

6.2 Foreign type specifiers

Here is a list of valid foreign type specifiers:

scheme-object

An arbitrary Scheme data object (immediate or non-immediate).

`bool`

As argument: any value (`#f` is false, anything else is true). As result: anything different from 0 and the NULL-pointer is `#t`.

`byte unsigned-byte`

A byte.

`char unsigned-char`

A character.

`short unsigned-short`

A short integer number.

`int unsigned-int`

An small integer number in fixnum range (at least 30 bit).

`integer unsigned-integer`

Either a fixnum or a flonum in the range of a (unsigned) machine “int”.

`long unsigned-long`

Either a fixnum or a flonum in the range of a (unsigned) machine “long”.

`float double`

A floating-point number. If an exact integer is passed as an argument, then it is automatically converted to a float.

`pointer`

An untyped pointer to the contents of a non-immediate Scheme object (not allowed as return type). The value `#f` is also allowed and is passed as a NULL pointer.

`nonnull-pointer`

As `pointer`, but guaranteed not to be `#f`.

`c-pointer`

An untyped operating-system pointer or a locative. The value `#f` is also allowed and is passed as a NULL pointer. If uses as the type of a return value, a NULL pointer will be returned as `#f`.

`nonnull-c-pointer`

As `c-pointer`, but guaranteed not to be `#f/NULL`.

`[nonnull-] byte-vector`

A byte-vector object, passed as a pointer to its contents. Arguments of type `byte-vector` may optionally be `#f`, which is passed as a NULL pointer. This is not allowed as a return type.

[nonnull-] `u8vector`
 [nonnull-] `u16vector`
 [nonnull-] `u32vector`
 [nonnull-] `s8vector`
 [nonnull-] `s16vector`
 [nonnull-] `s32vector`
 [nonnull-] `f32vector`
 [nonnull-] `f64vector`

A SRFI-4 number-vector object, passed as a pointer to its contents. Arguments of type `byte-vector` may optionally be `#f`, which is passed as a NULL pointer. These are not allowed as return types.

`c-string`

A C string (zero-terminated). The value `#f` is also allowed and is passed as a NULL pointer. If used as the type of a return value, a NULL pointer will be returned as `#f`. Note that the string is copied (with a zero-byte appended) when passed as an argument to a foreign function. Also a return value of this type is copied into garbage collected memory.

`nonnull-c-string`

As `c-string`, but guaranteed not to be `#f/NULL`.

[nonnull-] `c-string*`

Similar to [nonnull-]`c-string`, but if used as a result-type, the pointer returned by the foreign code will be freed (using the C-libraries `free()`) after copying.

`void`

Specifies an undefined return value. Not allowed as argument type.

(`const TYPE`)

The foreign type `TYPE` with an additional `const` specifier.

(`enum NAME`)

An enumeration type. Handled internally as an `integer`.

(`pointer TYPE`)

(`c-pointer TYPE`)

An operating-system pointer or a locative to an object of `TYPE`.

(`nonnull-pointer TYPE`)

(`nonnull-c-pointer TYPE`)

As (`pointer TYPE`), but guaranteed not to be `#f/NULL`.

(`ref TYPE`)

A C++ reference type. Reference types are handled the same way as pointers inside Scheme code.

(`struct NAME`)

A struct of the name `NAME`, which should be a string. Structs can not be directly passed as arguments to foreign function, neither can they be result values. Pointers to structs are allowed, though.

(template TYPE ARGTYPE ...)

A C++ template type. For example `vector<int>` would be specified as `(template "vector" int)`. Template types can not be directly passed as arguments or returned as results.

(union NAME)

A union of the name `NAME`, which should be a string. Unions can not be directly passed as arguments to foreign function, neither can they be result values. Pointers to unions are allowed, though.

(instance CNAME SCHEMECLASS)

A pointer to a C++ class instance. `CNAME` should designate the name of the C++ class, and `SCHEMECLASS` should be the class that wraps the instance pointer. Normally `SCHEMECLASS` should be a subclass of `<c++-object>`.

(function RESULTTYPE (ARGUMENTTYPE1 ... [...]) [CALLCONV])

A function pointer. `CALLCONV` specifies an optional calling convention and should be a string. The meaning of this string is entirely platform dependent. The value `#f` is also allowed and is passed as a `NULL` pointer.

Foreign types are mapped to C types in the following manner:

```
bool      int
[unsigned-]char
           [unsigned] char
[unsigned-]short
           [unsigned] short
[unsigned-]int
           [unsigned] int
[unsigned-]integer
           [unsigned] int
[unsigned-]long
           [unsigned] long
float      float
double     double
[nonnull-]pointer
           void *
[nonnull-]c-pointer
           void *
[nonnull-]byte-vector
           unsigned char *
[nonnull-]u8vector
           unsigned char *
[nonnull-]s8vector
           char *
```

```

[nonnull-]u16vector
    unsigned short *

[nonnull-]s16vector
    short *

[nonnull-]u32vector
    uint32_t *

[nonnull-]s32vector
    int32_t *

[nonnull-]f32vector
    float *

[nonnull-]f64vector
    double *

[nonnull-]c-string
    char *

void        void

([nonnull-]pointer TYPE)
    TYPE *

(enum NAME)
    enum NAME

(struct NAME)
    struct NAME

(ref TYPE)
    TYPE &

(template T1 T2 ...)
    T1<T2, ...>

(union NAME)
    union NAME

(function RTYPE (ATYPE ...) [CALLCONV])
    [CALLCONV] RTYPE (*)(ATYPE, ...)

```

6.3 Entry points

To simplify embedding compiled Scheme code into arbitrary programs, one can define so called “entry points”, which provide a uniform interface and parameter conversion facilities. To use this facility, add

```
(include "chicken-entry-points")
```

to the beginning of your code.

define-entry-point

[syntax]

```
(define-entry-point INDEX ((VAR1 TYPE1) ...)
  (RTYPE1 ...)
  EXP1 EXP2 ...)
```

Defines a new entry-point with index `INDEX` which should evaluate to an exact integer. During execution of the body `EXP1 EXP2 ...` the variables `VAR1 ...` are bound to the parameters passed from the host program to the invoked entry point. The parameters passed are converted according to the foreign type specifiers `TYPE1`. The expressions should return as many values as foreign type specifiers are given in `RTYPE1 ...`, with the exception that if the list of return types is empty, a single value is expected to be returned from the body (there is no need to add a `(values)` form at the end). The results are then transformed into values that can be used in the host program.

Note: if one or more of the result types `RTYPE ...` specify the type `c-string`, then the parameter types at the same positions in `TYPE1 ...` have to be `c-strings` as well, because the result strings are copied into the same area in memory. You should also take care that the passed buffer is long enough to hold the result string or unpredictable things will happen.

If entry points were defined then the program will not terminate after execution of the last toplevel expression, but instead it will enter a loop that waits for the host to invoke one of the defined entry points.

define-embedded

[syntax]

```
(define-embedded [QUALIFIER ... ] ([CCONV] NAME (TYPE1 VAR1) ...) RTYPE BODY ...)
```

Defines a named entry-point that can be accessed from external code with a normal C/C++ function call. `QUALIFIER` may be a string for special function declarations (like `__declspec(dllexport)` on Windows, for example) and `CCONV` may be a string designating a calling convention (like `__cdecl`). During the execution of the `BODY` the variables `VAR1 ...` are bound to the arguments passed to the function, which should be of types compatible to the type specifiers `TYPE1`. `RTYPE` specifies the result type of the entry-point. The return type specifiers `[nonnull-]c-string` and `[nonnull-]c-string*` are handled specially: if the return type is `c-string`, a heap-allocated pointer to a zero-terminated string will be returned, which will be valid until the next invocation of an entry-point into the Scheme code. If the return type is `c-string*`, a buffer allocated with `malloc` will be returned, and freeing the string is the responsibility of the caller.

All entry-point definitions with `define-embedded` should be put into the same source file. `define-embedded` expands into a `define-entry-point` form and the entry-point index is provided by the macro (starting from 1). If `define-embedded` is used in multiple source files then the index is counted from 1 in each of the files, resulting in multiple entry-points with the same index.

The following C functions and data types are provided:

void CHICKEN_parse_command_line (int argc, char *argv[], [C function]
int *heap, int *stack int *symbols)

Parse the programs command-line contained in **argc** and **argv** and return the heap-, stack- and symbol table limits given by runtime options of the form **-:...**, or choose default limits. The library procedure **argv** can access the command-line only if this function has been called by the containing application.

int CHICKEN_initialize (int heap, int stack, int symbols, [C function]
void *toplevel)

Initializes the Scheme execution context and memory. **heap** holds the number of bytes that are to be allocated for the secondary heap. **stack** holds the number of bytes for the primary heap. **symbols** contains the size of the symbol table. Passing 0 to one or more of these parameters will select a default size. **toplevel** should be a pointer to the **toplevel** entry point procedure. You should pass **C_toplevel** here. In any subsequent call to **CHICKEN_run** or **CHICKEN_invoke** you can simply pass **NULL**. Calling this function more than once has no effect. If enough memory is available and initialization was successful, then 1 is returned, otherwise this function returns 0.

void CHICKEN_run (void **data, int *bytes, int *maxlen, [C function]
void *toplevel)

Starts the Scheme program. **data**, **bytes** and **maxlen** contain invocation parameters in raw form. Pass **NULL** here. Call this function once to execute all **toplevel** expressions in your compiled Scheme program. If the runtime system was not initialized before, then **CHICKEN_initialize** is called with default sizes. **toplevel** is the **toplevel** entry-point procedure.

void CHICKEN_invoke (int index, C_parameter *params, int [C function]
count, void *toplevel)

Invoke the entry point with index **index**. **count** should contain the maximum number of arguments or results (whatever is higher). **params** is a pointer to parameter data:

typedef union

```
{
    C_word x;          /* parameter type scheme-object */
    long i;            /* parameter type bool, [unsigned] int/short/long */
    long c;            /* parameter type [unsigned] char */
    double f;          /* parameter type float/double */
    void *p;           /* any pointer parameter type and C strings */
} C_parameter;
```

This function calls **CHICKEN_run** if it was not called at least once before.

int CHICKEN_is_running () [C function]

Returns 1, if called inside a dynamic context invoked via **CHICKEN_run** or **CHICKEN_invoke** (i.e. if running inside a call from Scheme to C). If no Scheme stack frame is currently active, then this function returns 0.

Here is a simple example (assuming a UNIX-like environment):

```
% cat foo.c
#include <stdio.h>
```

```

#include "chicken.h"

int main(void)
{
    C_parameter p[ 3 ];
    char str[ 32 ] = "hello!"; /* We need some space for the result string! */

    memset(p, 0, sizeof(p));
    p[ 0 ].i = -99;
    p[ 1 ].p = str;
    p[ 2 ].f = 3.14;
    CHICKEN_invoke(1, p, 3, C_toplevel);
    printf("->\n%d\n%s\n", p[ 0 ].i, p[ 1 ].p);
    return 0;
}

% cat bar.scm
(include "chicken-entry-points")

(define-entry-point 1
  ((a integer) (b c-string) (c double))
  (int c-string)
  (print (list a b c))
  (values 123 "good bye!") )

% chicken bar.scm -quiet
% gcc foo.c bar.c -o foo 'chicken-config -cflags -libs -embedded'
% foo
(-99 "hello!" 3.14)
->
123
good bye!

```

Note the use of `-embedded`. We have to compile with additional compiler options, because the host program provides the `main` function.

Here another example that uses named entry-points defined with `define-embedded`:

```

% cat foo.c
extern int foo(int, char *);
extern unsigned int square(double);

int main() { foo(square(9), "yo!"); return 0; }

% cat bar.scm
(include "chicken-entry-points")

(define-embedded (foo (int x) (c-string y)) int
  (print x ": " y)

```

```

x)

(define-embedded (square (double x)) unsigned-int
  (* x x))

% chicken bar.scm
compiling 'bar.scm' ...
% gcc foo.c bar.c 'chicken-config -cflags -libs -embedded'
% a.out
81: yo!

```

CHICKEN also provides “boilerplate” entry points, that simplify invoking Scheme code embedded in a C or C++ application tremendously. The include file `default-entry-points.scm` will define entry-points for common usage patterns, like loading a file, evaluating an expression or calling a procedure.

void CHICKEN_eval (C_word exp, C_word *result, int *status) [C macro]
 Evaluates the Scheme object passed in `exp`, writing the result value to `result`. `status` is set to 1 if the operation succeeded, or 0 if an error occurred. Call `CHICKEN_get_error_message` to obtain a description of the error.

void CHICKEN_eval_string (char *str, C_word *result, int *status) [C macro]
 Evaluates the Scheme expression passed in the string `str`, writing the result value to `result`.

void CHICKEN_eval_to_string (C_word exp, char *result, int size, int *status) [C macro]
 Evaluates the Scheme expression passed in `exp`, writing a textual representation of the result into `result`. `size` should specify the maximal size of the result string.

void CHICKEN_eval_string_to_string (char *str, char *result, int size, int *status) [C macro]
 Evaluates the Scheme expression passed in the string `str`, writing a textual representation of the result into `result`. `size` should specify the maximal size of the result string.

void CHICKEN_apply (C_word func, C_word args, C_word *result, int *status) [C macro]
 Applies the procedure passed in `func` to the list of arguments `args`, writing the result value to `result`.

void CHICKEN_apply_to_string (C_word func, C_word args, char *result, int size, int *status) [C macro]
 Applies the procedure passed in `func` to the list of arguments `args`, writing a textual representation of the result into `result`.

void CHICKEN_read (char *str, C_word *result, int *status) [C macro]
 Reads a Scheme object from the string `str`, writing the result value to `result`.

void CHICKEN_load (char *filename, int *status) [C macro]
 Loads the Scheme file `filename` (either in source form or compiled).

void CHICKEN_get_error_message (char *result, int size) [C macro]
 Returns a textual description, in case an error occurred while invoking embedded Scheme code.

void CHICKEN_yield (int *status) [C macro]
 If threads have been spawned during earlier invocations of embedded Scheme code, then this function will run the next scheduled thread for one complete time-slice. This is useful, for example, inside an “idle” handler in a GUI application with background Scheme threads.

An example:

```
% cat x.scm
;;; x.scm

(include "chicken-default-entry-points")
(define (bar x) (gc) (* x x))

% cat y.c
/* y.c */

#include "chicken.h"
#include <assert.h>

int main() {
  char buffer[ 256 ];
  int status;
  C_word val = C_SCHEME_UNDEFINED;
  C_word *data[ 1 ];

  data[ 0 ] = &val;

  CHICKEN_read("(bar 99)", &val, &status);
  assert(status);

  C_gc_protect(data, 1);

  printf("data: %08x\n", val);

  CHICKEN_eval_string_to_string("(bar)", buffer, 255, &status);
  assert(!status);

  CHICKEN_get_error_message(buffer, 255);
  printf("ouch: %s\n", buffer);

  CHICKEN_eval_string_to_string("(bar 23)", buffer, 255, &status);
```

```

    assert(status);

    printf("-> %s\n", buffer);
    printf("data: %08x\n", val);

    CHICKEN_eval_to_string(val, buffer, 255, &status);
    assert(status);
    printf("-> %s\n", buffer);

    return 0;
}

```

```
% csc x.scm y.c -embedded
```

A simpler interface for handling GC-safe references to Scheme data are the so called “gc-roots”:

void* CHICKEN_new_gc_root () [C function]

Returns a pointer to a “GC root”, which is an object that holds a reference to a Scheme value that will always be valid, even after a garbage collection. The content of the gc root is initialized to an unspecified value.

void CHICKEN_delete_gc_root (void *root) [C function]

Deletes the gc root.

C_word CHICKEN_gc_root_ref (void *root) [C macro]

Returns the value stored in the gc root.

void CHICKEN_gc_root_set (void *root, C_word value) [C macro]

Sets the content of the GC root to a new value.

Sometimes it is handy to access global variables from C code:

void* CHICKEN_global_lookup (char *name) [C function]

Returns a GC root that holds the global variable with the name **name**. If no such variable exists, NULL is returned.

C_word CHICKEN_global_ref (void *global) [C function]

Returns the value of the global variable referenced by the GC root **global**.

void CHICKEN_global_set (void *global, C_word value) [C function]

Sets the value of the global variable referenced by the GC root **global** to **value**.

6.4 Callbacks

To enable an external C function to call back to Scheme, the form **foreign-callback-lambda** (or **foreign-callback-lambda***) has to be used. This generates special code to save and restore important state information during execution of C code. There are two ways of calling Scheme procedures from C: the first is to invoke the runtime function **C_callback** with the closure to be called and the number of arguments. The second is to

define an externally visible wrapper function around a Scheme procedure with the `define-external` or `foreign-callback-wrapper` forms.

Note: the names of all functions, variables and macros exported by the CHICKEN runtime system start with “C_”. It is advisable to use a different naming scheme for your own code to avoid name clashes. Callbacks (either defined by `define-external` or `foreign-callback-wrapper` do not capture the lexical environment.

define-external

[syntax]

```
(define-external [QUALIFIERS] (NAME (ARGUMENTTYPE1 VARIABLE1) ...) RETURNTYPE BODY)
(define-external NAME TYPE [INIT])
```

The first form defines an externally callable Scheme procedure. `NAME` should be a symbol, which, when converted to a string, represents a legal C identifier. `ARGUMENTTYPE1 ...` and `RETURNTYPE` are foreign type specifiers for the argument variables `VAR1 ...` and the result, respectively. `QUALIFIERS` is an optional qualifier for the foreign procedure definition, like `__stdcall`.

```
(define-external (foo (c-string x)) int (string-length x))
```

is equivalent to

```
(define foo
  (foreign-callback-wrapper int "foo"
    (c-string) (lambda (x) (string-length x))))
```

The second form of `define-external` can be used to define variables that are accessible from foreign code. It declares a global variable named by the symbol `NAME` that has the type `TYPE`. `INIT` can be an arbitrary expression that is used to initialize the variable. `NAME` is accessible from Scheme just like any other foreign variable defined by `define-foreign-variable`.

```
(define-external foo int 42)
((foreign-lambda* int ()
  "return(foo);"))      ==> 42
```

Note: don't be tempted to assign strings or bytevectors to external variables. Garbage collection moves those objects around, so it is very bad idea to assign pointers to heap-data. If you have to do so, then copy the data object into statically allocated memory (for example by using `object-evict`).

foreign-callback-wrapper

[syntax]

```
(foreign-callback-wrapper RETURNTYPE NAME [QUALIFIERS] (ARGUMENTTYPE1 ...) EXP)
```

Defines an externally callable wrapper around the procedure `EXP`. `EXP` **must** be a lambda expression of the form `(lambda ...)`. The wrapper will have the name `NAME` and will have a signature as specified in the return- and argument-types given in `RETURNTYPE` and `ARGUMENTTYPE1 ...`. `QUALIFIERS` is a qualifier string for the function definition (see `define-external`).

C_word C_callback (C_word closure, int argc)

[C function]

This function can be used to invoke the Scheme procedure `closure`. `argc` should contain the number of arguments that are passed to the procedure on the temporary stack. Values are put onto the temporary stack with the `C_save` macro.

6.5 Locations

It is also possible to define variables containing unboxed C data, so called *locations*. It should be noted that locations may only contain simple data, that is: everything that fits into a machine word, and double-precision floating point values.

define-location [syntax]

```
(define-location NAME TYPE [INIT])
```

Identical to `(define-external NAME TYPE [INIT])`, but the variable is not accessible from outside of the current compilation unit (it is declared **static**).

let-location [syntax]

```
(let-location ((NAME TYPE [INIT]) ...) BODY ...)
```

Defines a lexically bound location.

location [syntax]

```
(location NAME)
```

```
(location X)
```

```
NAME
```

```
define-external
```

or `let-location`. This form returns a pointer object that contains the address of the variable `NAME`. If the argument to `location` is not a location defined by `define-location`, `define-external` or `let-location`, then

```
(location X)
```

is essentially equivalent to

```
(make-locative X)
```

(See the manual chapter or `locatives` for more information about locatives.

Note that `(location X)` may be abbreviated as `#$X`.

```
(define-external foo int)
```

```
((foreign-lambda* void (((pointer int) ip)) "*ip = 123;")
```

```
(location foo))
```

```
foo
```

This facility is especially useful in situations, where a C function returns more than one result value:

```
#>
```

```
#include <math.h>
```

```
<#
```

```
(define modf
```

```
(foreign-lambda double "modf" double (pointer double)) )
```

```
(let-location ([i double])
```

```
(let ([f (modf 1.99 (location i))])
```

```
(print "i=" i ", f=" f) ) )
```

`location` returns a value of type `c-pointer`, when given the name of a callback-procedure defined with `define-external`.

==>

6.6 Other support procedures

argc+argv [procedure]
 (argc+argv)

Returns two values: an integer and a foreign-pointer object representing the **argc** and **argv** arguments passed to the current process.

6.7 The *Easy* Foreign Function Interface

The compiler contains a builtin parser for a restricted subset of C and C++ that allows the easy generation of foreign variable declarations, procedure bindings and C++ class wrappers. The parser is invoked via the declaration-specifier **foreign-parse**, which extracts binding information and generates the necessary code. An example:

```
(declare
  (foreign-declare "
#include <math.h>

#define my_pi 3.14
")
  (foreign-parse "extern double sin(double);") )
```

```
(print (sin 3.14))
```

The parser would generate code that is equivalent to

```
(declare
  (foreign-declare "
#include <math.h>

#define my_pi 3.14
")

(define-foreign-variable my_pi float "my_pi")
(define sin (foreign-lambda double "sin" double))
```

Note that the read syntax **#>[SPEC] ... <#** provides a somewhat simpler way of using the parser. The example above could alternatively be expressed as

```
#>!
#define my_pi 3.14

extern double sin(double);
<#

(print (sin 3.14))
```

Another example, here using C++. Consider the following class:

```
// file: foo.h
```

```
class Foo {
  private:
    int x_;
  public:
    Foo(int x);
    void setX(int x);
    int getX();
};
```

To generate a wrapper class that provides generic functions for the constructor and the `setX` and `getX` methods, we can use the following class definition:

```
; file: test-foo.scm
```

```
#>!
#include "Foo.h"
<#

(define x (make <Foo> 99))
(print (getX x))           ; prints ‘‘99’’
(setX x 42)
(print (getX x))           ; prints ‘‘42’’
(destroy x)
```

Provided the file `foo.o` contains the implementation of the class `Foo`, the given example could be compiled like this (assuming a UNIX like environment):

```
% csc test-foo.scm foo.o -c++
```

Here is another example, a minimal “Hello world” application for QT. We can see the three different ways of embedding C/C++ code in Scheme:

```
; compile like this:
; csc hello.scm -c++ -C -IQTDIR/include -L "-LQTDIR/lib -lqt"
```

```
; Include into generated code, but don't parse:
```

```
#>
#include <qapplication.h>
#include <qpushbutton.h>
<#
```

```
; Parse but don't embed: we only want wrappers for a few classes:
```

```
#>?
class QWidget
{
public:
  void resize(int, int);
  void show();
};
```

```
class QApplication
```

```

{
public:
    QApplication(int, char **);
    ~QApplication();
    void setMainWidget(QWidget *);
    void exec();
};

class QPushButton : public QWidget
{
public:
    QPushButton(char *, QWidget *);
    ~QPushButton();
}
<#

(define a (apply make <QApplication> (receive (argc+argv))))
(define hello (make <QPushButton> "hello world!" #f))
(resize hello 100 30)
(setMainWidget a hello)
(show hello)
(exec a)
(destroy hello)
(destroy a)

```

6.7.1 #> ... <# Syntax

Occurrences of the special read syntax #>[SPEC ...] ...<# will be handled according to SPEC:

If SPEC is the ? character, the text following up to the next <# will be processed as a (declare (foreign-parse "...")) declaration (the code will be processed by the FFI parser described in this section).

If SPEC is the ! character, the text will be embedded as

```

(declare
  (foreign-declare "...")
  (foreign-parse "...") )

```

It will be both included verbatim in the declaration section of the generated C/C++ file and processed by the FFI parser.

If SPEC is the : character the text will be embedded as a (foreign-code "...") form, so it will be executed at the location where it appears.

If SPEC is a list of the form (TAG ...), then each TAG (which should be a symbol) specifies what should be done with the text:

```

declare    (declare (foreign-declare "..."))
parse      (declare (foreign-parse "..."))

```

execute (foreign-code "...")

If any other character follows the **#>**, then the complete text will be included verbatim in the declaration part of the generated file (as in a **foreign-declare** declaration).

6.7.2 General operation

The parser will generally perform the following functions

- 1) Translate macro, enum-definitions and constants into **define-foreign-variable** or **define-constant** forms
- 2) Translate function prototypes into **foreign-lambda** forms
- 3) Translate variable declarations into accessor procedures
- 4) Handle basic preprocessor operations
- 5) Translate simple C++ class definitions into TinyCLOS wrapper classes and methods

Basic token-substitution of macros defined via **#define** is performed. The preprocessor commands **#ifdef**, **#ifndef**, **#else**, **#endif**, **#undef** and **#error** are handled. The preprocessor commands **#if** and **#elif** are not supported and will signal an error when encountered by the parser, because C expressions (even if constant) are not parsed. The preprocessor command **#pragma** is allowed but will be ignored.

During processing of **foreign-parse** declarations the macro **CHICKEN** is defined (similar to the C compiler option **-DCHICKEN**).

Macro- and type-definitions are available in subsequent **foreign-parse** forms. C variables declared generate a procedure with zero or one argument with the same name as the variable. When called with no arguments, the procedure returns the current value of the variable. When called with an argument, then the variable is set to the value of that argument. Structs are not supported. C and C++ style comments are supported. Variables declared as **const** will generate normal Scheme variables, bound to the initial value of the variable.

Function-, member-function and constructor/destructor definitions may be preceded by the **__callback** qualifier, which marks the function as performing a callback into Scheme. If a wrapped function calls back into Scheme code, and **__callback** has not been given very strange and hard to debug problems will occur. Member functions prefixed with **__discard** and a result type that maps to a Scheme string (**c-string**), will have their result type changed to **c-string*** instead.

Constants (as declared by **#define** or **enum**) are not visible outside of the current Compilation units unless the **export_constants** pseudo declaration has been used.

When given the option **-ffi**, CHICKEN will compile a C/C++ file in “Scheme” mode, that is, it wraps the C/C++ source inside **#>! ... <#** and compiles it while generating Scheme bindings for exported definitions.

Keep in mind that this is not a fully general C/C++ parser. Taking an arbitrary headerfile and feeding it to CHICKEN will in most cases not work or generate ridiculous amounts of code. This FFI facility is for carefully written headerfiles, and for declarations directly embedded into Scheme code.

6.7.3 Pseudo declarations

Using the `__declare(DECL, VALUE)` form, pseudo declarations can be embedded into processed C/C++ code to provide additional control over the wrapper generation. Pseudo declarations will be ignored when processed by the system's C/C++ compiler.

- `abstract` [values: <string>] Marks the C++ class given in <string> as being abstract, i.e. no constructor will be defined. Alternatively, a class definition may be prefixed with `__abstract`.
- `class_finalizers` [values: yes, no] Automatically generates calls to `set-finalizer!` so that any unused references to instances of subsequently defined C++ class wrappers will be destroyed. This should be used with care: if the embedded C++ object which is represented by the reclaimed TinyCLOS instance is still in use in foreign code, then unpredictable things will happen.
- `destructor_name` [values: <string>] Specifies an alternative name for destructor methods (the default is `destroy`).
- `export_constants` [values: yes, no] Define a global variable for constant-declarations (as with `#define` or `enum`), making the constant available outside the current compilation unit. Use the values `yes/1` for switching constant export on, or `no/0` for switching it off.
- `exception_handler` [values: <string>] Defines C++ code to be executed when an exception is triggered inside a C++ class member function. The code should be one or more `catch` forms that perform any actions that should be taken in case an exception is thrown by the wrapped member function:

```
#>!
__declare(exception_handler, "catch(...) { return 0; }")

class Foo {
public:
    Foo *bar(bool f) { if(f) throw 123; else return this; }
};
<#
```

```
(define f1 (make <Foo>))
(print (bar f1 #f))
(print (bar f1 #t))
```

will print <Foo> and #f, respectively.

- `full_specialization` [values: yes, no] Enables “full specialization” mode. In this mode all wrappers for functions, member functions and static member functions are created as fully specialized TinyCLOS methods. This can be used to handle overloaded C++ functions properly. Only a certain set of foreign argument types can be mapped to TinyCLOS classes, as listed in the following table:

<code>char</code>	<code><char></code>
<code>bool</code>	<code><bool></code>
<code>c-string</code>	<code><string></code>

```
unsigned-char      <exact>
byte               <exact>
unsigned-byte      <exact>
[unsigned-]int     <exact>
[unsigned-]short   <exact>
[unsigned-]long    <integer>
[unsigned-]integer <integer>
float              <inexact>
double             <inexact>
(enum _)char       <exact>
(const T)char      (as T)
(function ...)      <pointer>
c-pointer          <pointer>
(pointer _)        <pointer>
(c-pointer _)      <pointer>
u8vector           <u8vector>
s8vector           <s8vector>
u16vector          <u16vector>
s16vector          <s16vector>
u32vector          <u32vector>
s32vector          <s32vector>
```



```
f32vector
    <f32vector>

f64vector
    <f64vector>
```

All other foreign types are specialized as `<top>`.

Full specialization can be enabled globally, or only for sections of code by enclosing it in

```
__declare(full_specialization, yes)
...
int foo(int x);
int foo(char *x);
...
__declare(full_specialization, no)
```

Alternatively, member function definitions may be prefixed by `__specialize` for specializing only specific members.

- `prefix` [values: `<string>`, `no`, `0`]

Sets a prefix that should be added to all generated Scheme identifiers. For example

```
__declare(prefix, "mylib:")
#define SOME_CONST 42
```

would generate the following code:

```
(define-constant mylib:SOME_CONST 42)
```

To switch prefixing off, use the values `no` or `0`.

- `rename` [value: `<string>`]

Defines to what a certain C/C++ name should be renamed. The value for this declaration should have the form "`<c-name>;<scheme-name>`", where `<c-name>` specifies the C/C++ identifier occurring in the parsed text and `<scheme-name>` gives the name used in generated wrapper code.

- `scheme` [value: `<string>`]

Embeds the Scheme expression `<string>` in the generated Scheme code.

- `substitute` [value: `<string>`]

Declares a name-substitution for all generated Scheme identifiers. The value for this declaration should be a string containing a regular expression and a replacement string (separated by the `;` character):

```
__declare(substitute, "^SDL_;sdl:")
```

```
extern void SDL_Quit();
```

generates

```
(define sdl:Quit
  (foreign-lambda integer "SDL_Quit") )
```

- `transform` [values: `<string>`]

Defines an arbitrary transformation procedure for names that match a given regular expression. The value should be a string containing a regular expression and a Scheme

expression that evaluates to a procedure of one argument. If the regex matches, the procedure will be called at compile time with the match-result (as returned by `string-match`) and should return a string with the desired transformations applied:

```
(require-for-syntax 'srfi-13)
```

```
#>!
```

```
__declare(transform, "([A-Z]+)(.*)";(lambda (x) (string-append (cadr x) \"-\\" (string-d
```

```
void F00_Bar(int x) { return x * 2; }
```

```
<#
```

```
(print (F00-bar 33))
```

- type [value: <string>]

Declares a foreign type transformation, similar to `define-foreign-type`. The value should be a list of two to four items, separated by the `;` character: a C typename, a Scheme foreign type specifier and optional argument- and result-value conversion procedures.

```
;;; foreign type that converts to unicode (assumes 4-byte wchar_t):
```

```
;
```

```
; - Note: this is rather kludgy is only meant to demonstrate the 'type'
```

```
; pseudo-declaration
```

```
(require-extension srfi-4)
```

```
(define mbstowcs (foreign-lambda int "mbstowcs" nonnull-u32vector c-string int))■
```

```
(define (str->ustr str)
```

```
  (let* ([len (string-length str)]
```

```
         [us (make-u32vector (add1 len) 0)] )
```

```
    (mbstowcs us str len)
```

```
    us) )
```

```
#>!
```

```
__declare(type, "unicode;nonnull-u32vector;str->ustr")
```

```
static void foo(unicode ws)
```

```
{
```

```
  printf("\n%s\n", ws);
```

```
}
```

```
<#
```

```
(foo "this is a test!")
```

6.7.4 Grammar

The parser understand the following grammar:

```
PROGRAM = PPCOMMAND
        | DECLARATION ";"
```

```
PPCOMMAND = "#define" ID [TOKEN ...]
           | "#ifdef" ID
           | "#ifndef" ID
           | "#else"
           | "#endif"
           | "#undef" ID
           | "#error" TOKEN ...
           | "#include" INCLUDEFILE
           | "#pragma" TOKEN ...
```

```
DECLARATION = FUNCTION
            | VARIABLE
            | ENUM
            | TYPEDEF
            | CLASS
            | CONSTANT
            | "struct" ID
            | "__declare" "(" PSEUDODECL "," <tokens> ")"
```

```
INCLUDEFILE = "\" ... "\"
            | "< ... >"
```

```
FUNCTION = {"__callback" | "__specialize" | "__discard"} [STORAGE] TYPE ID "(" TYPE [ID] ",
            | {"__callback" | "__specialize" | "__discard"} [STORAGE] TYPE ID "(" "void" ")" [
```

```
VARIABLE = [STORAGE] TYPE ID ["=" INITDATA]
```

```
STORAGE = "extern" | "static" | "volatile" | "inline"
```

```
CONSTANT = "const" TYPE ID "=" INITDATA
```

```
PSEUDODECL = "export_constants"
            | "prefix"
            | "substitute"
            | "abstract"
            | "type"
            | "scheme"
            | "rename"
            | "transform"
            | "full_specialization"
            | "destructor_name"
            | "class_finalizers"
            | "exception_handler"
```

```

ENUM = "enum" "{" ID ["=" NUMBER] "," ... "}"

TYPEDEF = "typedef" TYPE ["*" ...] ID

TYPE = ["const"] BASICTYPE ["*" ... | "&" | "<" TYPE "," ... ">" | "(" "*" [ID] ")" "(" TY

BASICTYPE = ["unsigned" | "signed"] "int"
           | ["unsigned" | "signed"] "char"
           | ["unsigned" | "signed"] "short"
           | ["unsigned" | "signed"] "long"
           | ["unsigned" | "signed"] "__byte"
           | "float"
           | "double"
           | "void"
           | "bool"
           | "__bool"
           | "__scheme_value"
           | "__fixnum"
           | "struct" ID
           | "union" ID
           | "enum" ID
           | ID

CLASS = ["__abstract"] "class" ID [":" [QUALIFIER] ID "," ...] "{" MEMBER ... "}"■

MEMBER = [QUALIFIER ":"] ["virtual"] (MEMBERVARIABLE | CONSTRUCTOR | DESTRUCTOR | MEMBERFUN

MEMBERVARIABLE = TYPE ID ["=" INITDATA]

MEMBERFUNCTION = {"__callback" | "static" | "__specialize" | "__discard"} TYPE ID "(" TYPE
                 | {"__callback" | "static" | "__specialize" | "__discard"} TYPE ID "(" "void

CONSTRUCTOR = ["__callback"] ["explicit"] ID "(" TYPE [ID] "," ... ")" [BASECONSTRUCTORS] [

DESTRUCTOR = ["__callback"] "~" ID "(" ["void"] ")" [CODE]

QUALIFIER = ("public" | "private" | "protected")

NUMBER = <a C integer or floating-point number, in decimal, octal or hexadecimal notation>■

INITDATA = <everything up to end of chunk>

BASECONSTRUCTORS = <everything up to end of chunk>

CODE = <everything up to end of chunk>

```

The following table shows how argument-types are translated:

```

[unsigned] char
    char
[unsigned] short
    [unsigned-]short
[unsigned] int
    [unsigned-]integer
[unsigned] long
    [unsigned-]long
float    float
double   double
bool     int
__bool   int
__fixnum int
__scheme_value
    scheme-object
char *    c-string
signed char *
    s8vector
[signed] short *
    s16vector
[signed] int *
    s32vector
[signed] long *
    s32vector
unsigned char *
    u8vector
unsigned short *
    u16vector
unsigned int *
    u32vector
unsigned long *
    u32vector
float *    f32vector
double *   f64vector
CLASS *    (instance CLASS <CLASS>)
TYPE *     (pointer TYPE)
TYPE       &(ref TYPE)

```

```

TYPE<T1, ...>
    (template TYPE T1 ...)
TYPE1 (*) (TYPE2, ...)
    (function TYPE1 (TYPE2 ...))

```

The following table shows how result-types are translated:

<code>void</code>	<code>void</code>
<code>[unsigned] char</code>	<code>char</code>
<code>[unsigned] short</code>	<code>[unsigned-]short</code>
<code>[unsigned] int</code>	<code>[unsigned-]integer</code>
<code>[unsigned] long</code>	<code>[unsigned-]long</code>
<code>float</code>	<code>float</code>
<code>double</code>	<code>double</code>
<code>bool</code>	<code>bool</code>
<code>__bool</code>	<code>bool</code>
<code>__fixnum</code>	<code>int</code>
<code>__scheme_value</code>	<code>scheme-object</code>
<code>char *</code>	<code>c-string</code>
<code>CLASS *</code>	<code>(instance CLASS <CLASS>)</code>
<code>TYPE *</code>	<code>(pointer TYPE)</code>
<code>TYPE</code>	<code>&(ref TYPE)</code>
<code>TYPE<T1, ...></code>	<code>(template TYPE T1 ...)</code>
<code>TYPE1 (*) (TYPE2, ...)</code>	<code>(function TYPE1 (TYPE2 ...))</code>

6.7.5 C notes

Foreign variable definitions for macros are not exported from the current compilation unit, but definitions for C variables and functions are.

`foreign-parse` does not embed the text into the generated C file, use `foreign-declare` for that (or even better, use the `#>! ... <#` syntax which does both).

Functions with variable number of arguments are not supported.

6.7.6 C++ notes

Each C++ class defines a TinyCLOS class, which is a subclass of `<c++-object>`. Instances of this class contain a single slot named `this`, which holds a pointer to a heap-allocated C++ instance. The name of the TinyCLOS class is obtained by putting the C++ classname between angled brackets (`<...>`). TinyCLOS classes are not seen by C++ code.

The C++ constructor is invoked by the `initialize` generic, which accepts as many arguments as the constructor. If no constructor is defined, a default-constructor will be provided taking no arguments. To allow creating class instances from pointers created in foreign code, the `initialize` generic will optionally accept an arguments list of the form `'this POINTER`, where `POINTER` is a foreign pointer object. This will create a TinyCLOS instance for the given C++ object.

To release the storage allocated for a C++ instance invoke the `destroy` generic (the name can be changed by using the `destructor_name` pseudo declaration).

Static member functions are wrapped in a Scheme procedure named `<class>::<member>`.

Member variables and non-public member functions are ignored.

Virtual member functions are not seen by C++ code. Overriding a virtual member function with a TinyCLOS method will not work when the member function is called by C++.

Operator functions and default arguments are not supported.

Exceptions must be explicitly handled by user code and may not be thrown beyond an invocation of C++ by Scheme code.

6.8 C interface

The following functions and macros are available for C code that invokes Scheme:

`void C_save (C_word x)` [C function]
 Saves the Scheme data object `x` on the temporary stack.

<code>C_word C_fix (int integer)</code>	[C macro]
<code>C_word C_make_character (int char_code)</code>	[C macro]
<code>C_word C_SCHEME_END_OF_LIST</code>	[C macro]
<code>C_word C_SCHEME_END_OF_FILE</code>	[C macro]
<code>C_word C_SCHEME_FALSE</code>	[C macro]
<code>C_word C_SCHEME_TRUE</code>	[C macro]

These macros return immediate Scheme data objects.

<code>C_word C_string (C_word **ptr, int length, char *string)</code>	[C function]
<code>C_word C_string2 (C_word **ptr, char *zero_terminated_string)</code>	[C function]
<code>C_word C_intern2 (C_word **ptr, char *zero_terminated_string)</code>	[C function]
<code>C_word C_intern3 (C_word **ptr, char *zero_terminated_string, C_word initial_value)</code>	[C function]
<code>C_word C_pair (C_word **ptr, C_word car, C_word cdr)</code>	[C function]
<code>C_word C_flonum (C_word **ptr, double number)</code>	[C function]
<code>C_word C_int_to_num (C_word **ptr, int integer)</code>	[C function]
<code>C_word C_mpointer (C_word **ptr, void *pointer)</code>	[C function]
<code>C_word C_vector (C_word **ptr, int length, ...)</code>	[C function]
<code>C_word C_list (C_word **ptr, int length, ...)</code>	[C function]

These functions allocate memory from `ptr` and initialize a fresh data object. The new data object is returned. `ptr` should be the **address** of an allocation pointer created with `C_alloc`.

<code>C_word* C_alloc (int words)</code>	[C macro]
------------------------------------------	-----------

Allocates memory from the C stack (`C_alloc`) and returns a pointer to it. `words` should be the number of words needed for all data objects that are to be created in this function. Note that stack-allocated data objects have to be passed to Scheme callback functions, or they will not be seen by the garbage collector. This is really only usable for callback procedure invocations, make sure not to use it in normal code, because the allocated memory will be re-used after the foreign procedure returns. When invoking Scheme callback procedures a minor garbage collection is performed, so data allocated with `C_alloc` will already have moved to a safe place.

<code>int C_SIZEOF_LIST (int length)</code>	[C macro]
<code>int C_SIZEOF_STRING (int length)</code>	[C macro]
<code>int C_SIZEOF_VECTOR (int length)</code>	[C macro]
<code>int C_SIZEOF_INTERNED_SYMBOL (int length)</code>	[C macro]
<code>int C_SIZEOF_PAIR</code>	[C macro]
<code>int C_SIZEOF_FLONUM</code>	[C macro]
<code>int C_SIZEOF_POINTER</code>	[C macro]
<code>int C_SIZEOF_LOCATIVE</code>	[C macro]
<code>int C_SIZEOF_TAGGED_POINTER</code>	[C macro]

These are macros that return the size in words needed for a data object of a given type.

<code>int C_character_code (C_word character)</code>	[C macro]
<code>int C_unfix (C_word fixnum)</code>	[C macro]
<code>double C_flonum_magnitude (C_word flonum)</code>	[C macro]
<code>char* C_c_string (C_word string)</code>	[C function]
<code>int C_num_to_int (C_word fixnum_or_flonum)</code>	[C function]
<code>void* C_pointer_address (C_word pointer)</code>	[C function]

These macros and functions can be used to convert Scheme data objects back to C data.

int C_header_size (C_word x) [C macro]
int C_header_bits (C_word x) [C macro]

Return the number of elements and the type-bits of the non-immediate Scheme data object `x`.

C_word C_block_item (C_word x, int index) [C macro]

This macro can be used to access slots of the non-immediate Scheme data object `x`. `index` specifies the index of the slot to be fetched, starting at 0. Pairs have 2 slots, one for the `car` and one for the `cdr`. Vectors have one slot for each element.

void* C_data_pointer (C_word x) [C macro]

Returns a pointer to the data-section of a non-immediate Scheme object.

C_word C_make_header (C_word bits, C_word size) [C macro]

A macro to build a Scheme object header from its bits and size parts.

C_word C_mutate (C_word *slot, C_word val) [C function]

Assign the Scheme value `val` to the location specified by `slot`. If the value points to data inside the nursery (the first heap-generation), then the garbage collector will remember to handle the data appropriately. Assigning nursery-pointers directly will otherwise result in lost data.

C_word C_symbol_value (C_word symbol) [C macro]

Returns the global value of the variable with the name `symbol`.

void C_gc_protect (C_word *ptrs[], int n) [C function]

Registers `n` variables at address `ptrs` to be garbage collection roots. The locations should not contain pointers to data allocated in the nursery, only immediate values or pointers to heap-data are valid. Any assignment of potential nursery data into a root-array should be done via `C_mutate()`. The variables have to be initialized to sensible values before the next garbage collection starts (when in doubt, set all locations in `ptrs` to `C_SCHEME_UNDEFINED`) `C_gc_protect` may not be called before the runtime system has been initialized (either by `CHICKEN_initialize`, `CHICKEN_run` or `CHICKEN_invoke`).

void C_gc_unprotect (int n) [C function]

Removes the last `n` registered variables from the set of root variables.

An example:

```
% cat foo.scm
```

```
#>
```

```
extern int callout(int, int, int);
```

```
<#
```

```
(define callout (foreign-callback-lambda int "callout" int int int))
```

```
(define-external (callin (scheme-object xyz)) int
```

```
  (print "This is 'callin': " xyz)
```

```
  123)
```

```
(print (callout 1 2 3))

% cat bar.c
#include <stdio.h>
#include "chicken.h"

extern int callout(int, int, int);
extern int callin(C_word x);

int callout(int x, int y, int z)
{
    C_word *ptr = C_alloc(C_SIZEOF_LIST(3));
    C_word lst;

    printf("This is 'callout': %d, %d, %d\n", x, y, z);
    lst = C_list(&ptr, 3, C_fix(x), C_fix(y), C_fix(z));
    return callin(lst); /* Note: 'callin' will have GC'd the data in 'ptr' */
}

% chicken foo.scm -quiet
% gcc foo.c bar.c -o foo 'chicken-config -cflags -libs'
% foo
This is 'callout': 1, 2, 3
This is 'callin': (1 2 3)
123
```

Notes:

- Scheme procedures can call C functions, and C functions can call Scheme procedures, but for every pending C stack frame, the available size of the first heap generation (the “nursery”) will be decreased, because the C stack is identical to the nursery. On systems with a small nursery this might result in thrashing, since the C code between the invocation of C from Scheme and the actual calling back to Scheme might build up several stack-frames or allocates large amounts of stack data. To prevent this it is advisable to increase the default nursery size, either when compiling the file (using the `-nursery` option) or when running the executable (using the `-:s` runtime option).
- Calls to Scheme/C may be nested arbitrarily, and Scheme continuations can be invoked as usual, but keep in mind that C stack frames will not be recovered, when a Scheme procedure call from C does not return normally.
- When multiple threads are running concurrently, and control switches from one thread to another, then the continuation of the current thread is captured and saved. Any pending C stack frame still active from a callback will remain on the stack until the threads is re-activated again. This means that in a multithreading situation, when C callbacks are involved, the available nursery space can be smaller than expected. So doing many nested Scheme->C->Scheme calls can reduce the available memory up to the point of thrashing. It is advisable to have only a single thread with pending C stack-frames at any given time.

- Pointers to Scheme data objects should not be stored in local or global variables while calling back to Scheme. Any Scheme object not passed back to Scheme will be reclaimed or moved by the garbage collector.
- Calls from C to Scheme are never tail-recursive.
- Continuations captured via `call-with-current-continuation` and passed to C code can be invoked like any other Scheme procedure.

7 chicken-setup

7.1 Extension libraries

Extension libraries are extensions to the core functionality provided by the basic CHICKEN system, to be built and installed separately. The mechanism for loading compiled extensions is based on dynamically loadable code and as such is only available on systems on which loading compiled code at runtime is supported. Currently this are most UNIX-compatible platforms that provide the `libdl` functionality like Linux, Solaris, BSD or Mac OS X. Windows with Cygwin is supported as well.

Note: Extension may also be normal applications or shell scripts.

7.2 Installing extensions

To install an extension library, run the `chicken-setup` program with the extension name as argument. If the extension consists of a single Scheme file, then it is compiled and installed in the extension *repository*. If it is an archive containing addition files, then the files are extracted and the contained *setup* script is executed. This setup script is a normal Scheme source file, which will be interpreted by `chicken-setup`. The complete language supported by `csi` is available, and the library units `srfi-1` `regex` `utils` `posix` `tcp` are loaded. Additional libraries can of course be loaded at run-time.

The setup script should perform all necessary steps to build the new library (or application). After a successful build, the extension can be installed by invoking one of the procedures `install-extension`, `install-program` or `install-script`. These procedures will copy a number of given files into the extension repository or in the path where the CHICKEN executables are located (in the case of executable programs or scripts). Additionally the list of installed files, and user-defined metadata is stored in the repository.

7.3 Creating extensions

Extensions can be created by creating an archive named `EXTENSION.egg` containing all needed files plus a `.setup` script in the root directory. After `chicken-setup` has extracted the files, the setup script will be invoked. There are no additional constraints on the structure of the archive, but the setup script has to be in the root path of the archive.

7.4 Procedures and macros available in setup scripts

`install-extension`

[procedure]

```
(install-extension ID FILELIST [INFOLIST])
```

Installs extension library with the name `ID`. All files given in the list of strings `FILELIST` will be copied to the extension repository. The optional argument `INFOLIST` should be an association list that maps symbols to values, this list will be stored as `ID.setup` at the same location as the extension code. Currently the following properties are used:

syntax [property]
 (syntax)

Marks the extension as syntax-only. No code is compiled, the extension is intended as a file containing macros to be loaded at compile/macro-expansion time.

require-at-runtime [property]
 (require-at-runtime ID ...)

Specifies extensions that should be loaded (via **require**) at runtime. This is mostly useful for syntax extensions that need additional support code at runtime.

version [property]
 (version STRING)

Specifies version string.

All other properties are currently ignored. The **FILELIST** argument may also be a single string.

install-program [procedure]
 (install-program ID FILELIST [INFOLIST])

Similar to **install-extension**, but installs an executable program in the executable path (usually `/usr/local/bin`).

install-script [procedure]
 (install-program ID FILELIST [INFOLIST])

Similar to **install-program**, but additionally changes the file permissions of all files in **FILELIST** to executable (for installing shell-scripts).

run [syntax]
 (run FORM ...)

Runs the shell command **FORM**, which is wrapped in an implicit **quasiquote**.

make [syntax]
 (make ((TARGET (DEPENDENT ...) COMMAND ...) ...) ARGUMENTS)

A “make” macro that executes the expressions **COMMAND ...**, when any of the dependents **DEPENDENT ...** have changed, to build **TARGET**. This is the same as the **make** extension, which is available separately. For more information, see **make**.

patch [procedure]
 (patch WHICH REGEX SUBST)

Replaces all occurrences of the regular expression **REGEX** with the string **SUBST**, in the file given in **WHICH**. If **WHICH** is a string, the file will be patched and overwritten. If **WHICH** is a list of the form **OLD NEW**, then a different file named **NEW** will be generated.

7.5 Examples for extensions

The simplest case is a single file that does not export any syntax. For example

```
;;;; hello.scm

(define (hello name)
  (print "Hello, " name " !") )
```

After entering

```
$ chicken-setup hello
```

at the shell prompt, the file `hello.scm` will be compiled into a dynamically loadable library, with the default compiler options `-optimize-level 2 -debug-level 0 -shared`. If the compilation succeeds, `hello.so` will be stored in the repository, together with a file named `hello.setup` (not to be confused with a setup script - this `.setup` file just contains an a-list with metadata).

Use it like any other CHICKEN extension:

```
$ csi -quiet
#;> (require-extension hello)
; loading /usr/local/lib/chicken/hello.so ...
#;> (hello "me")
Hello, me!
#;>
```

For more elaborate build operations, when installing applications or scripts, or when additional metadata should be stored for an extension, a `setup` script is required and the script and all additional files should be packaged in a gzipped `tar` archive.

Here we create a simple application:

```
;;;; hello2.scm

(require-extension extras) ; needed for 'printf'

(print "Hello, ")
(for-each (lambda (x) (printf "~A " x)) (command-line-arguments))
(print "!" )
```

We also need a setup script:

```
;;;; hello2.setup

(run (csc hello2.scm)) ; compile 'hello2'
(install-program 'hello2 "hello2") ; name of the extension and files to be installed
```

To use it, just run `chicken-setup` in the same directory:

```
$ chicken-setup hello2
```

Now the program `hello2` will be installed in the same location as the other CHICKEN tools (like `chicken`, `csi`, etc.), which will normally be `/usr/local/bin`. Note that you need write-permissions for those locations.

Uninstallation is just as easy:

```
$ chicken-setup -uninstall hello2
```

`chicken-setup` provides a `make` tool, so building operations can be of arbitrary complexity. When running `chicken-setup` with an argument `NAME`, for which no associated file `NAME.setup`, `NAME.egg` or `NAME.scm` exists will ask you to download the extension via HTTP from the default URL <http://www.call-with-current-continuation.org/eggs>. You can use the `-host` option to specify an alternative source location.

Finally a somewhat more complex example: We want to package a syntax extension with additional support code that is to be loaded at run-time of any Scheme code that uses that extension. We create a “glass” lambda, a procedure with free variables that can be manipulated from outside:

```
;;;; glass.scm

(define-macro (glass-lambda llist vars . body)
  ;; Low-level macros are fun!
  (let ([lvar (gensym)]
        [svar (gensym)]
        [x (gensym)]
        [y (gensym)]
        [yn (gensym)] )
    '(let ,(map (lambda (v) (list v #f)) vars)
      (define (,svar ,x . ,y)
        (let* ([,yn (pair? ,y)]
               [,y (and ,yn (car ,y))]) )
        (case ,x
          ,@(map (lambda (v)
                    '([,v] (if ,yn
                                (set! ,v ,y)
                                ,v) ) )
                 vars)
          (else (error "variable not found" ,x)) ) ) )
      (define ,lvar (lambda ,llist ,@body))
      (extend-procedure ,lvar ,svar) ) ) )
```

Here some support code that needs to be loaded at runtime:

```
;;;; glass-support.scm

(require-extension lolevel)

(define glass-lambda-accessor procedure-data)
(define (glass-lambda-ref gl v) ((procedure-data gl) v))
(define (glass-lambda-set! gl v x) ((procedure-data gl) v x))
```

The setup script looks like this:

```
(run (csc -s -O2 -d0 glass-support.scm))

(install-extension
  'glass
```

```
'("glass.scm" "glass-support.so")
'((syntax) (require-at-runtime glass-support))) )
```

The invocation of `install-extension` provides the files that are to be copied into the extension repository, and a metadata list that specifies that the extension `glass` is a syntax extension and that, if it is declared to be used by other code (either with the `require-extension` or `require-for-syntax` form), then client code should perform an implicit `(require 'glass-support)` at startup.

This can be conveniently packaged as an “egg”:

```
$ tar cfz glass.egg glass.setup glass.scm glass-support.scm
```

And now we use it:

```
$ csi -quiet
#;> (require-extension glass)
; loading /usr/local/lib/chicken/glass.scm ...
; loading /usr/local/lib/chicken/glass-support.so ...
#;> (define foo (glass-lambda (x) (y) (+ x y)))
#;> (glass-lambda-set! foo 'y 99)
#;> (foo 33)
132
```

7.6 chicken-setup reference

Available options:

- `-help` Show usage information and exit.
- `-version` Display version and exit.
- `-repository [PATHNAME]` When used without an argument, the path of the extension repository is displayed on standard output. When given an argument, the repository pathname (and the `repository-path` parameter) will be set to `PATHNAME` for all subsequent operations. The default repository path is the installation library directory (usually `/usr/local/lib/chicken`), or (if set) the directory given in the environment variable `CHICKEN_REPOSITORY`.
- `-program-path [PATHNAME]` When used without an argument, the path for executables is displayed on standard output. When given an argument, the program path for installing executables and scripts will be set to `PATHNAME` for all subsequent operations.
- `-host HOSTNAME[:PORT]` Specifies alternative host for downloading extensions, optionally with a TCP port number (which defaults to 80).
- `-uninstall EXTENSION` Removes all files that were installed for `EXTENSION` from the file-system, together with any metadata that has been stored.
- `-list` List all installed extensions and exit.
- `-run FILENAME` Load and execute given file.
- `-script FILENAME` Executes the given Scheme source file with all remaining arguments and exit. The “she-bang” shell script header is recognized, so you can write Scheme scripts that use `chicken-setup` just as with `csi`.
- `-verbose` Display additional debug information.

- **-keep** Keep temporary files and directories.

Note that the options are processed exactly in the order in which they appear in the command-line.

8 Additional files

In addition to library units the following files are provided. Use them by including the file in your code with the `include` special form.

8.1 `srfi-13-syntax.scm`

This file provides the `let-string-start+end` syntax defined in SRFI-13. See [Section 5.12 \[Unit `srfi-13`\], page 62](#).

8.2 `chicken-highlevel-macros.scm`

This file contains highlevel (`syntax-case`) macro definitions for all non-standard macros CHICKEN provides. Normally you don't directly use this file, since it is loaded automatically by the compiler or interpreter, when the `-hygienic` option is used.

If you intend to make highlevel macros (R5RS and/or `syntax-case`) available at run-time (for example, for evaluating code at runtime that contains highlevel macros), declare the `syntax-case` unit as used and install the macro system by hand, as in this example:

```
(require-extension syntax-case)
```

```
(install-highlevel-macro-system)
```

(This is basically what the `-hygienic-at-run-time` option does, but this procedure gives you a little more control.)

install-highlevel-macro-system [procedure]

```
(install-highlevel-macro-system FEATURE ...)
```

Installs the highlevel (R5RS / `syntax-case`) macro system in the running program. `FEATURE` should be a symbol and selects the amount of non-standard macros being provided. Possible features are:

- `r5rs`

The R5RS standard derived syntax, and only those.

- `srfi-0`

SRFI-0 (`cond-expand`)

- `extensions`

R5RS standard derived syntax and all non-standard extension provided in CHICKEN

If no feature is give, `'r5rs` is assumed.

8.3 `chicken-more-macros.scm`

This file contains the definitions of all non-standard syntax forms. You normally don't use this file directly.

8.4 `chicken-ffi-macros.scm`

This file contains the definitions of macros for interfacing to foreign code, and the definitions contained in this file are automatically made available in compiled code.

8.5 `chicken-entry-points.scm`

This file contains the definition of the macros `define-entry-point` and `define-embedded`. See the section “Entry points” earlier in this manual.

8.6 `chicken-default-entry-points.scm`

This file contains boilerplate entry point definitions. See the section “Entry points”. This file automatically includes `entry-points.scm`.

8.7 `test-infrastructure.scm`

This file provides a macro based unit testing facility based upon expectations concerning evaluations of expressions. These functions return tagged lists which contain the results of the test package, test case, or expectations evaluated (there are a few other types of results dealing with the `gloss`, `todo`, and `skip` macros detailed below). These result lists are wired together during evaluation to form a large hierarchical tree in memory. This result tree is then passed to either user defined functions which traverse the tree manipulating it in any way desired, or passed to a supplied (read: defined already in `test-infrastructure.scm`) function which manipulates it in a simple way usually producing human readable or html generated output. API functions to deal with the result types are supplied and the representation of the result is black boxed to the user. It is a violation of encapsulation to inspect the representation directly, and it may change unpredictably in the future.

8.7.1 The Test Package Macro API

This macro will evaluate in a left to right fashion the clauses inside it. Clauses can only be certain things, detailed below. All of the clauses are executed, except of course if you bail out of the test package with the escape procedure mechanism. Test packages may nest indefinitely.

test-package [macro]

```
(test-package MESSAGE DESTNAME TERMNAME CLAUSES)
(test-package MESSAGE DESTNAME TERMNAME (BINDINGS) CLAUSES)
(test-package MESSAGE DESTNAME TERMNAME (warn MESSAGE) CLAUSES)
(test-package MESSAGE DESTNAME TERMNAME (warn MESSAGE) (BINDINGS) CLAUSES)■
```

- `MESSAGE` can be any scheme object, though usually it is a string.
- `DESTNAME` is an unquoted symbol for an automatic destructor object that gets called when the test package completes for any reason. This symbol is bound to

a destructor object and is available to you in the CLAUSES section of the test package. See below for the description of the destructor object interface.

- **TERMNAME** is an unquoted symbol for an escape procedure available in the body of the test package, usually, this escape procedure is passed to `(terminate ...)` which calls it for you and performs other tasks. It is not recommended to call the escape procedure directly.
- `(warn MESSAGE)` allows you to specify a warning object, usually a string, that gets associated with the test package. The **warn** function name is actually a syntax reserved word in the macro.
- **BINDINGS** are let-style bindings that you may create and exist in the lexical scope of the test package.
- **CLAUSES** are uses of `(test-case ...)` macros along with `(gloss ...)`, `(todo ...)`, `(skip ...)`, and `(terminate ...)` macros. While you may use the `(expect-* ...)` style macros directly in a test package, doing so is not recommended. If the expectation fails, the test package macro will continue evaluating until all clauses are evaluated or the escape procedure mechanism is activated. This is different than a test-case macro where upon discovery of a failed expectation, evaluation stops immediately.

8.7.2 The Test Case Macro API

This macro will evaluate in a left to right fashion the clauses inside it **stopping at the first failed expectation**. Clauses can only be certain things as detailed below. You may also stop the execution of expectations if you bail out of the test case with the escape procedure mechanism. Test cases may **NOT** nest.

test-case [macro]

```
(test-case MESSAGE DESTNAME TERMNAME CLAUSES)
(test-case MESSAGE DESTNAME TERMNAME (BINDINGS) CLAUSES)
(test-case MESSAGE DESTNAME TERMNAME (warn MESSAGE) CLAUSES)
(test-case MESSAGE DESTNAME TERMNAME (warn MESSAGE) (BINDINGS) CLAUSES)■
```

- **MESSAGE** can be any scheme object, though usually it is a string.
- **DESTNAME** is an unquoted symbol for an automatic destructor object that gets called when the test case completes for any reason. This symbol is bound to a destructor object and is available to you in the CLAUSES section of the test package. See below for the description of the destructor object interface.
- **TERMNAME** is an unquoted symbol for an escape procedure available in the body of the test case, usually, this escape procedure is passed to `(terminate ...)` which calls it for you and performs other tasks. It is not recommended to call the escape procedure directly.
- `(warn MESSAGE)` allows you to specify a warning object, usually a string, that gets associated with the test case. The **warn** function name is actually a syntax reserved word in the macro.
- **BINDINGS** are let-style bindings that you may create and exist in the lexical scope of the test case.

- CLAUSES are uses of (`expect-* ...`) macros along with (`gloss ...`), (`todo ...`), (`skip ...`), and (`terminate ...`) macros. It is important to note that upon discovery of a failed expectation, the test case stops its evaluation and returns with the previous successful, and including the failed, expectations.

8.7.3 The Expectation Macro API

An expectation at its core simply evaluates its arguments and check to see if it matches the expectation. The positive or negative result is encapsulated, along with other things such as the unevaluated expressions being checked and some messages supplied with each expectation into a particular type of black box object that one can query with the appropriate API calls(detailed below).

Expectations all have a descriptive message that can be bound to them, along with an optional warning syntax detailed below. A design decision was made to supply expectation macros for the usual types of expectations a user needs because this reduced the abstractness of an expectation into something more manageable. In a future release however, I will supply a special expectation macro where you may supply any predicate you wish along with a “type tag” of the predicate.

expect-zero [macro]

```
(expect-zero MESSAGE CLAUSE)
(expect-zero MESSAGE (warn MESSAGE) CLAUSE)
```

- This expectation checks to see if the evaluated expression passed to it is numerically equal to the exact integer zero.
- MESSAGE can be any scheme object, though usually it is a string.
- (`warn MESSAGE`) allows you to specify a warning object, usually a string, that gets associated with the expectation. The `warn` function name is actually a syntax reserved word in the macro.
- CLAUSE is a single expression which should return a exact or inexact integer.

expect-nonzero [macro]

```
(expect-nonzero MESSAGE CLAUSE)
(expect-nonzero MESSAGE (warn MESSAGE) CLAUSE)
```

- This expectation checks to see if the evaluated expression passed to it is numerically not equal to the exact integer zero.
- MESSAGE can be any scheme object, though usually it is a string.
- (`warn MESSAGE`) allows you to specify a warning object, usually a string, that gets associated with the expectation. The `warn` function name is actually a syntax reserved word in the macro.
- CLAUSE is a single expression which should return an exact or inexact integer.

expect-true [macro]

```
(expect-true MESSAGE CLAUSE)
(expect-true MESSAGE (warn MESSAGE) CLAUSE)
```

- This expectation checks to see if the evaluated expression passed to it is the value `#t`.

- MESSAGE can be any scheme object, though usually it is a string.
- (warn MESSAGE) allows you to specify a warning object, usually a string, that gets associated with the expectation. The **warn** function name is actually a syntax reserved word in the macro.
- CLAUSE is a single expression which should return #t.

expect-false [macro]

```
(expect-false MESSAGE CLAUSE)
(expect-false MESSAGE (warn MESSAGE) CLAUSE)
```

- This expectation checks to see if the evaluated expression passed to it is the value #f.
- MESSAGE can be any scheme object, though usually it is a string.
- (warn MESSAGE) allows you to specify a warning object, usually a string, that gets associated with the expectation. The **warn** function name is actually a syntax reserved word in the macro.
- CLAUSE is a single expression which should return #t.

expect-eq? [macro]

```
(expect-eq? MESSAGE EXPECTED CLAUSE)
(expect-eq? MESSAGE (warn MESSAGE) EXPECTED CLAUSE)
```

- This expectation checks to see if (eq? EXPECTED CLAUSE) is true.
- MESSAGE can be any scheme object, though usually it is a string.
- (warn MESSAGE) allows you to specify a warning object, usually a string, that gets associated with the expectation. The **warn** function name is actually a syntax reserved word in the macro.
- EXPECTED is a single expression which is evaluated and represents the value the CLAUSE **must** be eq? to in order for this expectation to return a positive result.
- CLAUSE is a single expression which, when evaluated must return an object where an eq? of this result and the EXPECTED expression is #t.
- The result object this macro produce shall contain the unevaluated CLAUSE expression as a field, but not an unevaluated EXPECTED expression.

expect-eqv? [macro]

```
(expect-eqv? MESSAGE EXPECTED CLAUSE)
(expect-eqv? MESSAGE (warn MESSAGE) EXPECTED CLAUSE)
```

- This expectation checks to see if (eqv? EXPECTED CLAUSE) is true.
- MESSAGE can be any scheme object, though usually it is a string.
- (warn MESSAGE) allows you to specify a warning object, usually a string, that gets associated with the expectation. The **warn** function name is actually a syntax reserved word in the macro.
- EXPECTED is a single expression which is evaluated and represents the value the CLAUSE **must** be eqv? to in order for this expectation to return a positive result.
- CLAUSE is a single expression which, when evaluated must return an object where an eqv? of this result and the EXPECTED expression is #t.

- The result object this macro produce shall contain the unevaluated **CLAUSE** expression as a field, but not an unevaluated **EXPECTED** expression.

expect-equal? [macro]

```
(expect-equal? MESSAGE EXPECTED CLAUSE)
(expect-equal? MESSAGE (warn MESSAGE) EXPECTED CLAUSE)
```

- This expectation checks to see if (equal? EXPECTED CLAUSE) is true.
- MESSAGE can be any scheme object, though usually it is a string.
- (warn MESSAGE) allows you to specify a warning object, usually a string, that gets associated with the expectation. The **warn** function name is actually a syntax reserved word in the macro.
- EXPECTED is a single expression which is evaluated and represents the value the CLAUSE **must** be equal? to in order for this expectation to return a positive result.
- CLAUSE is a single expression which, when evaluated must return an object where an equal? of this result and the EXPECTED expression is #t.
- The result object this macro produce shall contain the unevaluated **CLAUSE** expression as a field, but not an unevaluated **EXPECTED** expression.

expect-near? [macro]

```
(expect-near? MESSAGE EXPECTED TOL CLAUSE)
(expect-near? MESSAGE (warn MESSAGE) EXPECTED TOL CLAUSE)
```

- This expectation checks to see if (< (abs (- EXPECTED CLAUSE)) TOL)) is true.
- MESSAGE can be any scheme object, though usually it is a string.
- (warn MESSAGE) allows you to specify a warning object, usually a string, that gets associated with the expectation. The **warn** function name is actually a syntax reserved word in the macro.
- EXPECTED is a single expression which is evaluated and represents the value the CLAUSE **must** be “near” to in order for this expectation to return a positive result.
- CLAUSE is a single expression which should return an inexact or exact number.
- TOL is a single expression which, when evaluated must return a tolerance value(usually a small inexact number like .0001).
- The result object this macro produce shall contain the unevaluated **CLAUSE** expression as a field, but not the unevaluated **EXPECTED** or **TOL** expression.

expect-positive [macro]

```
(expect-positive MESSAGE CLAUSE)
(expect-positive MESSAGE (warn MESSAGE) CLAUSE)
```

- This expectation checks to see if the evaluated expression passed to it is a positive value greater than zero.
- MESSAGE can be any scheme object, though usually it is a string.
- (warn MESSAGE) allows you to specify a warning object, usually a string, that gets associated with the expectation. The **warn** function name is actually a syntax reserved word in the macro.
- CLAUSE is a single expression which should return an inexact or exact number.

expect-negative [macro]

```
(expect-negative MESSAGE CLAUSE)
(expect-negative MESSAGE (warn MESSAGE) CLAUSE)
```

- This expectation checks to see if the evaluated expression passed to it is a negative value less than zero.
- MESSAGE can be any scheme object, though usually it is a string.
- (warn MESSAGE) allows you to specify a warning object, usually a string, that gets associated with the expectation. The **warn** function name is actually a syntax reserved word in the macro.
- CLAUSE is a single expression which should return an inexact or exact number.

8.7.4 Result Object API

Expectations, test cases, test packages, and helper macros(**gloss**, **todo**, **etc**) all return an object that contains the results and other various aspects of the action performed which ultimately get wired together to form the result tree. This collection of functions forming the rest of the test infrastructure API allows manipulation of these results in an abstracted way as to allow changing of the representation in the future.

8.7.5 Test Package Result Object API

If any of these API functions, except **test-package-result?**, are passed something that isn't a test package result object, they will return 'not-a-test-package-result'.

test-package-result? [procedure]

```
(test-package-result? RESULT)
```

If RESULT is a result object from the invocation of a test package macro, then this function will return #t. Otherwise, it will return #f.

test-package-result-result-ref [procedure]

```
(test-package-result-result-ref RESULT)
```

Returns the boolean result associated with the test package RESULT object.

test-package-result-message-ref [procedure]

```
(test-package-result-message-ref RESULT)
```

Returns the message object associated with the test package RESULT object.

test-package-result-exps-ref [procedure]

```
(test-package-result-exps-ref RESULT)
```

Returns the list of result objects associated with the test package RESULT object.

test-package-result-warning? [procedure]

```
(test-package-result-warning? RESULT)
```

If a warning had been attached to this test package, this function will return #t, otherwise it will be #f.

test-package-result-warning-ref [procedure]
 (test-package-result-warning-ref RESULT)

If a warning had been attached to this test package, this function will return the warning object supplied by the user, otherwise it shall return '().

8.7.6 Test Case Result Object API

If any of these API functions, except **test-case-result?**, are passed something that isn't a test case result object, they will return 'not-a-test-case-result.

test-case-result? [procedure]
 (test-case-result? RESULT)

If RESULT is a result object from the invocation of a test case macro, then this function will return #t. Otherwise, it will return #f.

test-case-result-result-ref [procedure]
 (test-case-result-result-ref RESULT)

Returns the boolean result associated with the test case RESULT object.

test-case-result-message-ref [procedure]
 (test-case-result-message-ref RESULT)

Returns the message object associated with the test case RESULT object.

test-case-result-expectations-ref [procedure]
 (test-case-result-expectations-ref RESULT)

Returns the list of expectation result objects associated with the test case RESULT object.

test-case-result-warning? [procedure]
 (test-case-result-warning? RESULT)

If a warning had been attached to this test case, this function will return #t, otherwise it will be #f.

test-case-result-warning-ref [procedure]
 (test-case-result-warning-ref RESULT)

If a warning had been attached to this test case, this function will return the warning object supplied by the user, otherwise it shall return '().

8.7.7 Expect Result Object API: Single Clause Style Expectation

These expectations all take the form of passing a single expression to them to see if they match some a priori expectation. If any of these API functions, except **expect-result?**, are passed something that isn't a single clause style expectation result object, they will return 'not-an-expect-result.

expect-result? [procedure]

(expect-result? RESULT)

If **RESULT** is a single clause style result object from the invocation of an expectation macro, then this function will return **#t**. Otherwise, it will return **#f**.

expect-result-result-ref [procedure]

(expect-result-result-ref RESULT)

Returns the boolean result associated with the single clause style expectation **RESULT** object.

expect-result-specific-ref [procedure]

(expect-result-specific-ref RESULT)

This retrieves the “specific” field of a particular single clause style expectation. For example, if you had a result object from an invocation of a **(expect-zero? "foobar" (- 1 1))** expectation, then the “specific” field of the expectation result object will be the string **"zero"**. Here is a table describing what the “specific” fields are for each kind of single clause style expectation:

Single Clause Style Expectation	Associated Specific String
expect-zero	"zero"
expect-nonzero	"nonzero"
expect-true	"true"
expect-false	"false"
expect-positive	"positive"
expect-negative	"negative"

expect-result-message-ref [procedure]

(expect-result-message-ref RESULT)

Returns the message object associated with the single clause style expectation **RESULT** object.

expect-result-uneval-ref [procedure]

(expect-result-uneval-ref RESULT)

Returns the unevaluated expression supplied to a single clause style expectation macro.

expect-result-eval-ref [procedure]

(expect-result-eval-ref RESULT)

Returns the evaluated expression supplied to a single clause style expectation macro.

expect-result-warning? [procedure]

(expect-result-warning? RESULT)

If a warning had been attached to this expectation, this function will return **#t**, otherwise it will be **#f**.

expect-result-warning-ref [procedure]

(expect-result-warning-ref RESULT)

If a warning had been attached to this expectation, this function will return the warning object supplied by the user, otherwise it shall return **'()**.

8.7.8 Expect Result Object API: Equivalence Style Expectation

These expectations all take the form of passing a two expressions, the “left hand side” and the “right hand side” to them to see if they match some a priori equivalence. The left hand side is that which you expect the right hand side to be equivalent. If any of these API functions, except **expect-equivalence-result?**, are passed something that isn’t a single clause style expectation result object, they will return `'not-an-expect-equivalence-result`.

expect-equivalence-result? [procedure]

(expect-equivalence-result? RESULT)

If RESULT is a comparison style result object from the invocation of an expectation macro, then this function will return `#t`. Otherwise, it will return `#f`.

expect-equivalence-result-result-ref [procedure]

(expect-equivalence-result-result-ref RESULT)

Returns the boolean result associated with the comparison style expectation RESULT object.

expect-equivalence-result-specific-ref [procedure]

(expect-equivalence-result-specific-ref RESULT)

This retrieves the “specific” field of a particular equivalence style expectation. For example, if you had a result object from an invocation of a `(expect-equal? "foobar" 0 (- 1 1))` expectation, then the “specific” field of the expectation result object will be the string **"equal"**. Here is a table describing what the “specific” fields are for each kind of equivalence style expectation:

Equivalence Style Expectation	Associated Specific String
<code>expect-eq</code>	<code>"eq"</code>
<code>expect-eqv</code>	<code>"eqv"</code>
<code>expect-equal</code>	<code>"equal"</code>

expect-equivalence-result-message-ref [procedure]

(expect-equivalence-result-message-ref RESULT)

Returns the message object associated with the equivalence style expectation RESULT object.

expect-equivalence-result-lhs-eval-ref [procedure]

(expect-equivalence-result-lhs-eval-ref RESULT)

Returns the evaluated “left hand side” expression supplied to an equivalence style expectation.

expect-equivalence-result-rhs-uneval-ref [procedure]

(expect-equivalence-result-rhs-uneval-ref RESULT)

Returns the unevaluated “right hand side” expression supplied to an equivalence style expectation.

expect-equivalence-result-rhs-eval-ref [procedure]

(expect-equivalence-result-rhs-eval-ref RESULT)

Returns the evaluated “right hand side” expression supplied to an equivalence style expectation.

expect-equivalence-result-warning? [procedure]
 (expect-equivalence-result-warning? RESULT)

If a warning had been attached to this expectation, this function will return `#t`, otherwise it will be `#f`.

expect-equivalence-result-warning-ref [procedure]
 (expect-equivalence-result-warning-ref RESULT)

If a warning had been attached to this expectation, this function will return the warning object supplied by the user, otherwise it shall return `'()`.

8.7.9 Expect Result Object API: Tolerance Style Expectation

This is a specialized expectation which accepts three expressions and checks to see if the “right hand side” is within a “tolerance” of the “left hand side”. There is only one expectation in the tolerance style currently. If any of these API functions, except **expect-tolerance-result?**, are passed something that isn’t a tolerance style expectation result object, they will return `'not-an-expect-tolerance-result`.

expect-tolerance-result? [procedure]
 (expect-tolerance-result? RESULT)

If `RESULT` is a tolerance style result object from the invocation of an expectation macro, then this function will return `#t`. Otherwise, it will return `#f`.

expect-tolerance-result-result-ref [procedure]
 (expect-tolerance-result-result-ref RESULT)

Returns the boolean result associated with the tolerance style expectation `RESULT` object.

expect-tolerance-result-specific-ref [procedure]
 (expect-tolerance-result-specific-ref RESULT)

This retrieves the “specific” field of a particular tolerance style expectation. For example, if you had a result object from an invocation of a `(expect-near? "foobar" 100 .01 100.001)` expectation, then the “specific” field of the expectation result object will be the string `"near"`. Here is a table describing what the “specific” fields are for each kind of tolerance style expectation:

Tolerance Style Expectation	Associated Specific String
<code>expect-near</code>	<code>"near"</code>

expect-tolerance-result-message-ref [procedure]
 (expect-tolerance-result-message-ref RESULT)

Returns the message object associated with a tolerance style expectation `RESULT` object.

expect-tolerance-result-lhs-eval-ref [procedure]
 (expect-tolerance-result-lhs-eval-ref RESULT)

Returns the evaluated “left hand side” expression supplied to a tolerance style expectation.

expect-tolerance-result-lhs-tol-eval-ref [procedure]

(expect-tolerance-result-lhs-tol-eval-ref RESULT)

Returns the evaluated “tolerance” expression supplied to a tolerance style expectation.

expect-tolerance-result-rhs-uneval-ref [procedure]

(expect-tolerance-result-rhs-uneval-ref RESULT)

Returns the unevaluated “right hand side” expression supplied to a tolerance style expectation.

expect-tolerance-result-rhs-eval-ref [procedure]

(expect-tolerance-result-rhs-eval-ref RESULT)

Returns the evaluated “right hand side” expression supplied to a tolerance style expectation.

expect-tolerance-result-warning? [procedure]

(expect-tolerance-result-warning? RESULT)

If a warning had been attached to this expectation, this function will return #t, otherwise it will be #f.

expect-tolerance-result-warning-ref [procedure]

(expect-tolerance-result-warning-ref RESULT)

If a warning had been attached to this expectation, this function will return the warning object supplied by the user, otherwise it shall return '().

8.7.10 Various Helper API

These upcoming macros and functions allow the author of the test suite to better control both the execution flow of the test suite and “decoration” of the test suite with important information like things yet to do, or just plain documentation.

8.7.11 Termination API

When executing in a test package or a test case, one might discover some catastrophic failure of such proportions that it is utterly impossible to continue executing the test case or test package. When that happens you can use the termination facility to exit the test case or test package. Of course, no more expressions will be evaluated in the scope of the termination. It is recommended that you use this method of terminating the test case or test package evaluation since it wraps some contextual information up into the termination result so you can figure out what happened(and where) later when analyzing the result tree.

When using the manipulation API for a terminate result, if you pass a result to one of these function that is not a terminate result, it will return 'not-a-terminate-result.

terminate [procedure]

(terminate TERMFUNC MESSAGE)

- This is the recommended termination method for a test case or a test package.

- **TERMFUNC** is the name of the termination procedure that you specified in a test case or test package. You may pass any test package or test case termination function available to you in the lexical scope in which you call this function. The termination will take effect in the scope of the created termination function.
- **MESSAGE** can be any scheme object, though usually it is a string.

terminate-result? [procedure]
 (terminate-result? RESULT)

If **RESULT** is a termination result object from the invocation of a termination function, then this function will return **#t**. Otherwise, it will return **#f**.

terminate-result-result-ref [procedure]
 (terminate-result-result-ref RESULT)

Returns the boolean result associated with the termination function **RESULT** object. This is currently hard coded to be **#f**.

terminate-result-scope-ref [procedure]
 (terminate-result-scope-ref RESULT)

The “scope” of the termination result is exactly the **MESSAGE** parameter supplied to the test case or test package associated with the **TERMFUNC**.

terminate-result-container-ref [procedure]
 (terminate-result-container-ref RESULT)

The “container” of the termination result is going to be either **'test-package** or **'test-case** depending upon which the **TERMFUNC** was associated.

terminate-result-message-ref [procedure]
 (terminate-result-message-ref RESULT)

Returns the message object associated with the termination **RESULT** object.

8.7.12 Destructor Object API

The destructor object allows for you to create helper functions which clean up for you usually in case of aborting of a test case or package. For example, suppose you are testing whether or not file writing to a file works correctly in a test case, so, you’d perform an expectation to open the file, and then queue a function in the destructor to remove the file, and then perform the expectation of the write. If the write(or subsequent) expectation fails, then the test case will **automatically** invoke the helper cleanup function specified in the destructor object that removes the file.

NOTE: This API is still a little experimental in the sense that eventually the destructor object should return a typed result that contains the success of the individual destructor calls. But for now, it is functional for what it does. Also, be **VERY CAREFUL** that you specify the arguments to these API calls correctly since due to lambda functions not being comparable, this API cannot guarantee that a true destructor object name had been passed to it. So if you call one of the following API calls incorrectly, the behavior will be undefined.

destructor-atexit! [procedure]

(destructor-atexit! DESTNAME FUNC ARGS ...)

This will insert a promise to calculate the **FUNC** with the supplied **ARGS ...** into a queue in the **DESTNAME** destructor object. Multiple invocations of this API call will continue to queue up (FUNC ARGS ...) promises indefinitely. This function returns a special **ignore** type that is ignored by the test infrastructure system.

destructor-activate! [procedure]

(destructor-activate! DESTNAME)

This function will call, in order of queueing, all the promises embedded into this destructor object, and then delete the queue. This function is **ALWAYS** called at the completion of a test package or test case; so be careful that the destructor object doesn't contain anything harmful. However, you may call it yourself and if you do, it will execute all of the queued promises and then **clear** itself. This function returns a special **ignore** type that is ignored by the test infrastructure system.

destructor-clear! [procedure]

(destructor-clear! DESTNAME)

This function completely removes all of the promises associated with the destructor object **DESTNAME**. This function returns a special **ignore** type that is ignored by the test infrastructure system.

destructor-dump [procedure]

(destructor-dump DESTNAME)

This function, mostly used for debugging purposes, prints out a simple representation of the queued atexit functions to the current port. This function returns a special **ignore** type that is ignored by the test infrastructure system.

8.7.13 Todo API

The purpose of the todo API is to allow the author of a test suite the ability to record into the result tree for later analysis that something still needs to be done. This way you can count/manipulate this information at a later date. Todo macro invocations can occur inside of test cases or test packages.

todo [macro]

(todo MESSAGE)

(todo (warn WARNING) MESSAGE)

- **MESSAGE** can be any scheme object, though usually it is a string.
- (warn **WARNING**) allows you to specify a warning object, usually a string, that gets associated with the todo. The **warn** function name is actually a syntax reserved word in the macro.

todo-result? [procedure]

(todo-result? RESULT)

If **RESULT** is a todo result object from the invocation of a todo macro, then this function will return **#t**. Otherwise, it will return **#f**.

todo-result-message-ref [procedure]
 (todo-result-message-ref RESULT)

Returns the message object associated with the todo RESULT object.

todo-result-warning? [procedure]
 (todo-result-warning? RESULT)

If a warning had been attached to this todo, this function will return #t, otherwise it will be #f.

todo-result-warning-ref [procedure]
 (todo-result-warning-ref RESULT)

If a warning had been attached to this todo, this function will return the warning object supplied by the user, otherwise it shall return '().

8.7.14 Gloss API

The purpose of the gloss API is to allow the author of a test suite the ability to record messages into the result tree purely for documentation purposes. Gloss macro invocations can occur inside of test cases or test packages.

gloss [macro]
 (gloss MESSAGE)
 (gloss (warn WARNING) MESSAGE)

- MESSAGE can be any scheme object, though usually it is a string.
- (warn WARNING) allows you to specify a warning object, usually a string, that gets associated with the gloss. The warn function name is actually a syntax reserved word in the macro.

gloss-result? [procedure]
 (gloss-result? RESULT)

If RESULT is a gloss result object from the invocation of the gloss macro, then this function will return #t. Otherwise, it will return #f.

gloss-result-message-ref [procedure]
 (gloss-result-message-ref RESULT)

Returns the message object associated with the gloss RESULT object.

gloss-result-warning? [procedure]
 (gloss-result-warning? RESULT)

If a warning had been attached to this gloss, this function will return #t, otherwise it will be #f.

gloss-result-warning-ref [procedure]
 (gloss-result-warning-ref RESULT)

If a warning had been attached to this gloss, this function will return the warning object supplied by the user, otherwise it shall return '().

8.7.15 Skip API

The purpose of the skip API is to allow the author of a test suite to completely skip evaluation of a set of expressions. Skip macro invocations can occur inside of test cases or test packages.

skip [macro]

```
(skip MESSAGE CLAUSES)
(skip (warn WARNING) MESSAGE CLAUSES)
```

- MESSAGE can be any scheme object, though usually it is a string.
- (warn WARNING) allows you to specify a warning object, usually a string, that gets associated with the gloss. The **warn** function name is actually a syntax reserved word in the macro.
- CLAUSES can be more than one expression (as in a lambda form) that does **NOT** get evaluated at any time.

skip-result? [procedure]

```
(skip-result? RESULT)
```

If RESULT is a skip result object from the invocation of the skip macro, then this function will return #t. Otherwise, it will return #f.

skip-result-message-ref [procedure]

```
(skip-result-message-ref RESULT)
```

Returns the message object associated with the skip RESULT object. Hopefully, it was stated why this set of clauses had been skipped.

skip-result-warning? [procedure]

```
(skip-result-warning? RESULT)
```

If a warning had been attached to this skip, this function will return #t, otherwise it will be #f.

skip-result-warning-ref [procedure]

```
(skip-result-warning-ref RESULT)
```

If a warning had been attached to this skip, this function will return the warning object supplied by the user, otherwise it shall return '().

8.7.16 Side Effect API

This section of the API just contains a single macro currently since it is considered a little experimental for now. The side effecting evaluates all of its arguments as in a (**begin** ...) form, it returns a result that is completely ignored by the system and unavailable to the output analysis code.

side-effect [macro]

```
(side-effect CLAUSES)
```

This macro expands into a begin form the clauses in order and when it finishes evaluating them, returns a result that is silently ignored by the testing infrastructure

system. Usually this is used in conjunction with `(set! ...)` or with complicated situations where a lot of setup work must happen for an expectation to be performed.

8.7.17 Miscellaneous API

This section contains a few functions whose purpose is to simplify certain kinds of manipulations of result objects.

***-result?** [procedure]

`(*-result? RESULTOBJ)`

This function will return `#t` if `RESULTOBJ` is any kind of an evaluated result object. Otherwise, it shall return `#f`.

***-result-ref** [procedure]

`(*-result-ref RESULTOBJ)`

This function will return the result of any kind of `RESULTOBJ` passed to it if it is indeed a true result object. Otherwise, it shall emit an error to the current port, and return `#f`.

all-testpackage-results-true? [procedure]

`(all-testpackage-results-true? RESULTLIST)`

This function takes the result of a call to `(test-package-result-result-ref PACKAGERESULTOBJ)` and returns `#t` if every single contained result in that list had been true, or `#f` otherwise.

all-testcase-expectations-true? [procedure]

`(all-testcase-expectations-true? RESULTLIST)`

This function takes the result of a call to `(test-case-result-result-ref CASERESULTOBJ)` and returns `#t` if every single contained result in that list had been true, or `#f` otherwise.

8.7.18 Analysis of the Result Tree

Once a result tree has been evaluated and constructed in memory, what do you do with it? Well, you can do anything you want with it if you choose to write the analysis or output generation functions and pass it the evaluated result tree, and this is, in fact, encouraged. However, usually you just want to print out the tree in a human readable format so you can check things before the serious analysis code gets written. So, to save work for the test suite designer, a tiny API has been written to produce human readable output given a tree of results rooted in a single test package. Of course the single test package may have many other test packages and test cases embedded within it.

8.7.19 Output Generation API

println [procedure]

`(println CLAUSES)`

This function will print all of the evaluated `CLAUSES` in order with a newline at the end of it.

printnl [procedure]
 (printnl INDENT CLAUSES)

This function will INDENT a number of spaces and then print all of the evaluated CLAUSES in order with a newline at the end of it.

output-style-human [procedure]
 (output-style-human RESULTTREE)

This function will print out a human readable rendering of the RESULTTREE and return the toplevel package result.

8.7.20 Example Usages of the Test Suite Infrastructure

This section contains some simple examples of how to author test suites.

Here is a simple example:

```
(let ((result
      ;; output-style-human function requires a single test package
      ;; to encapsulate everything.
      (test-package "Arithmetic Operators" pd pe

        (test-case "Testing '+'" d e
          (expect-equal "Adding two positive numbers" 2 (+ 1 1))
          (expect-equal "Adding two negative numbers" -2 (+ -1 -1))
          (expect-zero "Adding positive and negative" (+ -1 1)))

        (test-case "Testing '-'" d e
          (expect-zero "Subtracting two positive numbers" (- 1 1))
          (expect-zero "Subtracting two negative numbers" (- -1 -1))
          (expect-equal "Subtracting positive and negative" -2 (- -1 1))))))
  (output-style-human result))
```

The above example, when evaluated, will produce some human readable output and the a #t value as the result of the top level package. The **result** variable contains the tree of evaluated expectations, test cases, and the package arranged in a hierarchy extremely similar to the nesting of the above macros. If you desire to manipulate the result tree yourself, you may use the various APIs to manipulate the various results. Please see the implementation of (**output-style-human ...**) (it isn't large) in the `test-infrastructure.scm` file to see an example of this.

The variables: **pe**, **e** are the escape functions you may use with the (**terminate ...**) function call if you wish to abort the above code somewhere.

The variables: **pd**, **d** allow use of a "destructor" object which allows you to run side effecting functions at the "finishing" point of the evaluation of the test case or test package. These functions are run no matter if the code succeeded correctly or not, so be careful to manage the destructor object carefully so you don't perform unwanted side effects. The names of the destructor objects you supply are lexically scoped in the bodies of the test case or test package.

Now, here is some example output that (**output-style-human ...**) might generate with the above testing code:

```
Begin Package: Arithmetic Operators
Begin Test Case: Testing '+'
  Begin Expectation: Adding two positive numbers
  Expect equal
    Expected Value:
    2
    Unevaluated:
    (+ 1 1)
    Evaluated:
    2
  Result: #t
  End Expectation: Adding two positive numbers

  Begin Expectation: Adding two negative numbers
  Expect equal
    Expected Value:
    -2
    Unevaluated:
    (+ -1 -1)
    Evaluated:
    -2
  Result: #t
  End Expectation: Adding two negative numbers

  Begin Expectation: Adding positive and negative
  Expect zero
    Unevaluated:
    (+ -1 1)
    Evaluated:
    0
  Result: #t
  End Expectation: Adding positive and negative

Result: #t
End Test Case: Testing '+'

Begin Test Case: Testing '-'
  Begin Expectation: Subtracting two positive numbers
  Expect zero
    Unevaluated:
    (- 1 1)
    Evaluated:
    0
  Result: #t
  End Expectation: Subtracting two positive numbers

  Begin Expectation: Subtracting two negative numbers
```

```
Expect zero
  Unevaluated:
    (- -1 -1)
  Evaluated:
    0
Result: #t
End Expectation: Subtracting two negative numbers

Begin Expectation: Subtracting positive and negative
Expect equal
  Expected Value:
    -2
  Unevaluated:
    (- -1 1)
  Evaluated:
    -2
Result: #t
End Expectation: Subtracting positive and negative

Result: #t
End Test Case: Testing '-'

Result: #t
End Package: Arithmetic Operators

#t
```

9 Data Representation

There exist two different kinds of data objects in the CHICKEN system: immediate and non-immediate objects. Immediate objects are represented by a tagged machine word, which is usually of 32 bits length (64 bits on 64-bit architectures). The immediate objects come in four different flavors:

- **fixnums**, that is, small exact integers, distinguished by the lowest order bit in the machine word set to 1. This gives fixnums a range of 31 bits for the actual numeric value (63 bit on 64 bit architectures).
- **characters**, where the lowest four bits of machine words containing characters are equal to `C_CHARACTER_BITS`. The ASCII code of the character is encoded in bits 9 to 16, counting from 1 and starting at the lowest order position.
- **booleans**, where the lowest four bits of machine words containing booleans are equal to `C_BOOLEAN_BITS`. Bit 5 (counting from 0 and starting at the lowest order position) is one if the boolean designates true, or 0 if it is false.
- **other values**: the empty list, void and end-of-file. The lowest four bits of machine words containing these values are equal to `C_SPECIAL_BITS`. Bits 5 to 8 contain an identifying number for this type of object. The following constants are defined: `C_SCHEME_END_OF_LIST` `C_SCHEME_UNDEFINED` `C_SCHEME_END_OF_FILE`

Non-immediate objects are blocks of data represented by a pointer into the heap. The first word of the data block contains a header, which gives information about the type of the object. The header has the size of a machine word, usually 32 bits (64 bits on 64 bit architectures).

- bits 1 to 24 (starting at the lowest order position) contain the length of the data object, which is either the number of bytes in a string (or byte-vector) or the the number of elements for a vector or for a structure type.
- bits 25 to 28 contain the type code of the object.
- bits 29 to 32 contain miscellaneous flags used for garbage collection or internal data type dispatching. These flags are:

`C_GC_FORWARDING_BIT`

Flag used for forwarding garbage collected object pointers.

`C_BYTEBLOCK_BIT`

Flag that specifies whether this data object contains raw bytes (a string or byte-vector) or pointers to other data objects.

`C_SPECIALBLOCK_BIT`

Flag that specifies whether this object contains a “special” non-object pointer value in its first slot. An example for this kind of objects are closures, which are a vector-type object with the code-pointer as the first item.

`C_8ALIGN_BIT`

Flag that specifies whether the data area of this block should be aligned on an 8-byte boundary (floating-points numbers, for example).

The actual data follows immediately after the header. Note that block-addresses are always aligned to the native machine-word boundary. Scheme data objects map to blocks in the following manner:

- pairs: vector-like object (type bits `C_PAIR_TYPE`), where the car and the cdr are contained in the first and second slots, respectively.
- vectors: vector object (type bits `C_VECTOR_TYPE`).
- strings: byte-vector object (type bits `C_STRING_TYPE`).
- procedures: special vector object (type bits `C_CLOSURE_TYPE`). The first slot contains a pointer to a compiled C function. Any extra slots contain the free variables (since a flat closure representation is used).
- flonum: a byte-vector object (type bits `C_FLONUM_BITS`). Slots one and two (or a single slot on 64 bit architectures) contain a 64-bit floating-point number, in the representation used by the host systems C compiler.
- symbol: a vector object (type bits `C_SYMBOL_TYPE`). Slots one and two contain the toplevel variable value and the print-name (a string) of the symbol, respectively.
- port: a special vector object (type bits `C_PORT_TYPE`). The first slot contains a pointer to a file- stream, if this is a file-pointer, or NULL if not. The other slots contain housekeeping data used for this port.
- structure: a vector object (type bits `C_STRUCTURE_TYPE`). The first slot contains a symbol that specifies the kind of structure this record is an instance of. The other slots contain the actual record items.
- pointer: a special vector object (type bits `C_POINTER_TYPE`). The single slot contains a machine pointer.
- tagged pointer: similar to a pointer (type bits `C_TAGGED_POINTER_TYPE`), but the object contains an additional slot with a tag (an arbitrary data object) that identifies the type of the pointer.

Data objects may be allocated outside of the garbage collected heap, as long as their layout follows the above mentioned scheme. But care has to be taken not to mutate these objects with heap-data (i.e. non-immediate objects), because this will confuse the garbage collector.

For more information see the header file `chicken.h`.

10 Bugs and limitations

- Compiling large files takes too much time.
- There is no support for rationals, complex numbers or extended-precision integers (bignums).
- The maximal number of arguments that may be passed to a compiled procedure or macro is 126 (or 1024 on x86 platforms). A macro-definition that has a single rest-parameter can have any number of arguments.
- The maximum number of values that can be passed to continuations captured using `call-with-current-continuation` is 126.
- Some numeric procedures are missing since CHICKEN does not support the full numeric tower.
- If a known procedure has unused arguments, but is always called without those parameters, then the optimizer “repairs” the procedure in certain situations and removes the parameter from the lambda-list.
- `eval-when` doesn’t allow toplevel definitions inside its body in combination with hygienic macros.
- `port-position` currently works only for input ports.
- Leaf routine optimization can theoretically result in code that thrashes, if tight loops perform excessively many mutations.
- Building CHICKEN on RS/6000 systems under AIX is currently not possible, due to strange assembler errors during compilation of the compiler sources.
- If `eval` is invoked with `scheme-report-environment` or `null-environment` inside the interpreter, then non-standard syntax is still visible, unless the interpreter has been started with the `-strict` option.
- When the highlevel macro system is used, line number information is not properly maintained.
- `format` is not reentrant. This means that recursive invocation of this procedure (either inside `print-object` methods or record-printer defined with `define-record-printer` will not work.
- User-defined types are currently not supported in the argument and result specifications for entry-points defined with `define-entry-point`.

11 Acknowledgements

- Jonah Beckford added CHICKEN-support to **SWIG** and provided support for shared libraries and dynamic loading under Windows.
- “Category 5” ported CHICKEN to several BSD platforms and suggested a great many improvements.
- Linh Dang translated the TeX manual into texinfo format and wrote the hen emacs mode.
- Steve Elkins ported CHICKEN to OpenBSD.
- Tollef Fog Heen and Thomas Weidner helped porting CHICKEN to the AMD-64 platform.
- Tony Garnock-Jones ported CHICKEN to HP-UX and provided countless fixes and improvements.
- Sven Hartrumpf helped porting CHICKEN to the UltraSparc, suggested many improvements and helped fixing numerous bugs.
- Bruce Hoult fixed several bugs and pointed out performance improvements.
- Dale Jordan pointed out several bugs, helped fixing problems on the Cygwin platform and contributed the `calendar.scm` example script.
- Peter Keller translated the manual from HTML into LaTeX and contributed the testing infrastructure code.
- Kirill Lisovsky found a couple of bugs while porting Oleg Kiselyov’s SSAX XML parser to CHICKEN.
- Dennis Marti ported CHICKEN to Mac OS X.
- Chris Moline and Bakul Shah helped porting CHICKEN to FreeBSD.
- Davide Puricelli maintains the Debian package.
- Doug Quale contributed the configuration scripts for installation on UNIX-like systems, suggested numerous improvements and was generally very helpful.
- Benedikt Rosenau found several bugs and spent a lot of time testing the system and pointing out improvements.
- Michele Simionato discovered several bugs and provided numerous helpful suggestions.
- Dorai Sitaram pointed out several improvements in the TeX manual.
- Mike Thomas ported CHICKEN to the Mingw32 platform.
- John Tobey ported CHICKEN to MIPS.
- Panagiotis Vossos ported CHICKEN to Alpha/Linux.
- Peter Wang produced countless bugfixes and helpful suggestions.
- Jorg Wittenberger found and fixed countless bugs in the runtime system.
- CHICKEN contains code from several people:
 - Eli Barzilay: some performance tweaks used in TinyCLOS.
 - Anthony Carrico: the option parsing facility.
 - Mikael Djurfeldt: topological sort used by compiler.
 - Marc Feeley: pretty-printer.

- Aubrey Jaffer: implementation of `dynamic-wind`.
- R. Kent Dybvig, Oscar Waddel, Robert Hieb & Carl Bruggeman: `syntax-case` macro system.
- Gregor Kiczales: original implementation of TinyCLOS.
- Dirk Lutzebaeck: Common LISP `format`.
- Richard O’Keefe: sorting routines.
- Jussi Piitulainen: reference implementation for SRFI-25.
- Olin Shivers: implementation of `let-optionals[*]` and reference implementations of SRFI-1, SRFI-13 and SRFI-14.
- Dorai Sitaram: the PREGEXP regular expression package and TeX2page, which was used to generate the HTML documentation.
- Andrew Wilcox: queues.
- Andrew Wright: pattern matcher.

Thanks also to:

William Annis, Marc Baily, Peter Barabas, Peter Bex, Dave Bodestab, T. Kurt Bond, Terence Brannon, Roy Bryant, Taylor Campbell, Franklin Chen, Grzegorz Chrupala, James Crippen, Alejandro Forero Cuervo, Brian Denheyer, Chris Double, Petter Egesund, Daniel B. Faken, Fizzie, Kimura Fuyuki, Martin Gasbichler, Joey Gibson, Johannes Groedem, Andreas Gustafsson, Jun-ichiro itojun Hagino, Matthias Heiler, Karl M. Hegbloom, William P. Heinemann, Dale Jordan, Valentin Kamysenko, Ron Kneusel, Matthias Koeppe, Todd R. Kueny Sr, Charles Martin, Alain Mellan, Perry Metzger, Scott G. Miller, Mikael, Bruce Mitchener, Eric Merrit, Eric E. Moore, o.t., David Rush, Lars Rustemeier, Oskar Schirmer, Burton Samograd, Ronald Schroder, Spencer Schumann, Shmul, Jeffrey B. Siegal, Robert Skeels, Jason Songhurst, Clifford Stein, Christian Tismer, Vladimir Tsichevsky, Neil van Dyke, Sander Vesik, Shawn Wagner, Matthew Welland, Richard Zidlicky and Houman Zolfaghari for bug-fixes, tips, suggestions and moral support.

Bibliography

Henry Baker: *CONS Should Not CONS Its Arguments, Part II: Cheney on the M.T.A.*

<http://home.pipeline.com/~hbaker1/CheneyMTA.html>

Revised⁵ Report on the Algorithmic Language Scheme

<http://www.schemers.org/Documents/Standards/R5RS>

Index

#

#!	25
##	25
#<#TAG	24
#>	24
#>!	25
#>?	25

\$

\$	20
----	----

&

&	20
---	----

*

*-result?	163
*-result-ref	163

-

->string	58
----------	----

:

:optional	26
-----------	----

<

<array>	107
<boolean>	106
<byte-vector>	107
<c++-class>	108
<char-set>	108
<char>	107
<class>	107
<condition>	107
<end-of-file>	107
<entity-class>	107
<environment>	107
<exact>	107
<f32vector>	108
<f64vector>	108
<generic>	107
<hash-table>	107
<inexact>	107
<input-port>	107
<integer>	107
<locative>	108
<lock>	108
<method>	107
<mmap>	108

<null>	107
<number>	107
<object>	107
<output-port>	107
<pair>	107
<pointer>	108
<port>	107
<primitive>	106
<procedure-class>	107
<procedure>	107
<promise>	108
<queue>	107
<s16vector>	108
<s32vector>	108
<s8vector>	108
<string>	107
<structure>	107
<symbol>	107
<tagged-pointer>	108
<tcp-listener>	108
<time>	108
<u16vector>	108
<u32vector>	108
<u8vector>	108
<vector>	107

_

_exit	81
-------	----

#\$EXPRESSION

#\$EXPRESSION	24
---------------	----

#'EXPRESSION

#'EXPRESSION	24
--------------	----

#, (CONSTRUCTORNAME DATUM ...)

#, (CONSTRUCTORNAME DATUM ...)	24
--------------------------------	----

#:SYMBOL

#:SYMBOL	24
----------	----

#;EXPRESSION

#;EXPRESSION	24
--------------	----

#<<TAG

#<<TAG	24
--------	----

#| ... |#

#| ... |# 24

A

absolute-pathname? 86
 add-method 102
 add1 36
 address->pointer 91
 advise 19
 align-to-word 93
 alist-update! 51
 all-testcase-expectations-true? 163
 all-testpackage-results-true? 163
 allocate 91
 allocate-instance 104
 always-bound 32
 and-let* 27
 andmap 45
 argc+argv 124
 argv 42
 arithmetic-shift 37
 assert 31

B

binary-search 61
 bitwise-and 37
 bitwise-ior 37
 bitwise-not 37
 bitwise-xor 37
 block 32
 block-global 32
 block-ref 99
 block-set! 99
 bound-to-procedure 32
 build-platform 42
 butlast 51
 byte-vector 94
 byte-vector->f32vector 62
 byte-vector->f64vector 62
 byte-vector->list 94
 byte-vector->s16vector 62
 byte-vector->s32vector 62
 byte-vector->s8vector 62
 byte-vector->string 94
 byte-vector->u16vector 62
 byte-vector->u32vector 62
 byte-vector->u8vector 62
 byte-vector-fill! 94
 byte-vector-length 94
 byte-vector-ref 95
 byte-vector-set! 95
 byte-vector? 94

C

C_alloc 137
 C_block_item 138
 C_c_string 137
 C_callback 122
 C_character_code 137
 C_data_pointer 138
 C_fix 136
 C_flonum 137
 C_flonum_magnitude 137
 C_gc_protect 138
 C_gc_unprotect 138
 C_header_bits 138
 C_header_size 137
 C_int_to_num 137
 C_intern2 137
 C_intern3 137
 C_list 137
 C_make_character 136
 C_make_header 138
 C_mpointer 137
 C_mutate 138
 C_num_to_int 137
 C_pair 137
 C_pointer_address 137
 C_save 136
 C_SCHEME_END_OF_FILE 136
 C_SCHEME_END_OF_LIST 136
 C_SCHEME_FALSE 136
 C_SCHEME_TRUE 136
 C_SIZEOF_FLONUM 137
 C_SIZEOF_INTERNED_SYMBOL 137
 C_SIZEOF_LIST 137
 C_SIZEOF_LOCATIVE 137
 C_SIZEOF_PAIR 137
 C_SIZEOF_POINTER 137
 C_SIZEOF_STRING 137
 C_SIZEOF_TAGGED_POINTER 137
 C_SIZEOF_VECTOR 137
 C_string 136
 C_string2 137
 C_symbol_value 138
 C_unfix 137
 C_vector 137
 call-with-input-pipe 70
 call-with-input-string 52
 call-with-output-pipe 70
 call-with-output-string 52
 call/cc 47
 case-lambda 26
 case-sensitive 35
 change-directory 69
 change-file-mode 76
 change-file-owner 76
 char-name 46
 chicken-version 42
 CHICKEN_apply 119
 CHICKEN_apply_to_string 119

CHICKEN_delete_gc_root 121
 CHICKEN_eval 119
 CHICKEN_eval_string 119
 CHICKEN_eval_string_to_string 119
 CHICKEN_eval_to_string 119
 CHICKEN_gc_root_ref 121
 CHICKEN_gc_root_set 121
 CHICKEN_get_error_message 120
 CHICKEN_global_lookup 121
 CHICKEN_global_ref 121
 CHICKEN_global_set 121
 CHICKEN_initialize 117
 CHICKEN_invoke 117
 CHICKEN_is_running 117
 CHICKEN_load 120
 CHICKEN_new_gc_root 121
 CHICKEN_parse_command_line 116
 CHICKEN_read 119
 CHICKEN_run 117
 CHICKEN_yield 120
 chop 51
 class-cpl 103
 class-direct-slots 103
 class-direct-supers 103
 class-name 103
 class-of 103
 class-slots 103
 clear-hash-table! 53
 close-input-pipe 70
 close-output-pipe 70
 command-line-arguments 35
 complement 60
 compose 60
 compress 51
 compress-literals 33
 compute-apply-generic 104
 compute-apply-methods 104
 compute-cpl 104
 compute-getter-and-setter 104
 compute-method-more-specific? 104
 compute-methods 104
 compute-slots 105
 conc 58
 cond-expand 31
 condition-case 40
 conjoin 60
 constantly 60
 cpu-time 44
 create-directory 69
 create-fifo 71
 create-pipe 70
 create-symbolic-link 75
 create-temporary-file 87
 critical-section 31
 current-directory 69
 current-effective-group-id 76
 current-effective-user-id 76
 current-environment 79

current-error-port 38
 current-group-id 76
 current-milliseconds 44
 current-process-id 74
 current-seconds 44
 current-user-id 76
 cut 27
 cute 27

D

declare 32
 decompose-pathname 86
 define-class 101
 define-const-structure 63
 define-constant 28
 define-embedded 116
 define-entry-point 116
 define-external 122
 define-foreign-record 110
 define-foreign-type 109
 define-foreign-variable 109
 define-generic 101
 define-inline 29
 define-location 123
 define-macro 29
 define-method 102
 define-reader-ctor 50
 define-record 30
 define-record-printer 30
 define-record-type 30
 define-structure 63
 define-values 27
 delete-directory 69
 delete-file 38
 delete-file* 87
 describe-object 105
 destructor-activate! 160
 destructor-atexit! 160
 destructor-clear! 160
 destructor-dump 160
 directory 69
 directory? 69
 disable-interrupts 33, 44
 disjoint 60
 duplicate-filenos 71
 dynamic-load-libraries 35

E

enable-interrupts 44
 enable-warnings 44
 end-of-file 38
 ensure 31
 errno 42
 errno/acces 81
 errno/again 81
 errno/badf 81

errno/busy	81	expect-tolerance-result-result-ref	157
errno/child	81	expect-tolerance-result-rhs-eval-ref ..	158
errno/fault	81	expect-tolerance-result-rhs-uneval-ref	
errno/intr	81	158
errno/invalid	81	expect-tolerance-result-specific-ref	157
errno/io	81	expect-tolerance-result-warning-ref	158
errno/isdir	81	expect-tolerance-result-warning?	158
errno/mfile	81	expect-tolerance-result?	157
errno/noent	81	expect-true	150
errno/noexec	81	expect-zero	150
errno/nomem	81	export	33
errno/nospc	81	extend-procedure	93
errno/notdir	81	extended-bindings	34
errno/perm	81	extended-procedure?	94
errno/pipe	81	extension-info	50
errno/rofs	81		
errno/spipe	81	F	
errno/srch	81	f32vector->byte-vector	61
errno/wouldblock	81	f64vector->byte-vector	61
error	44	features	39
eval	51	fifo?	71
eval-handler	35	file-close	71
eval-when	31	file-execute-access?	76
executable-byte-vector->procedure	95	file-exists?	38
exit	42	file-lock	77
exit-handler	35	file-lock/blocking	77
expect-eq?	151	file-mkstemp	72
expect-equal?	152	file-modification-time	73
expect-equivalence-result-lhs-eval-ref		file-open	71
.....	156	file-owner	75
expect-equivalence-result-message-ref ...	156	file-permissions	76
expect-equivalence-result-result-ref	156	file-position	73
expect-equivalence-result-rhs-eval-ref		file-read	72
.....	156	file-read-access?	76
expect-equivalence-result-rhs-uneval-ref		file-select	72
.....	156	file-size	73
expect-equivalence-result-specific-ref ..	156	file-test-lock	77
expect-equivalence-result-warning-ref ...	157	file-truncate	74
expect-equivalence-result-warning?	157	file-unlock	78
expect-equivalence-result?	156	file-write	72
expect-eqv?	151	file-write-access?	76
expect-false	151	fileno/stderr	72
expect-near?	152	fileno/stdin	72
expect-negative	153	fileno/stdout	72
expect-nonzero	150	find-files	82
expect-positive	152	fixnum-arithmetic	34
expect-result-eval-ref	155	fixnum?	37
expect-result-message-ref	155	flatten	52
expect-result-result-ref	155	flip	60
expect-result-specific-ref	155	fluid-let	27
expect-result-uneval-ref	155	flush-output	38
expect-result-warning-ref	155	for-each-argv-line	87
expect-result-warning?	155	for-each-line	87
expect-result?	155	force-finalizers	36
expect-tolerance-result-lhs-eval-ref ..	157	foreign-callback-lambda	111
expect-tolerance-result-lhs-tol-eval-ref		foreign-callback-lambda*	111
.....	158	foreign-callback-wrapper	122
expect-tolerance-result-message-ref	157		

foreign-code 109
 foreign-declare 33
 foreign-lambda 111
 foreign-lambda* 111
 foreign-parse 33
 foreign-value 109
 format 68
 fprintf 53
 free 91
 fx* 37
 fx+ 37
 fx- 37
 fx/ 37
 fx< 37
 fx<= 37
 fx= 37
 fx> 37
 fx>= 37
 fxmax 37
 fxmin 37
 fxmod 37
 fxneg 37

G

gc 45
 generic-methods 103
 gensym 46
 get 53
 get-host-name 82
 get-keyword 40
 get-line-number 49
 get-output-string 39
 getenv 42
 glob 69
 global-bound? 98
 global-ref 98
 global-set! 99
 gloss 161
 gloss-result-message-ref 161
 gloss-result-warning-ref 161
 gloss-result-warning? 161
 gloss-result? 161
 grep 65
 group-information 76

H

hash-table->list 54
 hash-table-count 54
 hash-table-for-each 54
 hash-table-ref 54
 hash-table-remove! 54
 hash-table-set! 54
 hash-table-size 54
 hash-table? 54
 hide 32

I

identity 60
 implicit-exit-handler 36
 include 32
 initialize 105
 initialize-slots 105
 install-extension 141
 install-highlevel-macro-system 147
 install-program 142
 install-script 142
 instance? 102
 interrupts-enabled 33
 intersperse 52
 invalid-procedure-call-handler 100
 invoke-executable-byte-vector 95

J

join 52

K

keyword->string 40
 keyword-style 36
 keyword? 40

L

let*-values 28
 let-location 123
 let-optionals 27
 let-optionals* 27
 let-values 27
 letrec-values 28
 list->byte-vector 96
 list->queue 55
 list-of 61
 load 48
 load-library 48
 load-noisily 48
 load-verbose 36
 location 123
 locative->object 98
 locative-ref 98
 locative-set! 98
 locative? 98

M

machine-type	43
macro?	49
macroexpand	49
macroexpand-1	49
make	102, 142
make-absolute-pathname	86
make-byte-vector	96
make-class	102
make-executable-byte-vector	96
make-generic	102
make-hash-table	54
make-input-port	56
make-locative	98
make-method	102
make-output-port	57
make-parameter	35
make-pathname	86
make-queue	55
make-record-instance	99
make-static-byte-vector	96
make-weak-locative	98
map-file-to-memory	80
match	63
match-define	63
match-error-control	64
match-lambda	63
match-lambda*	63
match-let	63
match-let*	63
match-letrec	63
memory-mapped-file-pointer	80
memory-statistics	45
merge	56
merge!	56
method-procedure	103
method-specializers	103
move-memory!	99

N

no-argc-checks	33
no-bound-checks	33
no-procedure-checks	33
not	33, 34
nth-value	32
null-pointer	91
null-pointer?	91
number-of-bytes	100
number-of-slots	100

O

object->pointer	91
object-become!	100
object-copy	99
object-evict	96
object-evict-to-location	97

object-evicted?	97
object-release	97
object-size	97
object-unevict	97
open-input-file*	73
open-input-pipe	70
open-input-string	39
open-output-file*	73
open-output-pipe	70
open-output-string	39
open/append	73
open/binary	73
open/creat	73
open/excl	73
open/fsync	73
open/noctty	73
open/nonblock	73
open/rdonly	72
open/rdwr	73
open/read	73
open/sync	73
open/text	73
open/trunc	73
open/write	73
open/wronly	73
ormap	46
output-style-human	164

P

parameterize	28
parent-process-id	74
patch	142
pathname-directory	86
pathname-directory-separator	39
pathname-extension	86
pathname-extension-separator	39
pathname-file	86
pathname-replace-directory	86
pathname-replace-extension	87
pathname-replace-file	87
pathname-strip-directory	87
pathname-strip-extension	87
pattern->regexp	65
perm/irgrp	77
perm/iroth	77
perm/irusr	76
perm/irwxg	77
perm/irwxo	77
perm/irwxu	77
perm/isgid	77
perm/isuid	77
perm/isvtx	77
perm/iwgrp	77
perm/iwoth	77
perm/iwusr	77
perm/ixgrp	77
perm/ixoth	77

perm/ixusr	77
pipe/buf	70
pointer->address	91
pointer->object	91
pointer-f32-ref	92
pointer-f32-set!	93
pointer-f64-ref	92
pointer-f64-set!	93
pointer-offset	91
pointer-s16-ref	92
pointer-s16-set!	92
pointer-s32-ref	92
pointer-s32-set!	93
pointer-s8-ref	92
pointer-s8-set!	92
pointer-tag	93
pointer-u16-ref	92
pointer-u16-set!	92
pointer-u32-ref	92
pointer-u32-set!	93
pointer-u8-ref	92
pointer-u8-set!	92
pointer?	91
port->fileno	73
port-name	38
port-position	38
port?	46
pp	57
pretty-print	57
pretty-print-width	57
print	46
print*	46
print-backtrace	44
print-error-message	45
print-object	105
printf	53
println	164
println	163
procedure-data	94
process	75
process-execute	74
process-fork	74
process-run	74
process-signal	75
process-wait	75
project	60
provide	50
provided?	50
put!	54

Q

queue->list	55
queue-add!	55
queue-empty?	55
queue-first	55
queue-last	55
queue-remove!	55

queue?	55
--------------	----

R

random	56
randomize	56
read-all	88
read-file	57
read-line	57
read-lines	57
read-string	57
read-symbolic-link	75
read-token	58
receive	28
record-instance?	100
regexp	65
regexp?	65
register-feature!	39
rename-file	39
repl	48
repl-prompt	36
repository-path	49
require	50
require-at-runtime	142
require-extension	25
reset	45
reset-handler	36
reverse-list->string	46
run	142
run-time-macros	34

S

s16vector->byte-vector	61
s32vector->byte-vector	61
s8vector->byte-vector	61
seconds->local-time	80
seconds->string	81
seconds->utc-time	81
set!-values	28
set-alarm!	78
set-buffering-mode!	82
set-file-position!	74
set-finalizer!	45
set-gc-report!	45
set-port-name!	38
set-procedure-data!	94
set-read-syntax!	50
set-signal-handler!	78
set-signal-mask!	78
set-user-id!	77
setenv	79
shuffle	52
side-effect	162
signal/abrt	79
signal/alrm	79
signal/chld	79
signal/cont	79

signal/fpe	79
signal/hup	79
signal/ill	79
signal/int	79
signal/io	79
signal/kill	79
signal/pipe	79
signal/prof	79
signal/quit	79
signal/segv	79
signal/stop	79
signal/term	78
signal/trap	79
signal/tstp	79
signal/urg	79
signal/usr1	79
signal/usr2	79
signal/vtalm	79
signal/winch	79
signal/xcpu	79
signal/xfsz	79
signum	38
skip	162
skip-result-message-ref	162
skip-result-warning-ref	162
skip-result-warning?	162
skip-result?	162
sleep	75
slot-ref	103
slot-set!	103
software-type	43
software-version	43
sort	56
sort!	56
sorted?	56
sprintf	53
standard-bindings	34
static-byte-vector->pointer	96
strict-reader	36
string->byte-vector	96
string->keyword	40
string->uninterned-symbol	46
string-chop	58
string-compare3	58
string-compare3-ci	58
string-interperse	58
string-match	65
string-match-positions	65
string-search	65
string-search-positions	65
string-split	59
string-split-fields	65
string-substitute	66
string-substitute*	66
string-translate	59
string-translate*	59
sub1	36
subclass?	104

subf32vector	62
subf64vector	62
subs16vector	62
subs32vector	62
subs8vector	62
substring-ci=?	59
substring-index	59
substring-index-ci	59
substring=?	59
subu16vector	62
subu32vector	62
subu8vector	62
switch	29
syntax	142
syntax-error	49
system	43
system*	88
system-information	82

T

tag-pointer	93
tagged-pointer?	93
tail?	52
tcp-abandon-port	89
tcp-accept	88
tcp-accept-ready?	89
tcp-addresses	89
tcp-close	88
tcp-connect	89
tcp-listen	88
tcp-listener-port	89
tcp-listener?	88
terminal-name	82
terminal-port?	82
terminate	158
terminate-result-container-ref	159
terminate-result-message-ref	159
terminate-result-result-ref	159
terminate-result-scope-ref	159
terminate-result?	159
test-case	149
test-case-result-expectations-ref	154
test-case-result-message-ref	154
test-case-result-result-ref	154
test-case-result-warning-ref	154
test-case-result-warning?	154
test-case-result?	154
test-package	148
test-package-result-exps-ref	153
test-package-result-message-ref	153
test-package-result-result-ref	153
test-package-result-warning-ref	154
test-package-result-warning?	153
test-package-result?	153
thread-deliver-signal!	68
thread-quantum	68
thread-quantum-set!	68

time 32
time->string 81
todo 160
todo-result-message-ref 161
todo-result-warning-ref 161
todo-result-warning? 161
todo-result? 160
trace 20
TYPE 34
TYPENAME-SLOTNAME 110
TYPENAME-SLOTNAME-set! 110

U

u16vector->byte-vector 61
u32vector->byte-vector 61
u8vector->byte-vector 61
unadvise 20
unbound-variable-value 100
undefine-macro! 49
unit 34
unless 29
unmap-file-from-memory 80
unregister-feature! 39
unsafe 34
unsetenv 79
untrace 20
use 25
user-information 77

user-options-pass 13
user-pass 13
user-pass-2 13
user-post-analysis-pass 13
user-preprocessor-pass 13
user-read-pass 13
uses 34
usual-integrations 34

V

vector-copy! 47
vector-resize 47
version 142
visit 67
void 47

W

when 30
with-error-output-to-port 58
with-input-from-pipe 70
with-input-from-port 58
with-input-from-string 52
with-output-to-pipe 70
with-output-to-port 58
with-output-to-string 53
write-line 57
write-string 57